



CATÁLOGO de productos

PRODUCT CATALOGUE
CATALOGUE DES PRODUITS
PRODUKTKATALOG

01
VERSIÓN



The image features an abstract design. On the left side, there are several curved, parallel lines in black and red that sweep upwards from the bottom left towards the top right. A large, solid red shape, resembling a parallelogram or a trapezoid, is positioned in the lower right quadrant. The text 'passion for tooling' is written in white, lowercase letters, with a short white vertical bar preceding the word 'passion'.

| passion
for tooling



HOLA
HELLO
BONJOUR
HALLO

Somos una empresa joven pero con una trayectoria importante en el diseño, fabricación, control y distribución de herramienta de corte de metal duro.

Arralbe Tooling is a young company but with a long experience in design, manufacture, measuring and marketing of Solid Carbide Cutting Tools.

Arralbe tooling sl, c'est une jeune société d'une grande trajectoire, spécialisée dans le projet, réalisation et distribution d'outils en carbure monobloc.

Arralbe Tooling ist eine junge Firma. Wir haben jedoch eine große Erfahrung in der Entwicklung, Herstellung, Messung und Vertrieb von VHM Zerspanungswerkzeuge.

	Z1 FRESA FRENTRE RECTO ALUMINIO Serie Normal PÁG 12 Z1 SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Normal Series
	Z1 FRESA FRENTRE RECTO ALUMINIO Serie Larga PÁG 13 Z1 SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Long Series
	Z2 HELICE 45° Serie Normal PÁG 14 Z2 HELICE 45° SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Normal Series
	Z2 HELICE 45° Serie Larga PÁG 15 Z2 HELICE 45° SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Long Series
	Z2 HELICE 45° Serie Normal ZRN PÁG 16 Z2 HELICE 45° ZRN SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Normal Series
	Z2 HELICE 45° Serie Larga ZRN PÁG 17 Z2 HELICE 45° ZRN SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Long Series
	Z3 HELICE 45° Serie Normal PÁG 18 Z3 HELICE 45° SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Normal Series
	Z3 HELICE 45° Serie Larga PÁG 19 Z3 HELICE 45° SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Long Series
	Z3 HELICE 45° Serie Normal ZRN PÁG 20 Z3 HELICE 45° ZRN SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Normal Series
	Z3 HELICE 45° Serie Larga ZRN PÁG 21 Z3 HELICE 45° ZRN SQUARE END MILL FRAISE CYLINDRIQUE EN BOUT LANGLOCHFRÄFER Aluminium Long Series
	Z2 HELICE 40° Esférica Serie Normal PÁG 22 Z2 HELICE 40° BALL NOSE FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE KUGELFRÄSER Aluminium Normal Series
	Z2 HELICE 40° Esférica Serie Larga PÁG 23 Z2 HELICE 40° BALL NOSE FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE KUGELFRÄSER Aluminium Long Series
	Z2 HELICE 40° Esférica ZRN Serie Normal PÁG 24 Z2 HELICE 40° ZRN BALL NOSE FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE KUGELFRÄSER Aluminium Normal Series
	Z2 HELICE 40° Esférica ZRN Serie Larga PÁG 25 Z2 HELICE 40° ZRN BALL NOSE FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE KUGELFRÄSER Aluminium Long Series
	Z3 HELICE 45° Tórica Serie Larga PÁG 26 Z3 HELICE 45° CORNER RADIUS END MILL FRAISE TORIQUE À BOUT HÉMISPHERIQUE TORUSFRÄSER Aluminium Long Series
	Z3 HELICE 45° Tórica ZRN Serie Larga PÁG 27 Z3 HELICE 45° ZRN CORNER RADIUS END MILL FRAISE TORIQUE À BOUT HÉMISPHERIQUE TORUSFRÄSER Aluminium Long Series

**Z2 FRESA FRENTE RECTO. SERIE NORMAL PÁG 30**

Z2 SQUARE END MILL | FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Normal Series

**Z2 FRESA FRENTE RECTO. SERIE LARGA PÁG 32**

Z2 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Long Series

**Z2 FRESA FRENTE RECTO. SERIE EXTRA LARGA..... PÁG 33**

Z2 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Extralong Series

**Z3 FRESA FRENTE RECTO. SERIE NORMAL PÁG 34**

Z3 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Normal Series

**Z3 FRESA FRENTE RECTO. SERIE LARGA PÁG 36**

Z3 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Long Series

**Z4 FRESA FRENTE RECTO. SERIE EXTRA LARGA..... PÁG 37**

Z4 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Extralong Series

**Z4 FRESA FRENTE RECTO. SERIE NORMAL PÁG 38**

Z4 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Normal Series

**Z4 FRESA FRENTE RECTO. SERIE LARGA..... PÁG 40**

Z4 SQUARE END MILL / FRAISE CYLINDRIQUE EN BOUT | LANGLOCHFRÄFER Long Series

**Z6 FRESA MULTILABIO. SERIE NORMAL..... PÁG 42**

Z6 MUTLI FLUTE END MILL | FRAISE CYLINDRIQUE MULTIDENTS | CHAFTFRÄSER MEHRSCHEIDEN Normal Series

**Z6 FRESA MULTILABIO. SERIE LARGA Y EXTRALARGA..... PÁG 43**

Z6 MUTLI FLUTE END MILL | FRAISE CYLINDRIQUE MULTIDENTS | CHAFTFRÄSER MEHRSCHEIDEN Long & Extralong Series

**Z3 & Z4 FRESA SEMIDESBASTE FRENTE RECTO. SERIE NORMAL PÁG 44**

Z3 & Z4 SEMI-ROUGHING END MILL | FRAISE CYLINDRIQUE EN BOUT | SEMI-FINITION SCHRUPPSCHLICHTFRÄFER Normal Series

**Z4 FRESA SEMIDESBASTE FRENTE RECTO. SERIE LARGA PÁG 45**

Z4 SEMI-ROUGHING END MILL | FRAISE CYLINDRIQUE EN BOUT | SEMI-FINITION SCHRUPPSCHLICHTFRÄFER Long Series

**Z2 FRESA FRONTAL CUELLO REBAJADO. MANGO 6..... PÁG 46**

Z2 END MILL | FRAISE CYLINDRIQUE | LANGLOCHFRÄFER Shank 6

**Z4 FRESA FRONTAL CUELLO REBAJADO. MANGO 6..... PÁG 48**

Z4 END MILL | FRAISE CYLINDRIQUE | LANGLOCHFRÄFER Shank 6

**Z2 MICRO FRESA FRONTAL SIN CUELLO. MANGO 4 PÁG 50**

Z2 MICRO END MILL | MICROFRAISE EN BOUT | MIKROLANGLOCHFRÄFER Shank 4

**Z2 MICRO FRESA FRONTAL CUELLO REBAJADO. MANGO 4 PÁG 51**

Z2 MICRO END MILL | MICROFRAISE EN BOUT | MIKROLANGLOCHFRÄFER Shank 4



Z2 FRESAS ESFERICAS Serie Normal	PÁG 54
Z2 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Normal Series	



Z2 FRESAS ESFERICAS Serie Larga	PÁG 56
Z2 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Long Series	



Z2 FRESAS ESFERICAS Serie Extra Larga	PÁG 57
Z2 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Extralong Series	



Z4 FRESAS ESFERICAS Serie Normal	PÁG 58
Z4 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Normal Series	



Z4 FRESAS ESFERICAS Serie Larga	PÁG 59
Z4 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Long Series	



Z2 FRESAS ESFERICAS MANGO 4	PÁG 60
Z2 BALL NOSE END MIL Shank d4 FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Shank 4	



Z2 FRESAS ESFERICAS MANGO 6	PÁG 62
Z2 BALL NOSE END MIL Shank d6 FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Shank 6	



Z2 FRESAS ESFERICAS CÓNICAS	PÁG 64
Z2 BALL NOSE END MIL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER Conical Form	



Z2 FRESAS ESFERICAS CÓNICA 1°	PÁG 66
Z2 BALL NOSE END MIL 1° FRAISE CYLINDRIQUE HÉMISPHERIQUE 1° KUGELFRÄSER 1° Conical Form	



Z2 FRESAS ESFERICAS CONICA 1,5°	PÁG 68
Z2 BALL NOSE END MIL 1,5° FRAISE CYLINDRIQUE HÉMISPHERIQUE 1,5° KUGELFRÄSER 1,5° Conical Form	



Z2 ARRAL-TOP: FRESAS ESFERICAS CILÍNDRICAS	PÁG 70
Z2 ARRAL-TOP: BALL NOSE END MILL FRAISE CYLINDRIQUE HÉMISPHERIQUE KUGELFRÄSER	



Z2 ARRAL-TOP: FRESAS ESFERICAS CÓNICAS 1°	PÁG 71
Z2 ARRAL-TOP: BALL NOSE END MILL 1° FRAISE CYLINDRIQUE HÉMISPHERIQUE 1° KUGELFRÄSER 1°	



Z2 ARRAL-TOP: FRESAS ESFERICAS CÓNICAS 1,5°	PÁG 72
Z2 ARRAL-TOP: BALL NOSE END MILL 1,5° FRAISE CYLINDRIQUE HÉMISPHERIQUE 1,5° KUGELFRÄSER 1,5°	



Z2 FRESAS ESFERICAS MATERIAL DURO Serie Normal.....	PÁG 73
Z2 ARRAL-TOP: BALL NOSE END MILL Hard Cutting 70HRC FRAISE CYLINDRIQUE HÉMISPHERIQUE 70HRC KUGELFRÄSER 70HRC Normal Series	



Z2 FRESAS ESFERICAS MATERIAL DURO Serie Larga	PÁG 74
Z2 ARRAL-TOP: BALL NOSE END MILL Hard Cutting 70HRC FRAISE CYLINDRIQUE HÉMISPHERIQUE 70HRC KUGELFRÄSER 70HRC Long Series	



Z2 MICRO FRESAS ESFERICAS.....	PÁG 75
Z2 MICRO BALL NOSE END MILL MICROFRAISE CYLINDRIQUE HÉMISPHERIQUE MIKROKUGELFRÄSER	



Z2 MICRO FRESAS ESFERICAS Cuello rebajado	PÁG 76
Z2 MICRO BALL NOSE END MILL MICROFRAISE CYLINDRIQUE HÉMISPHERIQUE MIKROKUGELFRÄSER Reduced neck	

**Z2 FRESA TÓRICA Serie Normal..... PÁG 78****Z2** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Normal Series**Z4 FRESA TÓRICA Serie Normal..... PÁG 80****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Normal Series**Z2 FRESA TÓRICA Corte Normal..... PÁG 82****Z2** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Normal Cuting**Z4 FRESA TÓRICA Corte Normal..... PÁG 83****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Normal Cuting**Z2 FRESA TÓRICA Corte Largo..... PÁG 84****Z2** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Long Cuting**Z4 FRESA TÓRICA Corte Largo..... PÁG 86****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Long Cuting**Z2 FRESA TÓRICA Extralarga..... PÁG 88****Z2** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Extralong Series**Z4 FRESA TÓRICA Extralarga..... PÁG 89****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Extralong Series**Z2 FRESA TÓRICA CUELLO-MANGO D6..... PÁG 90****Z2** CORNER RADIUS END MIL SHANK D6 | FRAISE TORIQUE SHANK D6 | TORUSFRÄSER END MILL **Shank 6****Z4 FRESA TÓRICA CUELLO-MANGO D6..... PÁG 94****Z4** CORNER RADIUS END MIL SHANK D6 | FRAISE TORIQUE SHANK D6 | TORUSFRÄSER END MILL **Shank 6****Z2 FRESA TÓRICA CUELLO REBAJADO Serie Larga..... PÁG 96****Z2** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Reduced Neck. Long Series**Z4 FRESA TÓRICA CUELLO REBAJADO Serie Larga..... PÁG 99****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Reduced Neck. Long Series**Z4 FRESA TÓRICA CUELLO REBAJADO Serie Normal..... PÁG 102****Z4** CORNER RADIUS END MIL | FRAISE TORIQUE | TORUSFRÄSER END MILL Reduced Neck. Normal Series**Z2 FRESA TÓRICA CONICA A 1°..... PÁG 104****Z2** CORNER RADIUS END MIL 1° | FRAISE TORIQUE 1° | TORUSFRÄSER END MILL 1°**Z4 FRESA TÓRICA CONICA A 1°..... PÁG 106****Z4** CORNER RADIUS END MIL 1° | FRAISE TORIQUE 1° | TORUSFRÄSER END MILL 1°**Z2 FRESA TÓRICA CONICA A 1,5°..... PÁG 108****Z2** CORNER RADIUS END MIL 1,5° | FRAISE TORIQUE 1,5° | TORUSFRÄSER END MILL 1,5°**Z4 FRESA TÓRICA CONICA A 1,5°..... PÁG 110****Z4** CORNER RADIUS END MIL 1,5° | FRAISE TORIQUE 1,5° | TORUSFRÄSER END MILL 1,5°



Z3 HYPERLINK: FRESA HELICE VARIABLE 35°/38° Económica..... PÁG 112
Z3 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° Eco.



Z4 HYPERLINK: FRESA HELICE VARIABLE 35°/38° Económica..... PÁG 113
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° Eco.



Z4 HYPERLINK: FRESA HELICE VARIABLE 35°/38° WELDOM Económica..... PÁG 114
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° Eco. Weldom



Z4 HYPERLINK: FRESA H.V. 35°/38° Medidas especiales. Económica..... PÁG 115
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° Special Sizes. Eco.



Z4 HYPERLINK: FRESA H.V. 35°/38° Cuello Rebajado. Económica..... PÁG 116
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° R. Neck. Eco.



Z4 HYPERLINK: F. H. V. 35°/38° Cuello Rebajado WELDOM. Económica..... PÁG 117
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° R. Neck. Weldom



Z4 HYPERLINK PLUS: FRESA HELICE VARIABLE 35°/38° Cuello Rebajado PÁG 118
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° R. Neck. Premium



Z4 HYPERLINK PLUS: FRESA H. VARIABLE 35°/38° C. Rebajado WELDOM..... PÁG 119
Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | HÉLICE DIFFÉRENTE 35°-38° | UNGLEICHER DRALLWINKEL 35°-38° R. Neck. Weldom



Z4 HYRUX: FRESA HELICE VARIABLE 43°/45° Alto Rendimiento..... PÁG 120
Z4 HYRUX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° Premium



Z4 HYRUX: FRESA H.V. 43°/45° WELDOM Alto Rendimiento PÁG 121
Z4 HYRUX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° Weldom. Premium



Z4 HYRUX: FRESA H.V. 43°/45° Cuello Rebajado. Alto Rendimiento PÁG 122
Z4 HYRUX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° R. Neck. Premium



Z4 HYRUX: F.H.V. 43°/45° Cuello Rebajado WELDOM Alto Rendimiento..... PÁG 123
Z4 HYRUX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° R. Neck. Weldom



Z4 HYRUX TITANIO: FRESA HELICE VARIABLE 43°/45° PÁG 124
Z4 HYRUX TITANIUM. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45°



Z4 HYRUX TITANIO: FRESA HELICE VARIABLE 43°/45° WELDOM PÁG 125
Z4 HYRUX TITANIUM. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° Weldom



Z4 HYRUX TITANIO: FRESA H. V. 43°/45° Cuello Rebajado..... PÁG 126
Z4 HYRUX TITANIUM. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° R. Neck



Z4 HYRUX TITANIO: FRESA H. V. 43°/45° Cuello Rebajado WELDOM PÁG 127
Z4 HYRUX TITANIUM. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° Weldom



Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Chaflán <55HRC PÁG 128
Z5 HELIX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° <55HRC



Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Chaflán <65HRC PÁG 130
Z5 HELIX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° <65HRC



Z5 HELIX: FRESA H.V. 43°/45° Chaflán <55HRC Refrigeración Central PÁG 132
Z5 HELIX. UNEQUAL HELIX ANGLES 43°-45° | HÉLICE DIFFÉRENTE 43°-45° | UNGLEICHER DRALLWINKEL 43°-45° <55HRC Central Coolant



Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <55HRC PÁG 134
Z5 HELIX. UNEQUAL HELIX ANGLES | HÉLICE DIFFÉRENTE | UNGLEICHER DRALLWINKEL **43°-45° <55HRC**



Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <65HRC PÁG 136
Z5 HELIX. UNEQUAL HELIX ANGLES | HÉLICE DIFFÉRENTE | UNGLEICHER DRALLWINKEL **43°-45° <65HRC**



Z5 HELIX: FRESA H.V. 43°/45° Radio <55HRC Refrigeración central PÁG 138
Z5 HELIX. UNEQUAL HELIX ANGLES | HÉLICE DIFFÉRENTE | UNGLEICHER DRALLWINKEL **43°-45° <55HRC Coolant**



Z4 HYPERBALL: FRESA HÉLICE VARIABLE ESFÉRICA..... PÁG 140
Z4 HYPERBALL. BALL NOSE END MILL | FRAISE CYLINDRIQUE HÉMISPHERIQUE | UNGLEICHER DRALLWINKEL



Z4 HYPERBALL: FRESA HÉLICE VARIABLE ESFÉRICA. Cónica 1,5° PÁG 141
Z4 HYPERBALL. BALL NOSE END MILL 1,5° | FRAISE CYLINDRIQUE HÉMISPHERIQUE 1,5° | UNGLEICHER DRALLWINKEL 1,5°



Z4 FRESA TURBO ALTO AVANCE Serie Normal PÁG 142
Z4 TURBO HIGH FEED END MILL | TURBO FRAISE CYLINDRIQUE DE HAUTE AVANCE | TURBO HOCHVORSCHUBFRÄSER N. Series



Z4 FRESA TURBO ALTO AVANCE Serie Larga PÁG 143
Z4 TURBO HIGH FEED END MILL | TURBO FRAISE CYLINDRIQUE DE HAUTE AVANCE | TURBO HOCHVORSCHUBFRÄSER L. Series



Z4-Z6 FRESA PARA ACHAFLANAR 60° PÁG 144
Z4-Z6 COUNTERSINKER 60° | CHAMFREIN 60° | KEGELSENKER 60°



Z4-Z6 FRESA PARA ACHAFLANAR 90° PÁG 145
Z4-Z6 COUNTERSINKER 90° | CHAMFREIN 90° | KEGELSENKER 90°



Z5 TROCOIDAL: FRESA DE ALTO RENDIMIENTO PÁG 146
Z5 TROCHOIDAL. HIGH PERFORMANCE END MILL | FRAISE DE HAUTE PERFORMANCE
 UNGLEICHER DRALLWINKEL HOCHLEISTUNGSBEARBEITUNG

6

BROCAS de metal duro

SOLID CARBIDE DRILL | FORET EN CARBURE MONOBLOC | VOLLHARTMETALLBOHRER



3XD BROCA METAL DURO DIN6537K PÁG 148
3XD SOLID CARBIDE DRILL | FORET EN CARBURE MONOBLOC | VOLLHARTMETALLBOHRER **DIN6537K**



5XD BROCA METAL DURO DIN6537L Con refrigeración PÁG 152
5XD SOLID CARBIDE DRILL | FORET EN CARBURE MONOBLOC | VOLLHARTMETALLBOHRER **DIN6537L Internal Coolant**



5XD BROCA METAL DURO DIN6537L PÁG 156
5XD SOLID CARBIDE DRILL | FORET EN CARBURE MONOBLOC | VOLLHARTMETALLBOHRER **DIN6537L**



8XD BROCA METAL DURO DIN6537L Con refrigeración PÁG 160
8XD SOLID CARBIDE DRILL | FORET EN CARBURE MONOBLOC | VOLLHARTMETALLBOHRER **DIN6537L Internal Coolant**

7

ESCARIADORES

REAMERS | ALÉSOIRS | REIBAHLEN



ESCARIADOR METAL DURO Sin recubrimiento PÁG 166
ARRALBE HELIX 10° | H7

PAUTAS de corte PÁG 170
 CUTTING PARAMETERS | PARAMÈTRES DE COUPE | SCHNITTDATEN



01

FRESAS para aluminio

END MILL FOR ALUMINIUM
FRAISE POUR ALUMINIUM
FRÄSER FÜR ALUMINIUM

I Z1 FRESA FRENTE RECTO ALUMINIO Serie Normal

SIN RECUBRIMIENTO

EN Z1 SQUARE END MILL ALUMINIUM | UNCOATED | Normal Series

FR Z1 FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Normale


DE Z1 LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Normale

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
1 Flute (Z1)	Dc	d	Lc	L	
A-SEM1030	3	3	8	38	12,70 €
A-SEM1040	4	4	11	50	14,55 €
A-SEM1050	5	5	13	50	17,96 €
A-SEM1060	6	6	16	50	19,23 €
A-SEM1080	8	8	19	60	27,42 €
A-SEM1100	10	10	22	75	42,30 €
A-SEM1120	12	12	26	75	57,15 €

I Z1 FRESA FRENTA RECTO ALUMINIO Serie Larga SIN RECUBRIMIENTO

EN Z1 SQUARE END MILL ALUMINIUM | UNCOATED | Long Series

FR Z1 FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Longue


DE Z1 LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE LARGA



					Precio €
1 Flute (Z1)	Dc	d	Lc	L	
A-SEM1060L	6	6	25	80	22,45 €
A-SEM1080L	8	8	35	90	36,68 €
A-SEM1100L	10	10	45	100	54,72 €
A-SEM1120L	12	12	50	100	68,37 €

I Z2 HELICE 45° Serie Normal

FRESA FRENTE RECTO ALUMINIO

EN Z2 HELICE 45° SQUARE END MILL ALUMINIUM | UNCOATED | Normal Series,
FR Z2 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Normale
DE Z2 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Normale

- ES** Aluminio, cobre, latón, bronce y termoplásticos.
- EN** Aluminium, copper, brass, bronze and thermoplastics.
- FR** Aluminium, cuivre, laiton, bronze et thermoplastiques.
- DE** Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SEM2030	3	6	8	50	13,50 €
A-SEM2040	4	6	11	50	13,50 €
A-SEM2050	5	6	13	50	13,50 €
A-SEM2060	6	6	16	50	13,50 €
A-SEM2080	8	8	19	60	17,30 €
A-SEM2100	10	10	25	72	25,95 €
A-SEM2120	12	12	30	75	35,60 €
A-SEM2140	14	14	35	84	49,20 €
A-SEM2160	16	16	40	92	70,30 €
A-SEM2200	20	20	45	100	103,70 €

I Z2 HELICE 45° Serie Larga

FRESA FRENTE RECTO ALUMINIO

EN Z2 HELICE 45° SQUARE END MILL ALUMINIUM | UNCOATED | Long Series

FR Z2 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Longue



DE Z2 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.




SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SEM2060L	6	6	25	80	17,70 €
A-SEM2080L	8	8	35	90	23,95 €
A-SEM2100L	10	10	45	100	34,60 €
A-SEM2120L	12	12	50	100	48,70 €
A-SEM2140L	14	14	65	165	75,10 €
A-SEM2160L	16	16	75	150	94,90 €
A-SEM2200L	20	20	80	150	141,00 €

Z2 HELICE 45° Serie Normal ZRN

FRESA FRENTA RECTO ALUMINIO / RECUBRIMIENTO ZRN

EN Z2 HELICE 45° SQUARE END MILL ALUMINIUM | ZRN COATED | Normal Series**FR** Z2 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | REVÊTEMENT ZRN | Normale**DE** Z2 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Normale**ES** Aluminio, cobre, latón, bronce y termoplásticos.**EN** Aluminium, copper, brass, bronze and thermoplastics.**FR** Aluminium, cuivre, laiton, bronze et thermoplastiques.**DE** Aluminium, kupfer, messing, bronze und kunststoffe.**SERIE NORMAL**

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SEM2030Z	3	6	8	50	16,90 €
A-SEM2040Z	4	6	11	50	16,90 €
A-SEM2050Z	5	6	13	50	16,90 €
A-SEM2060Z	6	6	16	50	16,90 €
A-SEM2080Z	8	8	19	60	22,20 €
A-SEM2100Z	10	10	25	72	31,40 €
A-SEM2120Z	12	12	30	75	42,75 €
A-SEM2140Z	14	14	35	84	57,30 €
A-SEM2160Z	16	16	40	92	79,50 €
A-SEM2200Z	20	20	45	100	115,70 €

I Z2 HELICE 45° Serie Larga ZRN

FRESA FRENTA RECTO ALUMINIO / RECUBRIMIENTO ZRN

EN Z2 HELICE 45° SQUARE END MILL ALUMINIUM | ZRN COATED | Long Series

FR Z2 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | REVÊTEMENT ZRN | Longue


DE Z2 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.





SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SEM2060LZ	6	6	25	80	22,23 €
A-SEM2080LZ	8	8	35	90	29,98 €
A-SEM2100LZ	10	10	45	100	41,70 €
A-SEM2120LZ	12	12	50	100	57,90 €
A-SEM2140LZ	14	14	65	165	85,50 €
A-SEM2160LZ	16	16	75	150	106,70 €
A-SEM2200LZ	20	20	80	150	157,00 €

Z3 HELICE 45° Serie Normal

FRESA FRENTA RECTO ALUMINIO / SIN RECUBRIMIENTO

EN Z3 HELICE 45° SQUARE END MILL ALUMINIUM | UNCOATED | Normal Series**FR** Z3 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Normale**DE** Z3 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Normale**ES** Aluminio, cobre, latón, bronce y termoplásticos.**EN** Aluminium, copper, brass, bronze and thermoplastics.**FR** Aluminium, cuivre, laiton, bronze et thermoplastiques.**DE** Aluminium, kupfer, messing, bronze und kunststoffe.**SERIE NORMAL**

Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
A-SEM3030	3	6	8	50	13,50 €
A-SEM3040	4	6	11	50	13,50 €
A-SEM3050	5	6	13	50	13,50 €
A-SEM3060	6	6	16	50	13,50 €
A-SEM3080	8	8	19	60	17,30 €
A-SEM3100	10	10	25	72	25,95 €
A-SEM3120	12	12	30	75	35,60 €
A-SEM3140	14	14	35	84	49,20 €
A-SEM3160	16	16	40	92	70,30 €
A-SEM3200	20	20	45	100	103,70 €

I Z3 HELICE 45° Serie Larga

FRESA FRENTA RECTO ALUMINIO / SIN RECUBRIMIENTO

EN Z3 HELICE 45° SQUARE END MILL ALUMINIUM | UNCOATED | Long Series

FR Z3 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | NO REVÊTEMENT | Longue



DE Z3 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronce und kunststoffe.



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
A-SEM3060L	6	6	25	80	17,70 €
A-SEM3080L	8	8	35	90	23,95 €
A-SEM3100L	10	10	45	100	34,60 €
A-SEM3120L	12	12	50	100	48,70 €
A-SEM3140L	14	14	65	165	75,10 €
A-SEM3160L	16	16	75	150	94,90 €
A-SEM3200L	20	20	80	150	141,00 €

I Z3 HELICE 45° Serie Normal ZRN

FRESA FRENTA RECTO ALUMINIO / RECUBRIMIENTO ZRN

EN Z3 HELICE 45° SQUARE END MILL ALUMINIUM | ZRN COATED | Normal Series

FR Z3 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | REVÊTEMENT ZRN | Normale



DE Z3 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Normale

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
A-SEM3030Z	3	6	8	50	16,90 €
A-SEM3040Z	4	6	11	50	16,90 €
A-SEM3050Z	5	6	13	50	16,90 €
A-SEM3060Z	6	6	16	50	16,90 €
A-SEM3080Z	8	8	19	60	22,20 €
A-SEM3100Z	10	10	25	72	31,40 €
A-SEM3120Z	12	12	30	75	42,75 €
A-SEM3140Z	14	14	35	84	57,30 €
A-SEM3160Z	16	16	40	92	79,50 €
A-SEM3200Z	20	20	45	100	115,70 €

I Z3 HELICE 45° Serie Larga ZRN

FRESA FRENTA RECTO ALUMINIO / RECUBRIMIENTO ZRN

EN Z3 HELICE 45° SQUARE END MILL ALUMINIUM | ZRN COATED | Long Series

FR Z3 HELICE 45° FRAISE CYLINDRIQUE EN BOUT ALUMINIUM | REVÊTEMENT ZRN | Longue



DE Z3 HELICE 45° LANGLOCHFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
A-SEM3060LZ	6	6	25	80	22,23 €
A-SEM3080LZ	8	8	35	90	29,98 €
A-SEM3100LZ	10	10	45	100	41,70 €
A-SEM3120LZ	12	12	50	100	57,90 €
A-SEM3140LZ	14	14	65	165	85,50 €
A-SEM3160LZ	16	16	75	150	106,70 €
A-SEM3200LZ	20	20	80	150	157,00 €

I Z2 HELICE 40° Serie Normal

FRESA ESFERICA ALUMINIO / SIN RECUBRIMIENTO

EN Z2 BALL NOSE ALUMINIUM END MILL | UNCOATED | Normal Series

FR Z2 FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | NO REVÊTEMENT | Normale


DE Z2 KUGELFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Normale

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SBM2030	3	6	6	50	14,75 €
A-SBM2040	4	6	8	50	14,75 €
A-SBM2050	5	6	10	50	14,75 €
A-SBM2060	6	6	12	50	14,75 €
A-SBM2080	8	8	15	60	18,77 €
A-SBM2100	10	10	20	72	27,85 €
A-SBM2120	12	12	24	75	38,25 €
A-SBM2140	14	14	26	83	52,95 €
A-SBM2160	16	16	30	92	75,60 €
A-SBM2200	20	20	40	100	112,70 €

I Z2 HELICE 40° Serie Larga

FRESA ESFERICA ALUMINIO / SIN RECUBRIMIENTO

EN Z2 BALL NOSE ALUMINIUM END MILL | UNCOATED | Long Series

FR Z2 FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | NO REVÊTEMENT | Longue


DE Z2 KUGELFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE LARGA

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
A-SBM2060L	6	6	5,5	35	12	80	19,20 €
A-SBM2080L	8	8	7,5	35	15	90	27,15 €
A-SBM2100L	10	10	9,5	45	20	100	39,75 €
A-SBM2120L	12	12	11,5	50	24	100	54,50 €
A-SBM2160L	16	16	15,5	92	30	150	106,85 €
A-SBM2200L	20	20	19,5	92	40	150	155,90 €

Z2 HELICE 40° ZRN Serie Normal

FRESA ESFERICA ALUMINIO / RECUBRIMIENTO ZRN

EN Z2 HELICE 40° BALL NOSE ALUMINIUM END MILL | ZRN COATED | Normal Series.**FR** Z2 HELICE 40° FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | REVÊTEMENT ZRN | Normale**DE** Z2 HELICE 40° KUGELFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Normale**ES** Aluminio, cobre, latón, bronce y termoplásticos.**EN** Aluminium, copper, brass, bronze and thermoplastics.**FR** Aluminium, cuivre, laiton, bronze et thermoplastiques.**DE** Aluminium, kupfer, messing, bronze und kunststoffe.**ZRN****SERIE NORMAL**

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
A-SBM2030Z	3	6	6	50	18,15 €
A-SBM2040Z	4	6	8	50	18,15 €
A-SBM2050Z	5	6	10	50	18,15 €
A-SBM2060Z	6	6	12	50	18,15 €
A-SBM2080Z	8	8	15	60	23,67 €
A-SBM2100Z	10	10	20	72	33,30 €
A-SBM2120Z	12	12	24	75	45,40 €
A-SBM2140Z	14	14	26	83	61,05 €
A-SBM2160Z	16	16	30	92	84,80 €
A-SBM2200Z	20	20	40	100	124,70 €

I Z2 HELICE 40° ZRN Serie Larga

FRESA ESFERICA ALUMINIO / RECUBRIMIENTO ZRN

EN Z2 HELICE 40° BALL NOSE ALUMINIUM END MILL | ZRN COATED | Long Series

FR Z2 HELICE 40° FRAISE CYLINDRIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | REVÊTEMENT ZRN | Longue

DE Z2 HELICE 40° KUGELFRÄSER ALUMINIUM | BESCHICHTUNG ZRN | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



ZRN



SERIE LARGA

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
A-SBM2060LZ	6	6	5,5	35	12	80	23,75 €
A-SBM2080LZ	8	8	7,5	35	15	90	33,15 €
A-SBM2100LZ	10	10	9,5	45	20	100	46,85 €
A-SBM2120LZ	12	12	11,5	50	24	100	63,70 €
A-SBM2160LZ	16	16	15,5	92	30	150	117,65 €
A-SBM2200LZ	20	20	19,5	92	40	150	171,90 €

I Z3 HELICE 45° Serie Larga

FRESA TÓRICA ALUMINIO / SIN RECUBRIMIENTO

EN Z3 HELICE 45° CORNER RADIUS ALUMINIUM END MILL | UNCOATED | Long Series

FR Z3 HELICE 45° FRAISE TORIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | NO REVÊTEMENT | Longue



DE Z3 HELICE 45° TORUSFRÄSER ALUMINIUM | OHNE BESCHICHTUNG | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



SERIE LARGA SIN RECUBRIMIENTO

Ref.	Dimensiones (mm)					Precio €
3 Flutes (Z3)	Dc	d	R	Lc	L	
A-SEM3060L-R0,5	6	6	0,5	25	80	21,75 €
A-SEM3060L-R1	6	6	1	25	80	21,75 €
A-SEM3080L-R0,5	8	8	0,5	35	90	29,95 €
A-SEM3080L-R1	8	8	1	35	90	29,95 €
A-SEM3100L-R0,5	10	10	0,5	45	100	43,85 €
A-SEM3100L-R1	10	10	1	45	100	43,85 €
A-SEM3100L-R2	10	10	2	45	100	43,85 €
A-SEM3100L-R3	10	10	3	45	100	43,85 €
A-SEM3120L-R0,5	12	12	0,5	50	110	59,80 €
A-SEM3120L-R1	12	12	1	50	110	59,80 €
A-SEM3120L-R2,5	12	12	2,5	50	110	59,80 €
A-SEM3120L-R4	12	12	4	50	110	59,80 €
A-SEM3160L-R1	16	16	1	50	110	99,55 €
A-SEM3160L-R2,5	16	16	2,5	50	110	99,55 €
A-SEM3160L-R4	16	16	4	50	110	99,55 €
A-SEM3200L-R2,5	20	20	2,5	50	130	149,23 €
A-SEM3200L-R4	20	20	4	50	130	149,23 €

Z3 HELICE 45° ZRN Serie Larga

FRESA TÓRICA ALUMINIO / RECUBRIMIENTO ZRN

EN Z3 HELICE 45° CORNER RADIUS ALUMINIUM END MILL | ZRN COATED | Long Series

FR Z3 HELICE 45° FRAISE TORIQUE À BOUT HÉMISPHERIQUE ALUMINIUM | REVÊTEMENT ZRN | Longue


DE Z3 HELICE 45° TORUSFRÄSER ALUMINIUM | OHNE BESCHICHTUNG ZRN | Lange

ES Aluminio, cobre, latón, bronce y termoplásticos.

EN Aluminium, copper, brass, bronze and thermoplastics.

FR Aluminium, cuivre, laiton, bronze et thermoplastiques.

DE Aluminium, kupfer, messing, bronze und kunststoffe.



ZRN



SERIE LARGA ZRN

Ref.	Dimensiones (mm)					Precio €
3 Flutes (Z3)	Dc	d	R	Lc	L	
A-SEM3060L-R0,5_Z	6	6	0,5	25	80	26,25 €
A-SEM3060L-R1_Z	6	6	1	25	80	26,25 €
A-SEM3080L-R0,5_Z	8	8	0,5	35	90	35,92 €
A-SEM3080L-R1_Z	8	8	1	35	90	35,92 €
A-SEM3100L-R0,5_Z	10	10	0,5	45	100	50,95 €
A-SEM3100L-R1_Z	10	10	1	45	100	50,95 €
A-SEM3100L-R2_Z	10	10	2	45	100	50,95 €
A-SEM3100L-R3_Z	10	10	3	45	100	50,95 €
A-SEM3120L-R0,5_Z	12	12	0,5	50	110	69,30 €
A-SEM3120L-R1_Z	12	12	1	50	110	69,30 €
A-SEM3120L-R2,5_Z	12	12	2,5	50	110	69,30 €
A-SEM3120L-R4_Z	12	12	4	50	110	69,30 €
A-SEM3160L-R1_Z	16	16	1	50	110	110,70 €
A-SEM3160L-R2,5_Z	16	16	2,5	50	110	110,70 €
A-SEM3160L-R4_Z	16	16	4	50	110	110,70 €
A-SEM3200L-R2,5_Z	20	20	2,5	50	130	165,20 €
A-SEM3200L-R4_Z	20	20	4	50	130	165,20 €



02

FRESAS de frente recto

SQUARE END MILL
FRAISE CYLINDRIQUE EN BOUT
LANGLOCHFRÄSER

I Z2 FRESA FRENTE RECTO Serie Normal

EN Z2 SQUARE END MILL | Normal Series

FR Z2 FRAISE CYLINDRIQUE EN BOUT | Normale


DE Z2 LANGLOCHFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SEM2010-d3	1	3	3	38	8,47 €
H-SEM2010-d4	1	4	3	50	9,35 €
H-SEM2015-d3	1,5	3	4	38	8,47 €
H-SEM2015-d4	1,5	4	4	50	9,35 €
H-SEM2020-d3	2	3	6	38	8,47 €
H-SEM2020-d4	2	4	6	50	9,35 €
H-SEM2025-d3	2,5	3	8	38	8,47 €
H-SEM2025-d4	2,5	4	8	50	9,35 €
H-SEM2030-d3	3	3	8	38	8,47 €
H-SEM2030-d4	3	4	8	50	9,35 €
H-SEM2030-d6	3	6	8	50	13,25 €
H-SEM2035-d4	3,5	4	11	50	9,35 €
H-SEM2040	4	4	11	50	9,35 €
H-SEM2040-d6	4	6	11	50	13,25 €
H-SEM2045-d6	4,5	6	11	50	13,25 €
H-SEM2050	5	5	13	50	11,81 €

I Z2 FRESA FRENTE RECTO Serie Normal

EN Z2 SQUARE END MILL | Normal Series

FR Z2 FRAISE CYLINDRIQUE EN BOUT | Normale

DE Z2 LANGLOCHFRÄSER | Normale



Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SEM2050-d6	5	6	13	50	13,25 €
H-SEM2055	5,5	6	16	50	13,25 €
H-SEM2060	6	6	16	50	13,25 €
H-SEM2063	6,35	8	19	60	18,65 €
H-SEM2065	6,5	8	19	60	18,65 €
H-SEM2070	7	8	19	60	18,65 €
H-SEM2075	7,5	8	19	60	18,65 €
H-SEM2080	8	8	19	60	16,96 €
H-SEM2085	8,5	10	22	72	27,60 €
H-SEM2090	9	10	22	72	27,60 €
H-SEM2095	9,5	10	22	72	27,60 €
H-SEM2100	10	10	22	72	25,09 €
H-SEM2105	10,5	12	26	75	37,77 €
H-SEM2110	11	12	26	75	37,77 €
H-SEM2120	12	12	26	75	34,34 €
H-SEM2125	12,5	14	30	84	52,78 €
H-SEM2130	13	14	30	84	52,78 €
H-SEM2140	14	14	30	84	47,98 €
H-SEM2150	15	16	32	92	75,15 €
H-SEM2160	16	16	32	92	68,32 €
H-SEM2170	17	18	38	100	92,36 €
H-SEM2180	18	18	38	100	87,96 €
H-SEM2190	19	20	38	100	104,74 €
H-SEM2200	20	20	38	100	99,75 €
H-SEM2220	22	22	38	100	132,50 €
H-SEM2250	25	25	45	100	162,50 €

I Z2 FRESA FRENTE RECTO Serie Larga

EN Z2 SQUARE END MILL | Long Series

FR Z2 FRAISE CYLINDRIQUE EN BOUT | Longue

DE Z2 LANGLOCHFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SEM2010L	1	3	5	60	10,95 €
H-SEM2020L	2	3	10	60	10,95 €
H-SEM2030L	3	3	15	60	10,95 €
H-SEM2040L	4	4	20	80	11,79 €
H-SEM2050L	5	5	25	80	14,59 €
H-SEM2060L	6	6	25	80	16,95 €
H-SEM2080L	8	8	35	90	23,46 €
H-SEM2100L	10	10	45	100	33,72 €
H-SEM2120L	12	12	50	100	47,23 €
H-SEM2140L	14	14	65	150	73,59 €
H-SEM2160L	16	16	65	150	92,47 €
H-SEM2200L	20	20	70	150	137,85 €
H-SEM2250L	25	25	75	150	263,77 €

I Z2 FRESA FRENTE RECTO Serie Extra Larga


- EN** Z2 SQUARE END MILL | Extra Long Series
FR Z2 FRAISE CYLINDRIQUE EN BOUT | Extra Longue
DE Z2 LANGLOCHFRÄSER | Extra Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



SERIE EXTRA LARGA

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SEM2030LL	3	3	25	75	11,72 €
H-SEM2040LL	4	4	25	100	14,25 €
H-SEM2050LL	5	5	25	100	15,93 €
H-SEM2060LL	6	6	25	100	18,02 €
H-SEM2060XL	6	6	40	100	20,75 €
H-SEM206LLL	6	6	25	150	24,85 €
H-SEM2060XXL	6	6	40	150	28,65 €
H-SEM2080XL	8	8	45	100	27,50 €
H-SEM2080LL	8	8	25	150	32,79 €
H-SEM2080XXL	8	8	45	150	37,77 €
H-SEM2100LL	10	10	38	150	46,23 €
H-SEM2100XL	10	10	50	150	51,25 €
H-SEM2100XXL	10	10	65	150	57,60 €
H-SEM2120LL	12	12	38	150	65,09 €
H-SEM2120XL	12	12	50	150	71,65 €
H-SEM2120XXL	12	12	75	150	78,90 €
H-SEM2120LLL	12	12	38	200	79,82 €

I Z3 FRESA FRENTE RECTO Serie Normal

EN Z3 SQUARE END MILL | Normal Series

FR Z3 FRAISE CYLINDRIQUE EN BOUT | Normale

DE Z3 LANGLOCHFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
H-SEM3010-d3	1	3	3	38	8,47 €
H-SEM3010-d4	1	4	3	50	9,35 €
H-SEM3015-d3	1,5	3	4	38	8,47 €
H-SEM3015-d4	1,5	4	4	50	9,35 €
H-SEM3020-d3	2	3	6	38	8,47 €
H-SEM3020-d4	2	4	6	50	9,35 €
H-SEM3025-d3	2,5	3	8	38	8,47 €
H-SEM3025-d4	2,5	4	8	50	9,35 €
H-SEM3030-d3	3	3	8	38	8,47 €
H-SEM3030-d4	3	4	8	50	9,35 €
H-SEM3030-d6	3	6	8	50	13,25 €
H-SEM3035-d4	3,5	4	8	50	9,35 €
H-SEM3040	4	4	11	50	9,35 €
H-SEM3040-d6	4	6	11	50	13,25 €

I Z3 FRESA FRENTE RECTO Serie Normal

EN Z3 SQUARE END MILL | Normal Series

FR Z3 FRAISE CYLINDRIQUE EN BOUT | Normale

DE Z3 LANGLOCHFRÄSER | Normale



Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
H-SEM3045-d6	4,5	6	11	50	13,25 €
H-SEM3050	5	5	13	50	11,81 €
H-SEM3050-d6	5	6	13	50	13,25 €
H-SEM3055	5,5	6	16	50	13,25 €
H-SEM3060	6	6	16	50	13,25 €
H-SEM3063	6,35	8	19	60	18,65 €
H-SEM3065	6,5	8	19	60	18,65 €
H-SEM3070	7	8	19	60	18,65 €
H-SEM3075	7,5	8	19	60	18,65 €
H-SEM3080	8	8	19	60	16,96 €
H-SEM3085	8,5	10	22	72	27,60 €
H-SEM3090	9	10	22	72	27,60 €
H-SEM3095	9,5	10	22	72	27,60 €
H-SEM3100	10	10	22	72	25,09 €
H-SEM3105	10,5	12	26	75	37,77 €
H-SEM3110	11	12	26	75	37,77 €
H-SEM3120	12	12	26	75	34,34 €
H-SEM3125	12,5	14	30	84	52,78 €
H-SEM3130	13	14	30	84	52,78 €
H-SEM3140	14	14	30	84	47,98 €
H-SEM3150	15	16	32	92	75,15 €
H-SEM3160	16	16	32	92	68,32 €
H-SEM3170	17	18	38	100	92,36 €
H-SEM3180	18	18	38	100	87,96 €
H-SEM3190	19	20	38	100	104,74 €
H-SEM3200	20	20	38	100	99,75 €
H-SEM3220	22	22	38	100	132,50 €
H-SEM3250	25	25	45	100	162,50 €

I Z3 FRESA FRENTE RECTO Serie Larga

EN Z3 SQUARE END MILL | Long Series

FR Z3 FRAISE CYLINDRIQUE EN BOUT | Longue

DE Z3 LANGLOCHFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN




Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	Dc	d	Lc	L	
H-SEM3010L	1	3	5	60	10,95 €
H-SEM3020L	2	3	10	60	10,95 €
H-SEM3030L	3	3	15	60	10,95 €
H-SEM3040L	4	4	20	80	11,79 €
H-SEM3050L	5	5	25	80	14,59 €
H-SEM3060L	6	6	25	80	16,95 €
H-SEM3080L	8	8	35	90	23,46 €
H-SEM3100L	10	10	45	100	33,72 €
H-SEM3120L	12	12	50	100	47,23 €
H-SEM3140L	14	14	65	150	73,59 €
H-SEM3160L	16	16	65	150	92,47 €
H-SEM3200L	20	20	70	150	137,85 €
H-SEM3250L	25	25	75	150	263,77 €

I Z4 FRESA FRENTE RECTO Extra Larga

- EN** Z4 SQUARE END MILL | Extra Long Series
FR Z4 FRAISE CYLINDRIQUE EN BOUT | Extra Longue
DE Z4 LANGLOCHFRÄSER | Extra Lange

- ES** Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.
- EN** Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.
- FR** Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusq'ua 56 HRC.
- DE** Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SEM4030LL	3	3	25	75	11,72 €
H-SEM4030XL	3	3	25	100	12,95 €
H-SEM4040LL	4	4	25	100	14,25 €
H-SEM4050LL	5	5	25	100	15,93 €
H-SEM4060LL	6	6	25	100	18,02 €
H-SEM4060XL	6	6	40	100	20,75 €
H-SEM406LLL	6	6	25	150	24,85 €
H-SEM4060XXL	6	6	40	150	28,65 €
H-SEM4080XL	8	8	45	100	27,50 €
H-SEM4080LL	8	8	25	150	32,79 €
H-SEM4080XXL	8	8	45	150	37,77 €
H-SEM4100LL	10	10	38	150	46,23 €
H-SEM4100XL	10	10	50	150	51,25 €
H-SEM4100XXL	10	10	65	150	57,60 €
H-SEM4120LL	12	12	38	150	65,09 €
H-SEM4120XL	12	12	50	150	71,65 €
H-SEM4120XXL	12	12	75	150	78,90 €
H-SEM4120LLL	12	12	38	200	79,82 €

I Z4 FRESA FRENTE RECTO Serie Normal

EN Z4 SQUARE END MILL | Normal Series

FR Z4 FRAISE CYLINDRIQUE EN BOUT | Normale


DE Z4 LANGLOCHFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SEM4010-d3	1	3	3	38	8,47 €
H-SEM4010-d4	1	4	3	50	9,35 €
H-SEM4015-d3	1,5	3	4	38	8,47 €
H-SEM4015-d4	1,5	4	4	50	9,35 €
H-SEM4020-d3	2	3	6	38	8,47 €
H-SEM4020-d4	2	4	6	50	9,35 €
H-SEM4025-d3	2,5	3	8	38	8,47 €
H-SEM4025-d4	2,5	4	8	50	9,35 €
H-SEM4030-d3	3	3	8	38	8,47 €
H-SEM4030-d4	3	4	8	50	9,35 €
H-SEM4030-d6	3	6	8	50	13,25 €
H-SEM4035-d4	3,5	4	8	50	9,35 €
H-SEM4040	4	4	11	50	9,35 €
H-SEM4040-d6	4	6	11	50	13,25 €
H-SEM4045-d6	4,5	6	11	50	13,25 €
H-SEM4050	5	5	13	50	11,81 €
H-SEM4050-d6	5	6	13	50	13,25 €

I Z4 FRESA FRENTE RECTO Serie Normal



Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SEM4055	5,5	6	16	50	13,25 €
H-SEM4060	6	6	16	50	13,25 €
H-SEM4060S	6	6	22	58	14,77 €
H-SEM4063	6,35	8	19	60	18,65 €
H-SEM4065	6,5	8	19	60	18,65 €
H-SEM4070	7	8	19	60	18,65 €
H-SEM4075	7,5	8	19	60	18,65 €
H-SEM3080	8	8	19	60	16,96 €
H-SEM4085	8,5	10	22	72	27,60 €
H-SEM4090	9	10	22	72	27,60 €
H-SEM4095	9,5	10	22	72	27,60 €
H-SEM4100	10	10	22	72	25,09 €
H-SEM4100S	10	10	32	80	28,50 €
H-SEM4105	10,5	12	26	75	37,77 €
H-SEM4110	11	12	26	75	37,77 €
H-SEM4120	12	12	26	75	34,34 €
H-SEM4120S	12	12	32	75	37,50 €
H-SEM4125	12,5	14	30	84	52,78 €
H-SEM4130	13	14	30	84	52,78 €
H-SEM4140	14	14	30	84	47,98 €
H-SEM4140S	14	14	50	100	52,00 €
H-SEM4150	15	16	32	92	75,15 €
H-SEM4160	16	16	32	92	68,32 €
H-SEM4160S	16	16	50	100	75,25 €
H-SEM4170	17	18	38	100	92,36 €
H-SEM4180	18	18	38	100	87,96 €
H-SEM4180S	18	18	50	100	95,30 €
H-SEM4190	19	20	38	100	104,74 €
H-SEM4200	20	20	38	100	99,75 €
H-SEM4200S	20	20	50	100	107,45 €
H-SEM4220	22	22	38	100	132,50 €
H-SEM4250	25	25	45	100	162,50 €
H-SEM4250S	25	25	55	110	171,70 €

I Z4 FRESA FRENTE RECTO Serie Larga

EN Z4 SQUARE END MILL | Long Series

FR Z4 FRAISE CYLINDRIQUE EN BOUT | Longue


DE Z4 LANGLOCHFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SEM4010L	1	3	5	60	10,95 €
H-SEM4020L	2	3	10	60	10,95 €
H-SEM4030L	3	3	15	60	10,95 €
H-SEM4040L	4	4	20	80	11,79 €
H-SEM4050L	5	5	25	80	14,59 €
H-SEM4060L	6	6	25	80	16,95 €
H-SEM4070L	7	8	35	90	25,80 €
H-SEM4080L	8	8	35	90	23,46 €
H-SEM4090L	9	10	45	100	37,15 €
H-SEM4100L	10	10	45	100	33,72 €
H-SEM4120L	12	12	50	100	47,23 €
H-SEM4140L	14	14	65	150	73,59 €
H-SEM4140LL	14	14	90	150	82,77 €
H-SEM4160L	16	16	65	150	92,47 €
H-SEM4160LL	16	16	90	150	107,00 €
H-SEM4180L	18	18	70	150	123,50 €

I Z4 FRESA FRENTE RECTO Serie Larga

EN Z4 SQUARE END MILL | Long Series

FR Z4 FRAISE CYLINDRIQUE EN BOUT | Longue

DE Z4 LANGLOCHFRÄSER | Lange



Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SEM4200L	20	20	70	150	137,85 €
H-SEM4200LL	20	20	90	150	157,50 €
H-SEM4200XL	20	20	100	165	179,50 €
H-SEM4200XLL	20	20	110	200	225,00 €
H-SEM4250L	25	25	75	150	263,77 €

I Z6 FRESA MULTILABIO Serie Normal

EN Z6 MULTI FLUTE END MILL | Normal Series

FR Z6 FRAISE CYLINDRIQUE MULTIDENTS | Normale

DE Z6 SCHAFTFRÄSER MEHRSCHEIDEN | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 65 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 65 HRC.



ALTIN NANO



Ref.	Dimensiones (mm)				Precio €
6 Flutes (Z6)	Dc	d	Lc	L	
H-HEM4030-Z4	3.0	3	8	38	10,97 €
H-HEM4040-Z4	4.0	4	11	50	12,14 €
H-HEM4050-Z4	5.0	5	13	50	15,35 €
H-HEM6060	6.0	6	16	50	17,82 €
H-HEM6080	8.0	8	19	60	22,03 €
H-HEM6100	10.0	10	22	75	30,72 €
H-HEM6120	12.0	12	26	75	44,98 €
H-HEM6140	14.0	14	32	90	58,06 €
H-HEM6160	16.0	16	32	100	79,22 €
H-HEM6160S	16.0	16	50	100	87,4 €
H-HEM6180	18.0	18	38	100	91,95 €
H-HEM6200	20.0	20	38	100	114,71 €
H-HEM6200S	20.0	20	50	100	123,5 €
H-HEM6250	25.0	25	38	100	195,53 €

Z6 FRESA MULTILABIO Series Larga y Extra Larga

EN Z6 MULTI FLUTE END MILL | Long & Extra Long Series

FR Z6 FRAISE CYLINDRIQUE MULTIDENTS | Longue & Extra Longue


DE Z6 SCHAFTFRÄSER MEHRSCHEIDEN | Lange & Extra Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 65 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 65 HRC.



ALTIN NANO



Ref.	Dimensiones (mm)				Precio €
6 Flutes (Z6)	Dc	d	Lc	L	
H-HEM4030L-Z4	3.0	3	15	60	13,95 €
H-HEM4040L-Z4	4.0	4	20	80	15,72 €
H-HEM4050L-Z4	5.0	5	25	80	18,05 €
H-HEM6060L	6.0	6	25	80	21,89 €
H-HEM6080L	8.0	8	35	90	31,97 €
H-HEM6100L	10.0	10	45	100	43,27 €
H-HEM6120L	12.0	12	50	100	61,82 €
H-HEM6120LL	12.0	12	70	125	76,54 €
H-HEM6140L	14.0	14	65	150	84,03 €
H-HEM6160L	16.0	16	65	150	107,97 €
H-HEM6160LL	16.0	16	100	165	123,23 €
H-HEM6200L	20.0	20	70	150	159,68 €
H-HEM6200LL	20.0	20	100	165	184,19 €
H-HEM6200LLL	20.0	20	135	200	235,42 €
H-HEM6250L	25.0	25	75	150	306,98 €
H-HEM6250LL	25.0	25	100	165	355,42 €
H-HEM6250LLL	25.0	25	140	200	398,55 €
H-HEM6320LL	32.0	32	100	165	498,2 €
H-HEM6320LLL	32.0	32	150	210	597,77 €

I Z3 y Z4 FRESA DE SEMIDESBASTE FRETE RECTO Serie Normal

EN Z3-Z4 SEMI-ROUGHING END MILL | Normal Series

FR Z3-Z4 FRAISE CYLINDRIQUE EN BOUT. SEMI-FINITION | Normale


DE Z3-Z4 SCHRUPPSCHLICHTFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE NORMAL

Ref.	Ref.	Dimensiones (mm)				Precio €
3 Flutes (Z3)	4 Flutes (Z4)	Dc	d	Lc	L	
BW-SEM3060	BW-SEM4060	6	6	16	50	22,98 €
BW-SEM3080	BW-SEM4080	8	8	19	60	31,14 €
	BW-SEM4100	10	10	22	75	47,92 €
	BW-SEM4120	12	12	26	75	65,77 €
	BW-SEM4140	14	14	30	90	116,55 €
	BW-SEM4160	16	16	32	100	149,63 €
	BW-SEM4200	20	20	38	100	224,23 €

I Z4 FRESA DE SEMIDESBASTE FRENTE RECTO Serie Larga


- EN** Z4 SEMI-ROUGHING END MILL | Long Series
FR Z4 FRAISE CYLINDRIQUE EN BOUT. SEMI-FINITION | Longue
DE Z4 SCHRUPPSCHLICHTFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
BW-SEM4060L	6	6	25	80	29,97 €
BW-SEM4080L	8	8	35	90	41,88 €
BW-SEM4100L	10	10	45	100	63,78 €
BW-SEM4120L	12	12	50	100	84,23 €
BW-SEM4160L	16	16	65	150	194,44 €
BW-SEM4200L	20	20	70	150	297,52 €

I Z2 FRESA FRONTAL CUELLO REBAJADO / MANGO 6


EN Z2 END MILLS,
FR Z2 FRAISE CYLINDRIQUE
DE Z2 LANGLOCHFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN NANO



SHANK d6

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
H-SEM2010-05	1	6	0,95	5	1,5	57	18,50 €
H-SEM2010-08	1	6	0,95	8	1,5	57	18,50 €
H-SEM2010-10	1	6	0,95	10	1,5	57	18,50 €
H-SEM2010-12	1	6	0,95	12	1,5	65	19,50 €
H-SEM2010-15	1	6	0,95	15	1,5	65	19,50 €
H-SEM2010-20	1	6	0,95	20	1,5	65	19,50 €
H-SEM2015-05	1,5	6	1,42	5	2	57	18,50 €
H-SEM2015-08	1,5	6	1,42	8	2	57	18,50 €
H-SEM2015-10	1,5	6	1,42	10	2	57	18,50 €
H-SEM2015-12	1,5	6	1,42	12	2	65	19,50 €
H-SEM2015-15	1,5	6	1,42	15	2	65	19,50 €
H-SEM2015-20	1,5	6	1,42	20	2	65	19,50 €
H-SEM2015-25	1,5	6	1,42	25	2	65	19,50 €
H-SEM2020-06	2	6	1,92	6	3	57	18,50 €
H-SEM2020-08	2	6	1,92	8	3	57	18,50 €
H-SEM2020-10	2	6	1,92	10	3	57	18,50 €

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	l1	Lc	L	
H-SEM2020-12	2	6	1,92	12	3	60	19,00 €
H-SEM2020-14	2	6	1,92	14	3	65	19,50 €
H-SEM2020-16	2	6	1,92	16	3	65	19,50 €
H-SEM2020-20	2	6	1,92	20	3	65	19,50 €
H-SEM2020-25	2	6	1,92	25	3	65	19,50 €
H-SEM2020-30	2	6	1,92	30	3	80	23,70 €
H-SEM2020-35	2	6	1,92	35	2	80	23,70 €
H-SEM2020-40	2	6	1,92	40	3	80	23,70 €
H-SEM2020-50	2	6	1,92	50	3	100	25,50 €
H-SEM2025-10	2,5	6	2,4	10	4	57	18,50 €
H-SEM2025-16	2,5	6	2,4	16	4	65	19,50 €
H-SEM2025-20	2,5	6	2,4	20	4	65	19,50 €
H-SEM2025-30	2,5	6	2,4	30	4	80	23,70 €
H-SEM2025-40	2,5	6	2,4	40	4	80	23,70 €
H-SEM2030-09	3	6	2,9	9	5	57	18,50 €
H-SEM2030-12	3	6	2,9	12	5	60	19,00 €
H-SEM2030-15	3	6	2,9	15	5	65	19,50 €
H-SEM2030-20	3	6	2,9	20	5	65	19,50 €
H-SEM2030-25	3	6	2,9	25	5	65	19,50 €
H-SEM2030-30	3	6	2,9	30	5	80	23,70 €
H-SEM2030-35	3	6	2,9	35	5	80	23,70 €
H-SEM2030-40	3	6	2,9	40	5	80	23,70 €
H-SEM2030-50	3	6	2,9	50	5	100	25,50 €
H-SEM2040-10	4	6	3,9	10	6	57	18,50 €
H-SEM2040-12	4	6	3,9	12	6	60	19,00 €
H-SEM2040-16	4	6	3,9	16	6	65	19,50 €
H-SEM2040-20	4	6	3,9	20	6	65	19,50 €
H-SEM2040-25	4	6	3,9	25	6	65	19,50 €
H-SEM2040-30	4	6	3,9	30	6	80	23,70 €
H-SEM2040-35	4	6	3,9	35	6	80	23,70 €
H-SEM2040-40	4	6	3,9	40	6	80	23,70 €
H-SEM2040-50	4	6	3,9	50	6	100	25,50 €
H-SEM2050-12	5	6	4,8	12	7	60	19,00 €
H-SEM2050-20	5	6	4,8	20	7	65	19,50 €
H-SEM2050-30	5	6	4,8	30	7	80	23,70 €
H-SEM2050-40	5	6	4,8	40	7	80	23,70 €
H-SEM2050-50	5	6	4,8	50	7	100	25,50 €

I Z4 FRESA FRONTAL CUELLO REBAJADO / MANGO 6

EN Z4 END MILLS | REDUCED NECK

FR Z4 FRAISE CYLINDRIQUE | REDUCED NECK


DE Z4 LANGLOCHFRÄSER | REDUCED NECK

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN NANO



SHANK d6

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	U/C	U	Lc	L	
H-SEM4020-06	2	6	1,92	6	3	57	18,50 €
H-SEM4020-08	2	6	1,92	8	3	57	18,50 €
H-SEM4020-10	2	6	1,92	10	3	57	18,50 €
H-SEM4020-12	2	6	1,92	12	3	60	19,00 €
H-SEM4020-14	2	6	1,92	14	3	65	19,50 €
H-SEM4020-16	2	6	1,92	16	3	65	19,50 €
H-SEM4020-20	2	6	1,92	20	3	65	19,50 €
H-SEM4020-25	2	6	1,92	25	3	65	19,50 €
H-SEM4020-30	2	6	1,92	30	3	80	23,70 €
H-SEM4020-35	2	6	1,92	35	2	80	23,70 €
H-SEM4020-40	2	6	1,92	40	3	80	23,70 €
H-SEM4020-50	2	6	1,92	50	3	100	25,50 €
H-SEM4025-10	2,5	6	2,4	10	4	57	18,50 €
H-SEM4025-16	2,5	6	2,4	16	4	65	19,50 €

I Z4 FRESA FRONTAL CUELLO REBAJADO / MANGO 6

EN Z4 END MILLS | REDUCED NECK

FR Z4 FRAISE CYLINDRIQUE | REDUCED NECK

DE Z4 LANGLOCHFRÄSER | REDUCED NECK



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	U/C	U	Lc	L	
H-SEM4025-20	2,5	6	2,4	20	4	65	19,50 €
H-SEM4025-30	2,5	6	2,4	30	4	80	23,70 €
H-SEM4025-40	2,5	6	2,4	40	4	80	23,70 €
H-SEM4030-09	3	6	2,9	9	5	57	18,50 €
H-SEM4030-12	3	6	2,9	12	5	60	19,00 €
H-SEM4030-15	3	6	2,9	15	5	65	19,50 €
H-SEM4030-20	3	6	2,9	20	5	65	19,50 €
H-SEM4030-25	3	6	2,9	25	5	65	19,50 €
H-SEM4030-30	3	6	2,9	30	5	80	23,70 €
H-SEM4030-35	3	6	2,9	35	5	80	23,70 €
H-SEM4030-40	3	6	2,9	40	5	80	23,70 €
H-SEM4030-50	3	6	2,9	50	5	100	25,50 €
H-SEM4040-10	4	6	3,9	10	6	57	18,50 €
H-SEM4040-12	4	6	3,9	12	6	60	19,00 €
H-SEM4040-16	4	6	3,9	16	6	65	19,50 €
H-SEM4040-20	4	6	3,9	20	6	65	19,50 €
H-SEM4040-25	4	6	3,9	25	6	65	19,50 €
H-SEM4040-30	4	6	3,9	30	6	80	23,70 €
H-SEM4040-35	4	6	3,9	35	6	80	23,70 €
H-SEM4040-40	4	6	3,9	40	6	80	23,70 €
H-SEM4040-50	4	6	3,9	50	6	100	25,50 €
H-SEM4050-12	5	6	4,8	12	7	60	19,00 €
H-SEM4050-20	5	6	4,8	20	7	65	19,50 €
H-SEM4050-30	5	6	4,8	30	7	80	23,70 €
H-SEM4050-40	5	6	4,8	40	7	80	23,70 €
H-SEM4050-50	5	6	4,8	50	7	100	25,50 €

I Z2 MICROFRESA FRONTAL SIN CUELLO / MANGO 4

EN Z2 MICRO END MILLS | Without Neck

FR Z2 MICROFRAISE CYLINDRIQUE | Without Neck


DE Z2 MIKROLANGLOCHFRÄSER | Without Neck

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN NANO




SIN CUELLO

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	D	d	Lc	L	
M-SEM2002	0,2	4	0,4	50	22,25 €
M-SEM2003	0,3	4	0,6	50	21,22 €
M-SEM2004	0,4	4	0,8	50	19,85 €
M-SEM2005	0,5	4	1	50	18,75 €
M-SEM2006	0,6	4	1,2	50	18,75 €
M-SEM2007	0,7	4	1,4	50	18,75 €
M-SEM2008	0,8	4	1,6	50	18,75 €
M-SEM2009	0,9	4	1,8	50	18,75 €


I Z2 MICROFRESA FRONTAL CUELLO REBAJADO / MANGO 4

- EN** Z2 MICRO END MILLS | REDUCED NECK
FR Z2 MICROFRAISE CYLINDRIQUE | REDUCED NECK
DE Z2 MIKROLANGLOCHFRÄSER | REDUCED NECK

- ES** Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.
- EN** Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.
- FR** Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.
- DE** Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 56 HRC.



ALTIN NANO



CON CUELLO REBAJADO

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	D	d	U/C	U	Lc	L	
H-MEM2005-04	0,5	4	0,48	4	0,7	50	19,95 €
H-MEM2005-06	0,5	4	0,48	6	0,7	50	19,95 €
H-MEM2006-04	0,6	4	0,57	4	0,9	50	19,95 €
H-MEM2006-06	0,6	4	0,57	6	0,9	50	19,95 €
H-MEM2006-08	0,6	4	0,57	8	0,9	50	19,95 €
H-MEM2008-06	0,8	4	0,76	6	1,2	50	19,95 €
H-MEM2008-08	0,8	4	0,76	8	1,2	50	19,95 €
H-MEM2008-10	0,8	4	0,76	10	1,2	50	19,95 €
H-MEM2012-06	1,2	4	1,15	6	1,8	50	13,50 €
H-MEM2012-08	1,2	4	1,15	8	1,8	50	13,50 €
H-MEM2012-10	1,2	4	1,15	10	1,8	50	13,50 €



03

FRESAS esféricas

BALL NOSE END MILL
FRAISE CYLINDRIQUE HÉMISPHERIQUE
KUGELFRÄSER

I Z2 FRESAS ESFERICAS Serie Normal

EN Z2 BALL NOSE END MILL | Normal series

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Normale

DE Z2 KUGELFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SBM2010	1	3	2	38	9,32 €
H-SBM2010-d4	1	4	2	50	10,02 €
H-SBM2015	1,5	3	3	38	9,32 €
H-SBM2015-d4	1,5	4	3	50	10,02 €
H-SBM2020	2	3	4	38	9,32 €
H-SBM2020-d4	2	4	4	50	10,02 €
H-SBM2025	2,5	3	5	38	9,32 €
H-SBM2030	3	3	6	38	9,32 €
H-SBM2030-d4	3	4	6	50	10,02 €
H-SBM2040	4	4	8	50	10,02 €
H-SBM2050	5	5	10	50	12,69 €
H-SBM2060	6	6	12	50	14,22 €
H-SBM2070	7	8	15	60	20,03 €
H-SBM2080	8	8	15	60	18,21 €
H-SBM2100	10	10	20	75	26,92 €
H-SBM2120	12	12	20	75	36,87 €

I Z2 FRESAS ESFERICAS Serie Normal

EN Z2 BALL NOSE END MILL | Normal series

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Normale

DE Z2 KUGELFRÄSER | Normale



Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SBM2140	14	14	25	90	52,78 €
H-SBM2160	16	16	25	100	75,15 €
H-SBM2180	18	18	30	100	94,76 €
H-SBM2200	20	20	30	100	109,73 €

I Z2 FRESAS ESFERICAS Serie Larga

EN Z2 BALL NOSE END MILL | Long series

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Longue

DE Z2 KUGELFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
H-SBM2010L	1	3	0,9	6	2	60	12,05 €
H-SBM2150L	1,5	3	1,4	8	3	60	12,05 €
H-SBM2020L	2	3	1,9	8	3	60	12,05 €
H-SBM2025L	2,5	3	2,4	12	3	60	12,05 €
H-SBM2030L	3	3	–	–	4	60	12,05 €
H-SBM2040L	4	4	–	–	5	80	12,97 €
H-SBM2050L	5	5	–	–	6	80	16,05 €
H-SBM2060L	6	6	–	–	8	80	18,65 €
H-SBM2080L	8	8	–	–	12	100	25,81 €
H-SBM2100L	10	10	–	–	15	100	37,09 €
H-SBM2120L	12	12	–	–	15	100	51,95 €
H-SBM2140L	14	14	–	–	20	150	77,00 €
H-SBM2160L	16	16	–	–	20	150	102,82 €
H-SBM2180L	18	18	–	–	25	150	127,50 €
H-SBM2200L	20	20	–	–	25	150	151,64 €

I Z2 FRESAS ESFERICAS Serie Extra Larga

- EN** Z2 BALL NOSE END MILL | Extra long series
FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Extra Longue
DE Z2 KUGELFRÄSER | Extra Lange

- ES** Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.
EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.
FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.
DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE EXTRA LARGA

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
H-SBM2030LL	3	3	6	75	12,92 €
H-SBM2030XL	3	3	6	100	13,65 €
H-SBM2040LL	4	4	6	100	14,75 €
H-SBM2050LL	5	5	6	100	17,95 €
H-SBM2060LL	6	6	15	100	20,32 €
H-SBM2060LLL	6	6	15	150	27,07 €
H-SBM2060LLLL	6	6	30	200	38,52 €
H-SBM2080LL	8	8	25	150	34,84 €
H-SBM2080LLL	8	8	50	200	51,75 €
H-SBM2100LL	10	10	25	150	49,45 €
H-SBM2100LLL	10	10	50	200	69,45 €
H-SBM2120LL	12	12	25	150	72,33 €
H-SBM2120LLL	12	12	25	200	84,79 €
H-SBM2140LL	14	14	50	200	113,25 €
H-SBM2160LL	16	16	50	200	148,72 €

I Z4 FRESAS ESFERICAS Serie Normal

EN Z4 BALL NOSE END MILL | Normal Series

FR Z4 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Normale

DE Z4 KUGELFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SBM4030	3	3	6	38	9,32 €
H-SBM4040	4	4	8	50	10,02 €
H-SBM4050	5	5	10	50	12,69 €
H-SBM4060	6	6	12	50	14,22 €
H-SBM4080	8	8	15	60	18,21 €
H-SBM4100	10	10	20	75	26,92 €
H-SBM4120	12	12	20	75	36,87 €
H-SBM4140	14	14	25	90	52,78 €
H-SBM4160	16	16	25	100	75,15 €
H-SBM4180	18	18	30	100	94,76 €
H-SBM4200	20	20	30	100	109,73 €


I Z4 FRESAS ESFERICAS Serie Larga

- EN** Z4 BALL NOSE END MILL | Long Series
FR Z4 FRAISE CYLINDRIQUE HÉMISPHERIQUE | Longue
DE Z4 KUGELFRÄSER | Lange

- ES** Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.
EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.
FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.
DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
H-SBM4030L	3	3	4	60	12,05 €
H-SBM4040L	4	4	5	80	12,97 €
H-SBM4050L	5	5	6	80	16,05 €
H-SBM4060L	6	6	8	80	18,65 €
H-SBM4080L	8	8	12	100	25,81 €
H-SBM4100L	10	10	15	100	37,09 €
H-SBM4120L	12	12	15	100	51,95 €
H-SBM4160L	16	16	20	150	102,82 €
H-SBM4200L	20	20	25	150	151,64 €

I Z2 FRESAS ESFERICAS MANGO 4

EN Z2 BALL NOSE END MILL | REDUCED NECK

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SHANK d4

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
H-NBM2010-04-d4	1	4	0,95	4	1,5	50	16,95 €
H-NBM2010-06-d4	1	4	0,95	6	1,5	50	16,95 €
H-NBM2010-08-d4	1	4	0,95	8	1,5	50	16,95 €
H-NBM2010-10-d4	1	4	0,95	10	1,5	50	16,95 €
H-NBM2010-12-d4	1	4	0,95	12	1,5	60	17,90 €
H-NBM2010-16-d4	1	4	0,95	16	1,5	60	17,90 €
H-NBM2010-20-d4	1	4	0,95	20	1,5	60	17,90 €
H-NBM2015-04-d4	1,5	4	1,42	4	2	50	16,95 €
H-NBM2015-06-d4	1,5	4	1,42	6	2	50	16,95 €
H-NBM2015-08-d4	1,5	4	1,42	8	2	50	16,95 €
H-NBM2015-10-d4	1,5	4	1,42	10	2	50	16,95 €
H-NBM2015-12-d4	1,5	4	1,42	12	2	60	17,90 €
H-NBM2015-16-d4	1,5	4	1,42	16	2	60	17,90 €
H-NBM2015-20-d4	1,5	4	1,42	20	2	60	17,90 €
H-NBM2015-25-d4	1,5	4	1,42	25	2	60	17,90 €
H-NBM2020-06-d4	2	4	1,92	6	3	50	16,95 €

I Z2 FRESAS ESFERICAS MANGO 4

EN Z2 BALL NOSE END MILL | REDUCED NECK

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	l1	Lc	L	
H-NBM2020-08-d4	2	4	1,92	8	3	50	16,95 €
H-NBM2020-10-d4	2	4	1,92	10	3	50	16,95 €
H-NBM2020-12-d4	2	4	1,92	12	3	60	17,90 €
H-NBM2020-16-d4	2	4	1,92	16	3	60	17,90 €
H-NBM2020-20-d4	2	4	1,92	20	3	60	17,90 €
H-NBM2020-25-d4	2	4	1,92	25	3	80	21,80 €
H-NBM2020-30-d4	2	4	1,92	30	3	80	21,80 €
H-NBM2020-35-d4	2	4	1,92	35	3	80	21,80 €
H-NBM2020-40-d4	2	4	1,92	40	3	80	21,80 €
H-NBM2030-08-d4	3	4	2,9	8	5	50	16,95 €
H-NBM2030-10-d4	3	4	2,9	10	5	50	16,95 €
H-NBM2030-12-d4	3	4	2,9	12	5	60	17,90 €
H-NBM2030-16-d4	3	4	2,9	16	5	60	17,90 €
H-NBM2030-20-d4	3	4	2,9	20	5	60	17,90 €
H-NBM2030-25-d4	3	4	2,9	25	5	80	21,80 €
H-NBM2030-30-d4	3	4	2,9	30	5	80	21,80 €
H-NBM2030-35-d4	3	4	2,9	35	5	80	21,80 €
H-NBM2030-40-d4	3	4	2,9	40	5	80	21,80 €

I Z2 FRESAS ESFERICAS MANGO 6

EN Z2 BALL NOSE END MILL | REDUCED NECK

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SHANK d6

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
H-NBM2010-U05	1	6	0,95	5	1,5	55	18,95 €
H-NBM2010-U08	1	6	0,95	8	1,5	57	19,50 €
H-NBM2010-U10	1	6	0,95	10	1,5	57	19,50 €
H-NBM2010-U12	1	6	0,95	12	1,5	65	20,40 €
H-NBM2010-U15	1	6	0,95	15	1,5	65	20,40 €
H-NBM2010-U20	1	6	0,95	20	1,5	65	20,40 €
H-NBM2015-U05	1,5	6	1,42	5	2	57	19,50 €
H-NBM2015-U08	1,5	6	1,42	8	2	57	19,50 €
H-NBM2015-U10	1,5	6	1,42	10	2	57	19,50 €
H-NBM2015-U12	1,5	6	1,42	12	2	65	20,40 €
H-NBM2015-U15	1,5	6	1,42	15	2	65	20,40 €
H-NBM2015-U20	1,5	6	1,42	20	2	65	20,40 €
H-NBM2020-U06	2	6	1,92	6	3	57	19,50 €
H-NBM2020-U08	2	6	1,92	8	3	57	19,50 €
H-NBM2020-U10	2	6	1,92	10	3	57	19,50 €
H-NBM2020-U12	2	6	1,92	12	3	57	19,50 €



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	U/C	U	Lc	L	
H-NBM2020-U14	2	6	1,92	14	3	57	19,50 €
H-NBM2020-U16	2	6	1,92	16	3	60	19,98 €
H-NBM2020-U20	2	6	1,92	20	3	60	19,98 €
H-NBM2020-U25	2	6	1,92	25	3	60	19,98 €
H-NBM2020-U30	2	6	1,92	30	3	75	24,55 €
H-NBM2020-U35	2	6	1,92	35	2	75	24,55 €
H-NBM2020-U40	2	6	1,92	40	3	80	24,75 €
H-NBM2020-U50	2	6	1,92	50	3	100	26,98 €
H-NBM2025-U20	2,5	6	2,4	20	4	60	19,98 €
H-NBM2025-U30	2,5	6	2,4	30	4	80	24,75 €
H-NBM2025-U40	2,5	6	2,4	40	4	80	24,75 €
H-NBM2030-U09	3	6	2,9	9	5	60	19,98 €
H-NBM2030-U12	3	6	2,9	12	5	60	19,98 €
H-NBM2030-U15	3	6	2,9	15	5	60	19,98 €
H-NBM2030-U20	3	6	2,9	20	5	60	19,98 €
H-NBM2030-U25	3	6	2,9	25	5	65	20,40 €
H-NBM2030-U30	3	6	2,9	30	5	80	24,75 €
H-NBM2030-U35	3	6	2,9	35	5	80	24,75 €
H-NBM2030-U40	3	6	2,9	40	5	80	24,75 €
H-NBM2030-U50	3	6	2,9	50	5	100	26,98 €
H-NBM2040-U10	4	6	3,9	10	6	57	19,50 €
H-NBM2040-U12	4	6	3,9	12	6	60	19,98 €
H-NBM2040-U16	4	6	3,9	16	6	60	19,98 €
H-NBM2040-U20	4	6	3,9	20	6	60	19,98 €
H-NBM2040-U25	4	6	3,9	25	6	65	20,40 €
H-NBM2040-U30	4	6	3,9	30	6	80	24,75 €
H-NBM2040-U35	4	6	3,9	35	6	80	24,75 €
H-NBM2040-U40	4	6	3,9	40	6	80	24,75 €
H-NBM2040-U50	4	6	3,9	50	6	100	26,98 €
H-NBM2050-U20	5	6	4,8	20	7	60	19,98 €
H-NBM2050-U30	5	6	4,8	30	7	80	24,75 €
H-NBM2050-U40	5	6	4,8	40	7	80	24,75 €
H-NBM2050-U50	5	6	4,8	50	7	100	26,98 €

I Z2 FRESAS ESFERICAS CÓNICAS

EN Z2 BALL NOSE END MILL | CONICAL FORM - PENCIL FORM

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CONICAL FORM - PENCIL FORM

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2010-20	1	6	20	1,5	60	19,98 €
H-CBM2010-30	1	6	30	1,5	65	20,40 €
H-CBM2010L-40	1	6	40	1,5	80	24,75 €
H-CBM2010L-50	1	6	50	1,5	100	26,98 €
H-CBM2010XL-60	1	6	60	1,5	108	28,50 €
H-CBM2010XL-70	1	6	70	1,5	108	29,75 €
H-CBM2015-20	1,5	6	20	2	60	19,98 €
H-CBM2015-30	1,5	6	30	2	65	20,40 €
H-CBM2015L-40	1,5	6	40	2	80	24,75 €
H-CBM2015XL-50	1,5	6	50	2	100	26,98 €
H-CBM2015XL-60	1,5	6	60	2	108	28,50 €
H-CBM2015XL-70	1,5	6	70	2	108	29,75 €
H-CBM2020-20	2	6	20	3	60	19,98 €
H-CBM2020-25	2	6	25	6	60	19,98 €
H-CBM2020-30	2	6	30	6	65	20,40 €
H-CBM2020L-40	2	6	40	3	80	24,75 €

I Z2 FRESAS ESFERICAS CÓNICAS CON FORMA DE LAPIZ

EN Z2 BALL NOSE END MILL | CONICAL FORM - PENCIL FORM

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2020XL-50	2	6	50	3	100	26,98 €
H-CBM2020XL-60	2	6	60	3	108	28,50 €
H-CBM2020XL-70	2	6	70	3	108	29,75 €
H-CBM2030-20	3	6	20	7	60	19,98 €
H-CBM2030-30	3	6	30	7	65	20,40 €
H-CBM2030L-40	3	6	40	5	80	24,75 €
H-CBM2030L-50	3	6	50	5	100	26,98 €
H-CBM2030XL-60	3	6	60	5	108	28,50 €
H-CBM2030XL-70	3	6	70	5	108	29,75 €
H-CBM2040-20	4	6	20	8	60	19,98 €
H-CBM2040-25	4	6	25	8	60	19,98 €
H-CBM2040-30	4	6	30	8	65	20,40 €
H-CBM2040L-40	4	6	40	6	80	24,75 €
H-CBM2040L-50	4	6	50	6	100	26,98 €
H-CBM2040XL-60	4	6	60	6	108	28,50 €
H-CBM2040XL-70	4	6	70	6	108	29,75 €
H-CBM2040-50	4	8	50	8	100	36,14 €
H-CBM2050L-50	5	6	50	7	100	26,98 €
H-CBM2050-41	5	8	41	12	90	34,25 €
H-CBM2050-60	5	8	60	12	90	34,25 €
H-CBM2060-33	6	8	33	14	90	34,25 €
H-CBM2060L-50	6	8	50	9	100	35,62 €
H-CBM2060-50	6	10	50	12	100	49,55 €
H-CBM2100-60	10	16	60	20	150	132,50 €
H-CBM2120-60	12	16	60	20	150	132,50 €

I Z2 FRESAS ESFERICAS CÓNICA 1°

1° DE SALIDA / RADIO

EN Z2 BALL NOSE END MILL 1°

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE 1°

DE Z2 KUGELFRÄSER 1°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CONICAL FORM - TAPER 1°

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2010-C20x1°	1	6	20	1,5	60	19,98 €
H-CBM2010-C30x1°	1	6	30	1,5	65	20,40 €
H-CBM2010L-C40x1°	1	6	40	1,5	80	24,75 €
H-CBM2010XL-C50x1°	1	6	50	1,5	100	26,98 €
H-CBM2010XL-C60x1°	1	6	60	1,5	108	28,50 €
H-CBM2010XL-C70x1°	1	6	70	1,5	108	29,75 €
H-CBM2015-C20x1°	1,5	6	20	2	60	19,98 €
H-CBM2015-C30x1°	1,5	6	30	2	65	20,40 €
H-CBM2015XL-C30x1°	1,5	6	30	2	108	28,50 €
H-CBM2015L-C40x1°	1,5	6	40	2	80	24,75 €
H-CBM2015L-C43x1°	1,5	6	43	2	108	28,50 €
H-CBM2015XL-C50x1°	1,5	6	50	2	100	26,98 €
H-CBM2015XL-C53x1°	1,5	6	53	2	108	28,50 €
H-CBM2015XL-C63x1°	1,5	6	63	2	108	28,50 €
H-CBM2015XL-C70x1°	1,5	6	70	2	108	29,75 €
H-CBM2015XL-C85x1°	1,5	6	85	2	150	50,00 €

I Z2 FRESAS ESFERICAS CÓNICA 1º

1º DE SALIDA / RADIO



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2020-C20x1º	2	6	20	3	60	19,98 €
H-CBM2020-C30x1º	2	6	30	3	65	20,40 €
H-CBM2020L-C30x1º	2	6	30	3	80	24,75 €
H-CBM2020XL-C30x1º	2	6	30	3	108	28,50 €
H-CBM2020L-C40x1º	2	6	40	3	80	24,75 €
H-CBM2020XL-C43x1º	2	6	43	3	108	28,50 €
H-CBM2020XL-C50x1º	2	6	50	3	100	26,98 €
H-CBM2020XL-C53x1º	2	6	53	3	108	28,50 €
H-CBM2020XL-C63x1º	2	6	63	3	108	28,50 €
H-CBM2020XL-C70x1º	2	6	70	3	108	29,75 €
H-CBM2020XL-C85x1º	2	6	85	3	150	50,00 €
H-CBM2030-C20x1º	3	6	20	5	60	19,98 €
H-CBM2030-C30x1º	3	6	30	5	65	20,40 €
H-CBM2030XL-C35x1º	3	6	35	5	108	28,50 €
H-CBM2030L-C40x1º	3	6	40	5	80	24,75 €
H-CBM2030XL-C44x1º	3	6	44	5	108	28,50 €
H-CBM2030XL-C50x1º	3	6	50	5	100	26,98 €
H-CBM2030XL-C55x1º	3	6	55	5	108	28,50 €
H-CBM2030XL-C65x1º	3	6	65	5	108	28,50 €
H-CBM2030XL-C75x1º	3	6	75	5	108	29,75 €
H-CBM2030XL-C85x1º	3	6	85	5	150	50,00 €
H-CBM2040-C20x1º	4	6	20	6	60	19,98 €
H-CBM2040-C30x1º	4	6	30	6	65	20,40 €
H-CBM2040XL-C35x1º	4	6	35	6	108	28,50 €
H-CBM2040L-C40x1º	4	6	40	6	80	24,75 €
H-CBM2040XL-C45x1º	4	6	45	6	108	28,50 €
H-CBM2040XL-C50x1º	4	6	50	6	100	26,98 €
H-CBM2040XL-C55x1º	4	6	55	6	108	28,50 €
H-CBM2040XL-C65x1º	4	6	65	6	108	29,75 €
H-CBM2040XL-C70x1º	4	6	70	6	150	50,00 €

I Z2 FRESAS ESFERICAS CÓNICA 1,5°

SALIDA / RADIO / MANGO 6

EN Z2 BALL NOSE END MILL | CONICAL FORM | TAPER 1,5°

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIM NANO



CONICA 1,5° SALIDA

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2010-C20x1,5°	1	6	20	1,5	60	19,98 €
H-CBM2010-C30x1,5°	1	6	30	1,5	65	20,40 €
H-CBM2010L-C40x1,5°	1	6	40	1,5	80	24,75 €
H-CBM2010XL-C50x1,5°	1	6	50	1,5	100	26,98 €
H-CBM2010XL-C60x1,5°	1	6	60	1,5	108	28,50 €
H-CBM2010XL-C70x1,5°	1	6	70	1,5	108	29,75 €
H-CBM2015-C20x1,5°	1,5	6	20	2	60	19,98 €
H-CBM2015-C30x1,5°	1,5	6	30	2	65	20,40 €
H-CBM2015XL-C30x1,5°	1,5	6	30	2	108	28,50 €
H-CBM2015L-C40x1,5°	1,5	6	40	2	80	24,75 €
H-CBM2015L-C43x1,5°	1,5	6	43	2	108	28,50 €
H-CBM2015XL-C50x1,5°	1,5	6	50	2	100	26,98 €
H-CBM2015XL-C53x1,5°	1,5	6	53	2	108	28,50 €
H-CBM2015XL-C63x1,5°	1,5	6	63	2	108	28,50 €
H-CBM2015XL-C70x1,5°	1,5	6	70	2	108	29,75 €
H-CBM2015XL-C85x1,5°	1,5	6	85	2	150	50,00 €

I Z2 FRESAS ESFERICAS CÓNICA 1,5°

SALIDA / RADIO / MANGO 6

EN Z2 BALL NOSE END MILL | CONICAL FORM | TAPER 1,5°

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 KUGELFRÄSER



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
H-CBM2020-C20x1,5°	2	6	20	3	60	19,98 €
H-CBM2020-C30x1,5°	2	6	30	3	65	20,40 €
H-CBM2020L-C30x1,5°	2	6	30	3	80	24,75 €
H-CBM2020XL-C30x1,5°	2	6	30	3	108	28,50 €
H-CBM2020L-C40x1,5°	2	6	40	3	80	24,75 €
H-CBM2020XL-C40x1,5°	2	6	40	3	108	28,50 €
H-CBM2020XL-C50x1,5°	2	6	50	3	100	26,98 €
H-CBM2020XL-C53x1,5°	2	6	53	3	108	28,50 €
H-CBM2020XL-C63x1,5°	2	6	63	3	108	28,50 €
H-CBM2020XL-C70x1,5°	2	6	70	3	108	29,75 €
H-CBM2020XL-C84x1,5°	2	6	84	3	150	50,00 €
H-CBM2030-C20x1,5°	3	6	20	5	60	19,98 €
H-CBM2030-C30x1,5°	3	6	30	5	65	20,40 €
H-CBM2030XL-C35x1,5°	3	6	35	5	108	28,50 €
H-CBM2030L-C40x1,5°	3	6	40	5	80	24,75 €
H-CBM2030XL-C44x1,5°	3	6	44	5	108	28,50 €
H-CBM2030XL-C50x1,5°	3	6	50	5	100	26,98 €
H-CBM2030XL-C55x1,5°	3	6	55	5	108	28,50 €
H-CBM2030XL-C65x1,5°	3	6	65	5	108	28,50 €
H-CBM2030XLL-C65x1,5°	3	6	65	5	150	50,00 €
H-CBM2040-C20x1,5°	4	6	20	6	60	19,98 €
H-CBM2040-C30x1,5°	4	6	30	6	65	20,40 €
H-CBM2040-C35x1,5°	4	6	35	6	108	28,50 €
H-CBM2040L-C40x1,5°	4	6	40	6	80	24,75 €
H-CBM2040XL-C45x1,5°	4	6	45	6	108	28,50 €

I Z2 ARRAL-TOP: FRESAS ESFERICAS CILÍNDRICAS

EN Z2 ARRAL-TOP: BALL NOSE END MILL

FR Z2 ARRAL-TOP: FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 ARRAL-TOP: KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALCrN



Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
AT-SBM2060	6	6	12	50	19,20 €
AT-SBM2060L	6	6	8	80	25,18 €
AT-SBM2060LLL	6	6	15	100	27,73 €
AT-SBM2080	8	8	15	60	24,58 €
AT-SBM2080L	8	8	12	100	34,84 €
AT-SBM2100	10	10	20	72	36,34 €
AT-SBM2100L	10	10	15	100	50,07 €
AT-SBM2120	12	12	20	75	49,77 €
AT-SBM2120L	12	12	15	100	70,13 €

I Z2 ARRAL-TOP: FRESAS ESFERICAS CÓNICAS 1° CON 1° DE SALIDA AL RADIO

EN Z2 ARRAL-TOP: BALL NOSE END MILL | TAPER 1°

FR Z2 ARRAL-TOP: FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 ARRAL-TOP: KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALCrN



CONICAL FORM - TAPER 1°

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
AT-CBM2060XL-C35x1°	6	8	35	9	108	48,09 €
AT-CBM2060XL-C48x1°	6	8	48	9	108	48,09 €
AT-CBM2060XL-C55x1°	6	8	55	9	108	48,09 €
AT-CBM2060XL-C70x1°	6	8	70	9	108	48,09 €
AT-CBM2060XL-C73x1°	6	8	73	9	150	63,15 €
AT-CBM2080XL-C48x1°	8	10	48	10	108	65,40 €
AT-CBM2080XL-C55x1°	8	10	55	10	108	65,40 €
AT-CBM2080XL-C70x1°	8	10	70	10	108	65,40 €
AT-CBM2080XXL-C70x1°	8	10	70	10	150	87,55 €

I Z2 ARRAL-TOP: FRESAS ESFERICAS CÓNICAS 1,5° CON 1,5° DE SALIDA AL RADIO

EN Z2 ARRAL-TOP: BALL NOSE END MILL | TAPER 1,5°

FR Z2 ARRAL-TOP: FRAISE CYLINDRIQUE HÉMISPHERIQUE

DE Z2 ARRAL-TOP: KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALCrN



CONICAL FORM - TAPER 1,5°

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	C	Lc	L	
AT-CBM2060XL-C35x1,5°	6	8	35	9	108	48,09 €
AT-CBM2060XL-C48x1,5°	6	8	48	9	108	48,09 €
AT-CBM2060XXL-C48x1,5°	6	8	48	9	150	63,15 €
AT-CBM2080XL-C48x1,5°	8	10	48	10	108	65,40 €
AT-CBM2080XXL-C48x1,5°	8	10	48	10	150	87,55 €

I Z2 FRESAS ESFÉRICAS MATERIAL DURO SerieNormal

MECANIZADO DURO 70HRC

EN Z2 BALL NOSE END MILL | HARD CUTTING 70HRC | Normal Series


FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | 70HRC | Normale

DE Z2 KUGELFRÄSER | 70HRC | Normale

- ES** Fundición Gris y
Aceros hasta 70 HRC.
- EN** Cast Iron, Cooper and
Hardened Steels up to 70 HRC.
- FR** Fonte Grise, Cuivre et
Acier Jusqu'à 70 HRC.
- DE** Gubeisen und
Gehärteter Stahl 70 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)							Precio €
2 Flutes (Z2)	Dc	d	Uc	C	U	Lc	L	
H-HBM2020	2	6	-	20	-	3	60	27,97 €
H-HBM2030	3	6	-	20	-	5	60	27,97 €
H-HBM2040	4	6	-	20	-	6	60	27,97 €
H-HBM2050	5	6	4,8	-	20	10	60	27,97 €
H-HBM2060	6	6	5,8	-	20	12	60	27,97 €
H-HBM2080	8	8	7,8	-	20	12	80	39,95 €
H-HBM2100	10	10	9,8	-	22	10	75	44,90 €
H-HBM2120	12	12	11,8	-	24	12	75	52,90 €
H-HBM2160	16	16	15,8	-	40	20	92	103,50 €

Z2 FRESAS ESFERICAS MATERIAL DURO Serie Larga

MECANIZADO DURO 70HRC

EN Z2 BALL NOSE END MILL | HARD CUTTING 70HRC | Long Series

FR Z2 FRAISE CYLINDRIQUE HÉMISPHERIQUE | HARD CUTTING 70HRC | Longue

DE Z2 KUGELFRÄSER | HARD CUTTING 70HRC | Lange

- ES** Fundición Gris y
Aceros hasta 70 HRC.
- EN** Cast Iron, Cooper and
Hardened Steels up to 70 HRC.
- FR** Fonte Grise, Cuivre et
Acier Jusqu'à 70 HRC.
- DE** Gubeisen und
Gehärteter Stahl 70 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)							Precio €
2 Flutes (Z2)	Dc	d	Uc	C	U	Lc	L	
H-HBM2020L	2	6	-	40	-	3	80	33,88 €
H-HBM2030L	3	6	-	40	-	5	80	33,88 €
H-HBM2040L	4	6	-	40	-	6	80	33,88 €
H-HBM2050L	5	6	4,8	-	20	10	80	33,88 €
H-HBM2060L	6	6	5,8	-	20	12	80	33,88 €
H-HBM2080L	8	8	7,8	-	20	12	100	48,23 €
H-HBM2100L	10	10	9,8	-	22	10	100	54,43 €
H-HBM2120L	12	12	11,8	-	24	12	100	74,48 €
H-HBM2160L	16	16	15,8	-	40	20	150	142,00 €

I Z2 MICRO FRESAS ESFERICAS

SIN CUELLO / MANGO 4

EN Z2 BALL NOSE MICRO END MILL | WITHOUT NECK | Normal Series

FR Z2 MICROFRAISE CYLINDRIQUE HÉMISPHERIQUE | Normale

DE Z2 MIKROKUGELFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)				Precio €
2 Flutes (Z2)	Dc	d	Lc	L	
M-SBM2002	0,2	4	0,4	50	27,95 €
M-SBM2003	0,3	4	0,6	50	25,75 €
M-SBM2004	0,4	4	0,8	50	22,55 €
M-SBM2005	0,5	4	1	50	21,47 €
M-SBM2006	0,6	4	1,2	50	21,47 €
M-SBM2007	0,7	4	1,4	50	21,47 €
M-SBM2008	0,8	4	1,6	50	21,47 €
M-SBM2009	0,9	4	1,8	50	21,47 €


I Z2 MICRO FRESAS ESFERICAS CUELLO REBAJADO

EN Z2 BALL NOSE MICRO END MILL | WITH NECK
FR Z2 MICROFRAISE CYLINDRIQUE HÉMISPHERIQUE
DE Z2 MIKROKUGELFRÄSER

- ES** Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.
- EN** Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.
- FR** Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.
- DE** Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	Uc	U	Lc	L	
M-SBM2005-04	0,5	4	0,48	4	0,7	50	24,15 €
M-SBM2005-06	0,5	4	0,48	6	0,7	50	24,15 €
M-SBM2006-04	0,6	4	0,57	4	0,9	50	24,15 €
M-SBM2006-06	0,6	4	0,57	6	0,9	50	24,15 €
M-SBM2006-08	0,6	4	0,57	8	0,9	50	24,15 €
M-SBM2008-06	0,8	4	0,76	6	1,2	50	24,15 €
M-SBM2008-08	0,8	4	0,76	8	1,2	50	24,15 €
M-SBM2008-10	0,8	4	0,76	10	1,2	50	24,15 €
M-SBM2012-06	1,2	4	1,15	6	1,8	50	14,10 €
M-SBM2012-08	1,2	4	1,15	8	1,8	50	14,10 €
M-SBM2012-10	1,2	4	1,15	10	1,8	50	14,10 €



04

FRESAS tóricas

CORNER RADIUS END MILL
FRAISE TORIQUE
TORUSFRÄSER END MILL

I Z2 FRESA TÓRICA Serie Normal

EN Z2 CORNER RADIUS END MILL | Normal Series

FR Z2 FRAISE TORIQUE | Normale


DE Z2 TORUSFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2020S-r0,2	2	6	0,2	6	50	15,80 €
H-SEM2020S-r0,5	2	6	0,5	6	50	15,80 €
H-SEM2030S-r0,2	3	6	0,2	8	50	15,80 €
H-SEM2030S-r0,5	3	6	0,5	8	50	15,80 €
H-SEM2040S-r0,2	4	6	0,2	11	50	15,80 €
H-SEM2040S-r0,5	4	6	0,5	11	50	15,80 €
H-SEM2040S-r1,0	4	6	1	11	50	15,80 €
H-SEM2050S-r0,2	5	6	0,2	12	50	15,80 €
H-SEM2050S-r0,5	5	6	0,5	12	50	15,80 €
H-SEM2050S-r1,0	5	6	1	12	50	15,80 €
H-SEM2060S-r0,2	6	6	0,2	12	50	15,80 €
H-SEM2060S-r0,5	6	6	0,5	13	50	15,80 €
H-SEM2060S-r1,0	6	6	1	13	50	15,80 €
H-SEM2060S-r1,5	6	6	1,5	13	50	15,80 €
H-SEM2060S-r2,0	6	6	2	13	50	15,80 €
H-SEM2080S-r0,2	8	8	0,2	15	60	21,75 €

I Z2 FRESA TÓRICA Serie Normal

EN Z2 CORNER RADIUS END MILL | Normal Series

FR Z2 FRAISE TORIQUE | Normale

DE Z2 TORUSFRÄSER | Normale



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2080S-r0,5	8	8	0,5	15	60	21,75 €
H-SEM2080S-r1,0	8	8	1	15	60	21,75 €
H-SEM2080S-r1,5	8	8	1,5	15	60	21,75 €
H-SEM2080S-r2,0	8	8	2	15	60	21,75 €
H-SEM2100S-r0,5	10	10	0,5	20	72	29,95 €
H-SEM2100S-r1,0	10	10	1	20	72	29,95 €
H-SEM2100S-r1,5	10	10	1,5	20	72	29,95 €
H-SEM2100S-r2,0	10	10	2	20	72	29,95 €
H-SEM2100S-r3,0	10	10	3	20	72	29,95 €
H-SEM2120S-r0,5	12	12	0,5	24	75	42,30 €
H-SEM2120S-r1,0	12	12	1	24	75	42,30 €
H-SEM2120S-r1,5	12	12	1,5	24	75	42,30 €
H-SEM2120S-r2,0	12	12	2	24	75	42,30 €
H-SEM2120S-r3,0	12	12	3	24	75	42,30 €
H-SEM2160S-r0,5	16	16	0,5	30	92	79,40 €
H-SEM2160S-r1,0	16	16	1	30	92	79,40 €
H-SEM2160S-r2,0	16	16	2	30	92	79,40 €
H-SEM2160S-r3,0	16	16	3	30	92	79,40 €
H-SEM2160S-r4,0	16	16	4	30	92	79,40 €

I Z4 FRESA TÓRICA Serie Normal

EN Z4 CORNER RADIUS END MIL | Normal Series

FR Z4 FRAISE TORIQUE | Normale


DE Z4 TORUSFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE NORMAL

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	R	Lc	L	
H-SEM4020S-r0,2	2	6	0,2	6	50	15,80 €
H-SEM4020S-r0,5	2	6	0,5	6	50	15,80 €
H-SEM4030S-r0,2	3	6	0,2	8	50	15,80 €
H-SEM4030S-r0,5	3	6	0,5	8	50	15,80 €
H-SEM4040S-r0,2	4	6	0,2	11	50	15,80 €
H-SEM4040S-r0,5	4	6	0,5	11	50	15,80 €
H-SEM4040S-r1,0	4	6	1	11	50	15,80 €
H-SEM4050S-r0,2	5	6	0,2	12	50	15,80 €
H-SEM4050S-r0,5	5	6	0,5	12	50	15,80 €
H-SEM4050S-r1,0	5	6	1	12	50	15,80 €
H-SEM4060S-r0,2	6	6	0,2	12	50	15,80 €
H-SEM4060S-r0,5	6	6	0,5	13	50	15,80 €
H-SEM4060S-r1,0	6	6	1	13	50	15,80 €
H-SEM4060S-r1,5	6	6	1,5	13	50	15,80 €
H-SEM4060S-r2,0	6	6	2	13	50	15,80 €
H-SEM4080S-r0,2	8	8	0,2	15	60	21,75 €

I Z4 FRESA TÓRICA Serie Normal

EN Z4 CORNER RADIUS END MILL | Normal Series

FR Z4 FRAISE TORIQUE | Normale

DE Z4 TORUSFRÄSER | Normale



Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	R	Lc	L	
H-SEM4080S-r0,5	8	8	0,5	15	60	21,75 €
H-SEM4080S-r1,0	8	8	1	15	60	21,75 €
H-SEM4080S-r1,5	8	8	1,5	15	60	21,75 €
H-SEM4080S-r2,0	8	8	2	15	60	21,75 €
H-SEM4100S-r0,5	10	10	0,5	20	72	29,95 €
H-SEM4100S-r1,0	10	10	1	20	72	29,95 €
H-SEM4100S-r1,5	10	10	1,5	20	72	29,95 €
H-SEM4100S-r2,0	10	10	2	20	72	29,95 €
H-SEM4100S-r3,0	10	10	3	20	72	29,95 €
H-SEM4120S-r0,5	12	12	0,5	24	75	42,30 €
H-SEM4120S-r1,0	12	12	1	24	75	42,30 €
H-SEM4120S-r1,5	12	12	1,5	24	75	42,30 €
H-SEM4120S-r2,0	12	12	2	24	75	42,30 €
H-SEM4120S-r3,0	12	12	3	24	75	42,30 €
H-SEM4160S-r0,5	16	16	0,5	30	92	79,40 €
H-SEM4160S-r1,0	16	16	1	30	92	79,40 €
H-SEM4160S-r2,0	16	16	2	30	92	79,40 €
H-SEM4160S-r3,0	16	16	3	30	92	79,40 €
H-SEM4160S-r4,0	16	16	4	30	92	79,40 €

I Z2 FRESA TÓRICA Corte Normal

EN Z2 CORNER RADIUS END MILL | Normal Cutting

FR Z2 FRAISE TORIQUE | Normal Cutting

DE Z2 TORUSFRÄSER | Normal Cutting

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2060X-r0,2	6	6	0,2	13	80	21,50 €
H-SEM2060X-r0,5	6	6	0,5	13	80	21,50 €
H-SEM2060X-r1,0	6	6	1	13	80	21,50 €
H-SEM2060X-r1,5	6	6	1,5	13	80	21,50 €
H-SEM2060X-r2,0	6	6	2	13	80	21,50 €
H-SEM2080X-r0,5	8	8	0,5	19	90	29,50 €
H-SEM2080X-r1,0	8	8	1	19	90	29,50 €
H-SEM2080X-r1,5	8	8	1,5	19	90	29,50 €
H-SEM2080X-r2,0	8	8	2	19	90	29,50 €
H-SEM2100X-r0,5	10	10	0,5	22	100	41,20 €
H-SEM2100X-r1,0	10	10	1	22	100	41,20 €
H-SEM2100X-r1,5	10	10	1,5	22	100	41,20 €
H-SEM2100X-r2,0	10	10	2	22	100	41,20 €
H-SEM2100X-r3,0	10	10	3	22	100	41,20 €
H-SEM2120X-r0,5	12	12	0,5	26	100	57,90 €
H-SEM2120X-r1,0	12	12	1	26	100	57,90 €
H-SEM2120X-r1,5	12	12	1,5	26	100	57,90 €
H-SEM2120X-r2,0	12	12	2	26	100	57,90 €
H-SEM2120X-r3,0	12	12	3	26	100	57,90 €

I Z4 FRESA TÓRICA Corte Normal

EN Z4 CORNER RADIUS END MILL | Normal Cutting

FR Z4 FRAISE TORIQUE | Normal Cutting

DE Z4 TORUSFRÄSER | Normal Cutting

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	R	Lc	L	
H-SEM4060X-r0,2	6	6	0,2	13	80	21,50 €
H-SEM4060X-r0,5	6	6	0,5	13	80	21,50 €
H-SEM4060X-r1,0	6	6	1	13	80	21,50 €
H-SEM4060X-r1,5	6	6	1,5	13	80	21,50 €
H-SEM4060X-r2,0	6	6	2	13	80	21,50 €
H-SEM4080X-r0,5	8	8	0,5	19	90	29,50 €
H-SEM4080X-r1,0	8	8	1	19	90	29,50 €
H-SEM4080X-r1,5	8	8	1,5	19	90	29,50 €
H-SEM4080X-r2,0	8	8	2	19	90	29,50 €
H-SEM4100X-r0,5	10	10	0,5	22	100	41,20 €
H-SEM4100X-r1,0	10	10	1	22	100	41,20 €
H-SEM4100X-r1,5	10	10	1,5	22	100	41,20 €
H-SEM4100X-r2,0	10	10	2	22	100	41,20 €
H-SEM4100X-r3,0	10	10	3	22	100	41,20 €
H-SEM4120X-r0,5	12	12	0,5	26	100	57,90 €
H-SEM4120X-r1,0	12	12	1	26	100	57,90 €
H-SEM4120X-r1,5	12	12	1,5	26	100	57,90 €
H-SEM4120X-r2,0	12	12	2	26	100	57,90 €
H-SEM4120X-r3,0	12	12	3	26	100	57,90 €

I Z2 FRESA TÓRICA CORTE Corte Largo

EN Z2 CORNER RADIUS END MILL | Long Cutting

FR Z2 FRAISE TORIQUE


DE Z2 TORUSFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



LONG CUTTING

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2020L-R0,2	2	6	0,2	10	80	23,70 €
H-SEM2020L-R0,5	2	6	0,5	10	80	23,70 €
H-SEM2030L-R0,2	3	6	0,2	15	80	23,70 €
H-SEM2030L-R0,5	3	6	0,5	15	80	23,70 €
H-SEM2040L-R0,2	4	6	0,2	20	80	23,70 €
H-SEM2040L-R0,5	4	6	0,5	20	80	23,70 €
H-SEM4040L-R1,0	4	6	1	20	80	23,70 €
H-SEM2050L-R0,2	5	6	0,2	25	80	23,70 €
H-SEM2050L-R0,5	5	6	0,5	25	80	23,70 €
H-SEM2050L-R1,0	5	6	1	25	80	23,70 €
H-SEM2060L-r0,2	6	6	0,2	25	80	23,70 €
H-SEM2060L-r0,5	6	6	0,5	25	80	23,70 €
H-SEM2060L-r1,0	6	6	1	25	80	23,70 €
H-SEM2060L-r2,0	6	6	2	25	80	23,70 €

I Z2 FRESA TÓRICA CORTE Corte Largo

EN Z2 CORNER RADIUS END MILL | Long Cutting

FR Z2 FRAISE TORIQUE

DE Z2 TORUSFRÄSER



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2080L-r0,5	8	8	0,5	35	90	33,40 €
H-SEM2080L-r1,0	8	8	1	35	90	33,40 €
H-SEM2080L-r2,0	8	8	2	35	90	33,40 €
H-SEM2100L-r0,5	10	10	0,5	45	100	45,70 €
H-SEM2100L-r1,0	10	10	1	45	100	45,70 €
H-SEM2100L-r2,0	10	10	2	45	100	45,70 €
H-SEM2100L-r3,0	10	10	3	45	100	45,70 €
H-SEM2120L-r0,5	12	12	0,5	50	100	63,40 €
H-SEM2120L-r1,0	12	12	1	50	100	63,40 €
H-SEM2120L-r2,0	12	12	2	50	100	63,40 €
H-SEM2120L-r3,0	12	12	3	50	100	63,4 € €

I Z4 FRESA TÓRICA CORTE Corte Largo

EN Z4 CORNER RADIUS END MILL | Long Cutting

FR Z4 FRAISE TORIQUE


DE Z4 TORUSFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



LONG CUTTING

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	R	Lc	L	
H-SEM4020L-R0,5	2	6	0,5	10	80	23,70 €
H-SEM4020L-R0,2	2	6	0,2	10	80	23,70 €
H-SEM4030L-R0,5	3	6	0,5	15	80	23,70 €
H-SEM4040L-R0,2	4	6	0,2	20	80	23,70 €
H-SEM4040L-R0,5	4	6	0,5	20	80	23,70 €
H-SEM4040L-R1,0	4	6	1	20	80	23,70 €
H-SEM4050L-R0,2	5	6	0,2	25	80	23,70 €
H-SEM4050L-R0,5	5	6	0,5	25	80	23,70 €
H-SEM4050L-R1,0	5	6	1	25	80	23,70 €
H-SEM4060L-r0,2	6	6	0,2	25	80	23,70 €
H-SEM4060L-r0,5	6	6	0,5	25	80	23,70 €
H-SEM4060L-r1,0	6	6	1	25	80	23,70 €
H-SEM4060L-r2,0	6	6	2	25	80	23,70 €
H-SEM4080L-r0,5	8	8	0,5	35	90	33,40 €
H-SEM4080L-r1,0	8	8	1	35	90	33,40 €
H-SEM4080L-r2,0	8	8	2	35	90	33,40 €

I Z4 FRESA TÓRICA CORTE Corte Largo

EN Z4 CORNER RADIUS END MILL | Long Cutting

FR Z4 FRAISE TORIQUE

DE Z4 TORUSFRÄSER



Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM4100L-r0,5	10	10	0,5	45	100	45,70 €
H-SEM4100L-r1,0	10	10	1	45	100	45,70 €
H-SEM4100L-r2,0	10	10	2	45	100	45,70 €
H-SEM4100L-r3,0	10	10	3	45	100	45,70 €
H-SEM4120L-r0,5	12	12	0,5	50	100	63,40 €
H-SEM4120L-r1,0	12	12	1	50	100	63,40 €
H-SEM4120L-r2,0	12	12	2	50	100	63,40 €
H-SEM4120L-r3,0	12	12	3	50	100	63,40 €

I Z2 FRESA TÓRICA EXTRALARGA

EN Z2 CORNER RADIUS END MILL | Extralong Series

FR Z2 FRAISE TORIQUE | Extra Longue


DE Z2 TORUSFRÄSER | Extra Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)					Precio €
2 Flutes (Z2)	Dc	d	R	Lc	L	
H-SEM2060XL-r0,5	6	6	0,5	13	150	31,75 €
H-SEM2060XL-r1,0	6	6	1	13	150	31,75 €
H-SEM2060XL-r1,5	6	6	1,5	13	150	31,75 €
H-SEM2060XL-r2,0	6	6	2	13	150	31,75 €
H-SEM2080XL-r0,5	8	8	0,5	19	150	42,50 €
H-SEM2080XL-r1,0	8	8	1	19	150	42,50 €
H-SEM2080XL-r1,5	8	8	1,5	19	150	42,50 €
H-SEM2080XL-r2,0	8	8	2	19	150	42,50 €
H-SEM2100XL-r0,5	10	10	0,5	22	150	57,50 €
H-SEM2100XL-r1,0	10	10	1	22	150	57,50 €
H-SEM2100XL-r2,0	10	10	2	22	150	57,50 €
H-SEM2100XL-r3,0	10	10	3	22	150	57,50 €
H-SEM2120XL-r0,5	12	12	0,5	26	150	81,70 €
H-SEM2120XL-r1,0	12	12	1	26	150	81,70 €
H-SEM2120XL-r2,0	12	12	2	26	150	81,70 €
H-SEM2120XL-r3,0	12	12	3	26	150	81,70 €

I Z4 FRESA TÓRICA EXTRALARGA

EN Z4 CORNER RADIUS END MILL | Extralong Series

FR Z4 FRAISE TORIQUE | Extra Longue


DE Z4 TORUSFRÄSER | Extra Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



SERIE LARGA

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	R	Lc	L	
H-SEM4060XL-r0,5	6	6	0,5	13	150	31,75 €
H-SEM4060XL-r1,0	6	6	1	13	150	31,75 €
H-SEM4060XL-r1,5	6	6	1,5	13	150	31,75 €
H-SEM4060XL-r2,0	6	6	2	13	150	31,75 €
H-SEM4080XL-r0,5	8	8	0,5	19	150	42,50 €
H-SEM4080XL-r1,0	8	8	1	19	150	42,50 €
H-SEM4080XL-r1,5	8	8	1,5	19	150	42,50 €
H-SEM4080XL-r2,0	8	8	2	19	150	42,50 €
H-SEM4100XL-r0,5	10	10	0,5	22	150	57,50 €
H-SEM4100XL-r1,0	10	10	1	22	150	57,50 €
H-SEM4100XL-r2,0	10	10	2	22	150	57,50 €
H-SEM4100XL-r3,0	10	10	3	22	150	57,50 €
H-SEM4120XL-r0,5	12	12	0,5	26	150	81,70 €
H-SEM4120XL-r1,0	12	12	1	26	150	81,70 €
H-SEM4120XL-r2,0	12	12	2	26	150	81,70 €
H-SEM4120XL-r3,0	12	12	3	26	150	81,70 €

Z2 FRESA TÓRICA CUELLO-MANGO D6

EN Z2 CORNER RADIUS END MILL | SHANK D6

FR Z2 FRAISE TORIQUE


DE Z2 TORUSFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CUELLO REFORZADO Y REBAJADO

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2010X-r0,1-U5	1	6	0,1	1,5	5	57	18,50 €
H-SEM2010X-r0,1-U12	1	6	0,1	1,5	12	65	19,50 €
H-SEM2010X-r0,1-U20	1	6	0,1	1,5	20	65	19,50 €
H-SEM2010X-r0,25-U5	1	6	0,25	1,5	5	57	18,50 €
H-SEM2010X-r0,25-U12	1	6	0,25	1,5	12	65	19,50 €
H-SEM2010X-r0,25-U20	1	6	0,25	1,5	20	65	19,50 €
H-SEM2015X-r0,1-U5	1,5	6	0,1	2	5	57	18,50 €
H-SEM2015X-r0,1-U12	1,5	6	0,1	2	12	65	19,50 €
H-SEM2015X-r0,1-U20	1,5	6	0,1	2	20	65	19,50 €
H-SEM2015X-r0,1-U25	1,5	6	0,1	2	25	65	19,50 €
H-SEM2015X-r0,3-U5	1,5	6	0,3	2	5	57	18,50 €
H-SEM2015X-r0,3-U12	1,5	6	0,3	2	12	65	19,50 €
H-SEM2015X-r0,3-U20	1,5	6	0,3	2	20	65	19,50 €
H-SEM2015X-r0,3-U25	1,5	6	0,3	2	25	65	19,50 €
H-SEM2020X-r0,2-U10	2	6	0,2	3	10	80	21,50 €
H-SEM2020X-r0,2-U15	2	6	0,2	3	15	80	21,50 €

I Z2 FRESA TÓRICA CUELLO-MANGO D6

EN Z2 CORNER RADIUS END MILL | SHANK D6

FR Z2 FRAISE TORIQUE

DE Z2 TORUSFRÄSER



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2020X-r0,2-U20	2	6	0,2	3	20	80	21,50 €
H-SEM2020X-r0,2-U25	2	6	0,2	3	25	80	21,50 €
H-SEM2020X-r0,2-U30	2	6	0,2	3	30	80	21,50 €
H-SEM2020X-r0,2-U40	2	6	0,2	3	40	80	21,50 €
H-SEM2020X-r0,5-U10	2	6	0,5	3	10	80	21,50 €
H-SEM2020X-r0,5-U15	2	6	0,5	3	15	80	21,50 €
H-SEM2020X-r0,5-U20	2	6	0,5	3	20	80	21,50 €
H-SEM2020X-r0,5-U25	2	6	0,5	3	25	80	21,50 €
H-SEM2020X-r0,5-U30	2	6	0,5	3	30	80	21,50 €
H-SEM2020X-r0,5-U40	2	6	0,5	3	40	80	21,50 €
H-SEM2030X-r0,2-U15	3	6	0,2	5	15	80	21,50 €
H-SEM2030X-r0,2-U20	3	6	0,2	5	20	80	21,50 €
H-SEM2030X-r0,2-U25	3	6	0,2	5	25	80	21,50 €
H-SEM2030X-r0,2-U30	3	6	0,2	5	30	80	21,50 €
H-SEM2030X-r0,2-U40	3	6	0,2	5	40	80	21,50 €
H-SEM2030X-r0,5-U15	3	6	0,5	5	15	80	21,50 €
H-SEM2030X-r0,5-U20	3	6	0,5	5	20	80	21,50 €
H-SEM2030X-r0,5-U25	3	6	0,5	5	25	80	21,50 €
H-SEM2030X-r0,5-U30	3	6	0,5	5	30	80	21,50 €
H-SEM2030X-r0,5-U40	3	6	0,5	5	40	80	21,50 €
H-SEM2040X-r0,2-U20	4	6	0,2	6	20	80	21,50 €
H-SEM2040X-r0,2-U30	4	6	0,2	6	30	80	21,50 €
H-SEM2040X-r0,2-U40	4	6	0,2	6	40	80	21,50 €
H-SEM2040X-r0,5-U20	4	6	0,5	6	20	80	21,50 €

I Z2 FRESA TÓRICA CUELLO-MANGO D6

EN Z2 CORNER RADIUS END MILL | SHANK D6

FR Z2 FRAISE TORIQUE

DE Z2 TORUSFRÄSER



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2040X-r0,5-U30	4	6	0,5	6	30	80	21,50 €
H-SEM2040X-r0,5-U40	4	6	0,5	6	40	80	21,50 €
H-SEM2040X-r1,0-U20	4	6	1	6	20	80	21,50 €
H-SEM2040X-r1,0-U30	4	6	1	6	30	80	21,50 €
H-SEM2040X-r1,0-U40	4	6	1	6	40	80	21,50 €
H-SEM2050X-r0,2-U25	5	6	0,2	7	25	80	21,50 €
H-SEM2050X-r0,2-U30	5	6	0,2	7	30	80	21,50 €
H-SEM2050X-r0,2-U40	5	6	0,2	7	40	80	21,50 €
H-SEM2050X-r0,5-U25	5	6	0,5	7	25	80	21,50 €
H-SEM2050X-r0,5-U30	5	6	0,5	7	30	80	21,50 €
H-SEM2050X-r0,5-U40	5	6	0,5	7	40	80	21,50 €
H-SEM2050X-r1,0-U25	5	6	1	7	25	80	21,50 €
H-SEM2050X-r1,0-U30	5	6	1	7	30	80	21,50 €
H-SEM2050X-r1,0-U40	5	6	1	7	40	80	21,50 €



DISEÑO
CONTROL
FABRICACIÓN
DISTRIBUCIÓN



I Z4 FRESA TÓRICA CUELLO-MANGO D6

EN Z4 CORNER RADIUS END MILL | SHANK D6

FR Z4 FRAISE TORIQUE

DE Z4 TORUSFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CUELLO REFORZADO Y REBAJADO

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4020X-r0,2-U10	2	6	0,2	3	10	80	21,50 €
H-SEM4020X-r0,2-U15	2	6	0,2	3	15	80	21,50 €
H-SEM4020X-r0,2-U20	2	6	0,2	3	20	80	21,50 €
H-SEM4020X-r0,2-U25	2	6	0,2	3	25	80	21,50 €
H-SEM4020X-r0,2-U30	2	6	0,2	3	30	80	21,50 €
H-SEM4020X-r0,2-U40	2	6	0,2	3	40	80	21,50 €
H-SEM4020X-r0,5-U10	2	6	0,5	3	10	80	21,50 €
H-SEM4020X-r0,5-U15	2	6	0,5	3	15	80	21,50 €
H-SEM4020X-r0,5-U20	2	6	0,5	3	20	80	21,50 €
H-SEM4020X-r0,5-U25	2	6	0,5	3	25	80	21,50 €
H-SEM4020X-r0,5-U30	2	6	0,5	3	30	80	21,50 €
H-SEM4020X-r0,5-U40	2	6	0,5	3	40	80	21,50 €
H-SEM4030X-r0,2-U15	3	6	0,2	5	15	80	21,50 €
H-SEM4030X-r0,2-U20	3	6	0,2	5	20	80	21,50 €
H-SEM4030X-r0,2-U25	3	6	0,2	5	25	80	21,50 €
H-SEM4030X-r0,2-U30	3	6	0,2	5	30	80	21,50 €

I Z4 FRESA TÓRICA CUELLO-MANGO D6

EN Z4 CORNER RADIUS END MILL | SHANK D6

FR Z4 FRAISE TORIQUE

DE Z4 TORUSFRÄSER



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4030X-r0,2-U40	3	6	0,2	5	40	80	21,50 €
H-SEM4030X-r0,5-U15	3	6	0,5	5	15	80	21,50 €
H-SEM4030X-r0,5-U20	3	6	0,5	5	20	80	21,50 €
H-SEM4030X-r0,5-U25	3	6	0,5	5	25	80	21,50 €
H-SEM4030X-r0,5-U30	3	6	0,5	5	30	80	21,50 €
H-SEM4030X-r0,5-U40	3	6	0,5	5	40	80	21,50 €
H-SEM4040X-r0,2-U20	4	6	0,2	6	20	80	21,50 €
H-SEM4040X-r0,2-U30	4	6	0,2	6	30	80	21,50 €
H-SEM4040X-r0,2-U40	4	6	0,2	6	40	80	21,50 €
H-SEM4040X-r0,5-U20	4	6	0,5	6	20	80	21,50 €
H-SEM4040X-r0,5-U30	4	6	0,5	6	30	80	21,50 €
H-SEM4040X-r0,5-U40	4	6	0,5	6	40	80	21,50 €
H-SEM4040X-r1,0-U20	4	6	1	6	20	80	21,50 €
H-SEM4040X-r1,0-U30	4	6	1	6	30	80	21,50 €
H-SEM4040X-r1,0-U40	4	6	1	6	40	80	21,50 €
H-SEM4050X-r0,2-U25	5	6	0,2	7	25	80	21,50 €
H-SEM4050X-r0,2-U30	5	6	0,2	7	30	80	21,50 €
H-SEM4050X-r0,2-U40	5	6	0,2	7	40	80	21,50 €
H-SEM4050X-r0,5-U25	5	6	0,5	7	25	80	21,50 €
H-SEM4050X-r0,5-U30	5	6	0,5	7	30	80	21,50 €
H-SEM4050X-r0,5-U40	5	6	0,5	7	40	80	21,50 €
H-SEM4050X-r1,0-U25	5	6	1	7	25	80	21,50 €
H-SEM4050X-r1,0-U30	5	6	1	7	30	80	21,50 €
H-SEM4050X-r1,0-U40	5	6	1	7	40	80	21,50 €

I Z2 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z2 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z2 FRAISE TORIQUE | Longue


DE Z2 TORUSFRÄSE | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CUELLO REBAJADO

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2060X-r0,2-U20	6	6	0,2	7	20	80	21,50 €
H-SEM2060X-r0,2-U30	6	6	0,2	7	30	80	21,50 €
H-SEM2060X-r0,2-U45	6	6	0,2	7	45	80	21,50 €
H-SEM2060X-r0,5-U20	6	6	0,5	7	20	80	21,50 €
H-SEM2060X-r0,5-U30	6	6	0,5	7	30	80	21,50 €
H-SEM2060X-r0,5-U45	6	6	0,5	7	45	80	21,50 €
H-SEM2060X-r1,0-U20	6	6	1	7	20	80	21,50 €
H-SEM2060X-r1,0-U30	6	6	1	7	30	80	21,50 €
H-SEM2060X-r1,0-U45	6	6	1	7	45	80	21,50 €
H-SEM2060X-r1,5-U20	6	6	1,5	7	20	80	21,50 €
H-SEM2060X-r1,5-U30	6	6	1,5	7	30	80	21,50 €
H-SEM2060X-r1,5-U45	6	6	1,5	7	45	80	21,50 €
H-SEM2060X-r2,0-U20	6	6	2	7	20	80	21,50 €
H-SEM2060X-r2,0-U30	6	6	2	7	30	80	21,50 €
H-SEM2060X-r2,0-U45	6	6	2	7	45	80	21,50 €
H-SEM2080X-r0,5-U25	8	8	0,5	9	25	90	29,50 €

I Z2 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z2 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z2 FRAISE TORIQUE | Longue

DE Z2 TORUSFRÄSER | Lange



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2080X-r0,5-U40	8	8	0,5	9	40	90	29,50 €
H-SEM2080X-r0,5-U55	8	8	0,5	9	55	90	29,50 €
H-SEM2080X-r1,0-U25	8	8	1	9	25	90	29,50 €
H-SEM2080X-r1,0-U40	8	8	1	9	40	90	29,50 €
H-SEM2080X-r1,0-U55	8	8	1	9	55	90	29,50 €
H-SEM2080X-r1,5-U25	8	8	1,5	9	25	90	29,50 €
H-SEM2080X-r1,5-U40	8	8	1,5	9	40	90	29,50 €
H-SEM2080X-r1,5-U55	8	8	1,5	9	55	90	29,50 €
H-SEM2080X-r2,0-U25	8	8	2	9	25	90	29,50 €
H-SEM2080X-r2,0-U40	8	8	2	9	40	90	29,50 €
H-SEM2080X-r2,0-U55	8	8	2	9	55	90	29,50 €
H-SEM2100X-r0,5-U30	10	10	0,5	11	30	100	41,20 €
H-SEM2100X-r0,5-U45	10	10	0,5	11	45	100	41,20 €
H-SEM2100X-r0,5-U60	10	10	0,5	11	60	100	41,20 €
H-SEM2100X-r1,0-U30	10	10	1	11	30	100	41,20 €
H-SEM2100X-r1,0-U45	10	10	1	11	45	100	41,20 €
H-SEM2100X-r1,0-U60	10	10	1	11	60	100	41,20 €
H-SEM2100X-r2,0-U30	10	10	2	11	30	100	41,20 €
H-SEM2100X-r2,0-U45	10	10	2	11	45	100	41,20 €
H-SEM2100X-r2,0-U60	10	10	2	11	60	100	41,20 €
H-SEM2100X-r3,0-U30	10	10	3	11	30	100	41,20 €
H-SEM2100X-r3,0-U45	10	10	3	11	45	100	41,20 €
H-SEM2100X-r3,0-U60	10	10	3	11	60	100	41,20 €
H-SEM2120X-r0,5-U30	12	12	0,5	13	30	100	57,90 €

I Z2 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z2 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z2 FRAISE TORIQUE | Longue

DE Z2 TORUSFRÄSER | Lange



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	U	L	
H-SEM2120X-r0,5-U45	12	12	0,5	13	45	100	57,90 €
H-SEM2120X-r0,5-U60	12	12	0,5	13	60	100	57,90 €
H-SEM2120X-r1,0-U30	12	12	1	13	30	100	57,90 €
H-SEM2120X-r1,0-U45	12	12	1	13	45	100	57,90 €
H-SEM2120X-r1,0-U60	12	12	1	13	60	100	57,90 €
H-SEM2120X-r2,0-U30	12	12	2	13	30	100	57,90 €
H-SEM2120X-r2,0-U45	12	12	2	13	45	100	57,90 €
H-SEM2120X-r2,0-U60	12	12	2	13	60	100	57,90 €
H-SEM2120X-r3,0-U30	12	12	3	13	30	100	57,90 €
H-SEM2120X-r3,0-U45	12	12	3	13	45	100	57,90 €
H-SEM2120X-r3,0-U60	12	12	3	13	60	100	57,90 €
H-SEM2160X-r0,5-U75	16	16	0,5	20	75	150	163,20 €
H-SEM2160X-r1,0-U75	16	16	1	20	75	150	163,20 €
H-SEM2160X-r2,0-U75	16	16	2	20	75	150	163,20 €
H-SEM2160X-r3,0-U75	16	16	2	20	75	150	163,20 €
H-SEM2160X-r4,0-U75	16	16	4	20	75	150	163,20 €

I Z4 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z4 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z4 FRAISE TORIQUE | Longue


DE Z4 TORUSFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CUELLO REBAJADO

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4060X-r0,2-U20	6	6	0,2	7	20	80	21,50 €
H-SEM4060X-r0,2-U30	6	6	0,2	7	30	80	21,50 €
H-SEM4060X-r0,2-U45	6	6	0,2	7	45	80	21,50 €
H-SEM4060X-r0,5-U20	6	6	0,5	7	20	80	21,50 €
H-SEM4060X-r0,5-U30	6	6	0,5	7	30	80	21,50 €
H-SEM4060X-r0,5-U45	6	6	0,5	7	45	80	21,50 €
H-SEM4060X-r1,0-U20	6	6	1	7	20	80	21,50 €
H-SEM4060X-r1,0-U30	6	6	1	7	30	80	21,50 €
H-SEM4060X-r1,0-U45	6	6	1	7	45	80	21,50 €
H-SEM4060X-r1,5-U20	6	6	1,5	7	20	80	21,50 €
H-SEM4060X-r1,5-U30	6	6	1,5	7	30	80	21,50 €
H-SEM4060X-r1,5-U45	6	6	1,5	7	45	80	21,50 €
H-SEM4060X-r2,0-U20	6	6	2	7	20	80	21,50 €
H-SEM4060X-r2,0-U30	6	6	2	7	30	80	21,50 €
H-SEM4060X-r2,0-U45	6	6	2	7	45	80	21,50 €
H-SEM4080X-r0,5-U25	8	8	0,5	9	25	90	29,50 €

I Z4 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z4 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z4 FRAISE TORIQUE | Longue

DE Z4 TORUSFRÄSER | Lange



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4080X-r0,5-U40	8	8	0,5	9	40	90	29,50 €
H-SEM4080X-r0,5-U55	8	8	0,5	9	55	90	29,50 €
H-SEM4080X-r1,0-U25	8	8	1	9	25	90	29,50 €
H-SEM4080X-r1,0-U40	8	8	1	9	40	90	29,50 €
H-SEM4080X-r1,0-U55	8	8	1	9	55	90	29,50 €
H-SEM4080X-r1,5-U25	8	8	1,5	9	25	90	29,50 €
H-SEM4080X-r1,5-U40	8	8	1,5	9	40	90	29,50 €
H-SEM4080X-r1,5-U55	8	8	1,5	9	55	90	29,50 €
H-SEM4080X-r2,0-U25	8	8	2	9	25	90	29,50 €
H-SEM4080X-r2,0-U40	8	8	2	9	40	90	29,50 €
H-SEM4080X-r2,0-U55	8	8	2	9	55	90	29,50 €
H-SEM4100X-r0,5-U30	10	10	0,5	11	30	100	41,20 €
H-SEM4100X-r0,5-U45	10	10	0,5	11	45	100	41,20 €
H-SEM4100X-r0,5-U60	10	10	0,5	11	60	100	41,20 €
H-SEM4100X-r1,0-U30	10	10	1	11	30	100	41,20 €
H-SEM4100X-r1,0-U45	10	10	1	11	45	100	41,20 €
H-SEM4100X-r1,0-U60	10	10	1	11	60	100	41,20 €
H-SEM4100X-r2,0-U30	10	10	2	11	30	100	41,20 €
H-SEM4100X-r2,0-U45	10	10	2	11	45	100	41,20 €
H-SEM4100X-r2,0-U60	10	10	2	11	60	100	41,20 €
H-SEM4100X-r3,0-U30	10	10	3	11	30	100	41,20 €
H-SEM4100X-r3,0-U45	10	10	3	11	45	100	41,20 €
H-SEM4100X-r3,0-U60	10	10	3	11	60	100	41,20 €
H-SEM4120X-r0,5-U30	12	12	0,5	13	30	100	57,90 €

I Z4 FRESA TÓRICA CUELLO REBAJADO Serie Larga

EN Z4 CORNER RADIUS END MILL | REDUCED NECK | Long Series

FR Z4 FRAISE TORIQUE | Longue

DE Z4 TORUSFRÄSER | Lange



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4120X-r0,5-U45	12	12	0,5	13	45	100	57,90 €
H-SEM4120X-r0,5-U60	12	12	0,5	13	60	100	57,90 €
H-SEM4120X-r1,0-U30	12	12	1	13	30	100	57,90 €
H-SEM4120X-r1,0-U45	12	12	1	13	45	100	57,90 €
H-SEM4120X-r1,0-U60	12	12	1	13	60	100	57,90 €
H-SEM4120X-r2,0-U30	12	12	2	13	30	100	57,90 €
H-SEM4120X-r2,0-U45	12	12	2	13	45	100	57,90 €
H-SEM4120X-r2,0-U60	12	12	2	13	60	100	57,90 €
H-SEM4120X-r3,0-U30	12	12	3	13	30	100	57,90 €
H-SEM4120X-r3,0-U45	12	12	3	13	45	100	57,90 €
H-SEM4120X-r3,0-U60	12	12	3	13	60	100	57,90 €
H-SEM4160X-r0,5-U75	16	16	0,5	20	75	150	163,20 €
H-SEM4160X-r1,0-U75	16	16	1	20	75	150	163,20 €
H-SEM4160X-r2,0-U75	16	16	2	20	75	150	163,20 €
H-SEM4160X-r3,0-U75	16	16	2	20	75	150	163,20 €
H-SEM4160X-r4,0-U75	16	16	4	20	75	150	163,20 €

I Z4 FRESA TÓRICA CUELLO REBAJADO Serie Normal

EN Z4 CORNER RADIUS END MILL | REDUCED NECK | Normal Series

FR Z4 FRAISE TORIQUE | Normale


DE Z4 TORUSFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



CUELLO REBAJADO

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4020S-r0,2-U21	2	6	0,2	3	21	57	18,50 €
H-SEM4020S-r0,5-U21	2	6	0,5	3	21	57	18,50 €
H-SEM4030S-r0,2-U21	3	6	0,2	5	21	57	18,50 €
H-SEM4030S-r0,5-U21	3	6	0,5	5	21	57	18,50 €
H-SEM4040S-r0,5-U21	4	6	0,5	6	21	57	18,50 €
H-SEM4040S-r1,0-U21	4	6	1	6	21	57	18,50 €
H-SEM4050S-r0,5-U21	5	6	0,5	7	21	57	18,50 €
H-SEM4050S-r1,0-U21	5	6	1	7	21	57	18,50 €
H-SEM4060S-r0,5-U21	6	6	0,5	7	21	57	18,50 €
H-SEM4060S-r1,0-U21	6	6	1	7	21	57	18,50 €
H-SEM4060S-r1,5-U21	6	6	1,5	7	21	57	18,50 €
H-SEM4060S-r2,0-U21	6	6	2	7	21	57	18,50 €
H-SEM4080S-r0,5-U27	8	8	0,5	9	27	63	23,00 €
H-SEM4080S-r1,0-U27	8	8	1	9	27	63	23,00 €
H-SEM4080S-r1,5-U27	8	8	1,5	9	27	63	23,00 €
H-SEM4080S-r2,0-U27	8	8	2	9	27	63	23,00 €

I Z4 FRESA TÓRICA CUELLO REBAJADO Serie Normal

EN Z4 CORNER RADIUS END MILL | REDUCED NECK | Normal Series

FR Z4 FRAISE TORIQUE | Normale

DE Z4 TORUSFRÄSER | Normale



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
H-SEM4100S-r0,5-U32	10	10	0,5	11	32	72	31,20 €
H-SEM4100S-r1,0-U32	10	10	1	11	32	72	31,20 €
H-SEM4100S-r1,5-U32	10	10	1,5	11	32	72	31,20 €
H-SEM4100S-r2,0-U32	10	10	2	11	32	72	31,20 €
H-SEM4120S-r0,5-U38	12	12	0,5	13	38	83	48,70 €
H-SEM4120S-r1,0-U38	12	12	1	13	38	83	48,70 €
H-SEM4120S-r1,5-U38	12	12	1,5	13	38	83	48,70 €
H-SEM4120S-r2,0-U38	12	12	2	13	38	83	48,70 €
H-SEM4120S-r3,0-U38	12	12	3	13	38	83	48,70 €
H-SEM4160S-r0,5-U44	16	16	0,5	17	44	92	85,35 €
H-SEM4160S-r1,0-U44	16	16	1	17	44	92	85,35 €
H-SEM4160S-r2,0-U44	16	16	2	17	44	92	85,35 €
H-SEM4160S-r3,0-U44	16	16	3	17	44	92	85,35 €
H-SEM4160S-r4,0-U44	16	16	4	17	44	92	85,35 €

I Z2 FRESA TÓRICA CONICA A 1°

EN Z2 CORNER RADIUS END MILL | 1° TAPER

FR Z2 FRAISE TORIQUE | 1°


DE Z2 TORUSFRÄSER | 1°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



1° CONICIDAD AL RÁDIO

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	C	L	
H-CEM2015XL-r0,3-C43x1°	1,5	6	0,3	2	43	109	26,70 €
H-CEM2015XL-r0,3-C53x1°	1,5	6	0,3	2	53	109	27,50 €
H-CEM2015XL-r0,3-C63x1°	1,5	6	0,3	2	63	109	28,50 €
H-CEM2020XL-r0,5-C43x1°	2	6	0,5	3	43	109	26,70 €
H-CEM2020XL-r0,5-C53x1°	2	6	0,5	3	53	109	27,50 €
H-CEM2020XL-r0,5-C63x1°	2	6	0,5	3	63	109	28,50 €
H-CEM2030XL-r0,5-C44x1°	3	6	0,5	5	44	109	26,70 €
H-CEM2030XL-r0,5-C55x1°	3	6	0,5	5	55	109	27,50 €
H-CEM2030XL-r0,5-C65x1°	3	6	0,5	5	65	109	28,50 €
H-CEM2040XL-r0,5-C45x1°	4	6	0,5	6	45	109	26,70 €
H-CEM2040XL-r0,5-C55x1°	4	6	0,5	6	55	109	27,50 €
H-CEM2040XL-r0,5-C65x1°	4	6	0,5	6	65	109	28,50 €
H-CEM2040XL-r1,0-C45x1°	4	6	1	6	45	109	26,70 €
H-CEM2040XL-r1,0-C55x1°	4	6	1	6	55	109	27,50 €
H-CEM2040XL-r1,0-C65x1°	4	6	1	6	65	109	28,50 €
H-CEM2050XL-r0,5-C45x1°	5	8	0,5	7	45	109	36,50 €

I Z2 FRESA TÓRICA CONICA A 1º



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	C	L	
H-CEM2050XL-r0,5-C55x1º	5	8	0,5	7	55	109	37,20 €
H-CEM2050XL-r0,5-C70x1º	5	8	0,5	7	70	109	39,70 €
H-CEM2050XL-r1,0-C45x1º	5	8	1	7	45	109	36,50 €
H-CEM2050XL-r1,0-C55x1º	5	8	1	7	55	109	37,20 €
H-CEM2050XL-r1,0-C70x1º	5	8	1	7	70	109	39,70 €
H-CEM2060XL-r0,5-C48x1º	6	8	0,5	9	48	109	36,50 €
H-CEM2060XL-r0,5-C55x1º	6	8	0,5	9	55	109	37,20 €
H-CEM2060XL-r0,5-C70x1º	6	8	0,5	9	70	109	39,70 €
H-CEM2060XL-r1,0-C48x1º	6	8	1	9	48	109	36,50 €
H-CEM2060XL-r1,0-C55x1º	6	8	1	9	55	109	37,20 €
H-CEM2060XL-r1,0-C70x1º	6	8	1	9	70	109	39,70 €
H-CEM2060XL-r1,5-C48x1º	6	8	1,5	9	48	109	36,50 €
H-CEM2060XL-r1,5-C55x1º	6	8	1,5	9	55	109	37,20 €
H-CEM2060XL-r1,5-C70x1º	6	8	1,5	9	70	109	39,70 €
H-CEM2080XL-r0,5-C48x1º	8	10	0,5	10	48	109	48,50 €
H-CEM2080XL-r0,5-C55x1º	8	10	0,5	10	55	109	49,30 €
H-CEM2080XL-r0,5-C70x1º	8	10	0,5	10	70	109	51,95 €
H-CEM2080XL-r1,0-C48x1º	8	10	1	10	48	109	48,50 €
H-CEM2080XL-r1,0-C55x1º	8	10	1	10	55	109	49,30 €
H-CEM2080XL-r1,0-C70x1º	8	10	1	10	70	109	51,95 €
H-CEM2080XL-r1,5-C48x1º	8	10	1,5	10	48	109	48,50 €
H-CEM2080XL-r1,5-C55x1º	8	10	1,5	10	55	109	49,30 €
H-CEM2080XL-r1,5-C70x1º	8	10	1,5	10	70	109	51,95 €
H-CEM2080XL-r2,0-C48x1º	8	10	2	10	48	109	48,50 €
H-CEM2080XL-r2,0-C55x1º	8	10	2	10	55	109	49,30 €
H-CEM2080XL-r2,0-C70x1º	8	10	2	10	70	109	51,95 €

I Z4 FRESA TÓRICA CONICA A 1°

EN Z4 CORNER RADIUS END MILL | 1° TAPER

FR Z4 FRAISE TORIQUE | 1°


DE Z4 TORUSFRÄSER | 1°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



1° CONICIDAD AL RÁDIO

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	C	L	
H-CEM4020XL-r0,5-C43x1°	2	6	0,5	3	43	109	26,70 €
H-CEM4020XL-r0,5-C53x1°	2	6	0,5	3	53	109	27,50 €
H-CEM4020XL-r0,5-C63x1°	2	6	0,5	3	63	109	28,50 €
H-CEM4030XL-r0,5-C44x1°	3	6	0,5	5	44	109	26,70 €
H-CEM4030XL-r0,5-C55x1°	3	6	0,5	5	55	109	27,50 €
H-CEM4030XL-r0,5-C65x1°	3	6	0,5	5	65	109	28,50 €
H-CEM4040XL-r0,5-C45x1°	4	6	0,5	6	45	109	26,70 €
H-CEM4040XL-r0,5-C55x1°	4	6	0,5	6	55	109	27,50 €
H-CEM4040XL-r0,5-C65x1°	4	6	0,5	6	65	109	28,50 €
H-CEM4040XL-r1,0-C45x1°	4	6	1	6	45	109	26,70 €
H-CEM4040XL-r1,0-C55x1°	4	6	1	6	55	109	27,50 €
H-CEM4040XL-r1,0-C65x1°	4	6	1	6	65	109	28,50 €
H-CEM4050XL-r0,5-C45x1°	5	8	0,5	7	45	109	36,50 €
H-CEM4050XL-r0,5-C55x1°	5	8	0,5	7	55	109	37,20 €
H-CEM4050XL-r0,5-C70x1°	5	8	0,5	7	70	109	39,70 €
H-CEM4050XL-r1,0-C45x1°	5	8	1	7	45	109	36,50 €

I Z4 FRESA TÓRICA CONICA A 1°

EN Z4 CORNER RADIUS END MILL | 1° TAPER

FR Z4 FRAISE TORIQUE | 1° j

DE Z4 TORUSFRÄSERj | 1° j



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	C	L	
H-CEM4050XL-r1,0-C55x1°	5	8	1	7	55	109	37,20 €
H-CEM4050XL-r1,0-C70x1°	5	8	1	7	70	109	39,70 €
H-CEM4060XL-r0,5-C48x1°	6	8	0,5	9	48	109	36,50 €
H-CEM4060XL-r0,5-C55x1°	6	8	0,5	9	55	109	37,20 €
H-CEM4060XL-r0,5-C70x1°	6	8	0,5	9	70	109	39,70 €
H-CEM4060XL-r1,0-C48x1°	6	8	1	9	48	109	36,50 €
H-CEM4060XL-r1,0-C55x1°	6	8	1	9	55	109	37,20 €
H-CEM4060XL-r1,0-C70x1°	6	8	1	9	70	109	39,70 €
H-CEM4060XL-r1,5-C48x1°	6	8	1,5	9	48	109	36,50 €
H-CEM4060XL-r1,5-C55x1°	6	8	1,5	9	55	109	37,20 €
H-CEM4060XL-r1,5-C70x1°	6	8	1,5	9	70	109	39,70 €
H-CEM4080XL-r0,5-C48x1°	8	10	0,5	10	48	109	48,50 €
H-CEM4080XL-r0,5-C55x1°	8	10	0,5	10	55	109	49,30 €
H-CEM4080XL-r0,5-C70x1°	8	10	0,5	10	70	109	51,95 €
H-CEM4080XL-r1,0-C48x1°	8	10	1	10	48	109	48,50 €
H-CEM4080XL-r1,0-C55x1°	8	10	1	10	55	109	49,30 €
H-CEM4080XL-r1,0-C70x1°	8	10	1	10	70	109	51,95 €
H-CEM4080XL-r1,5-C48x1°	8	10	1,5	10	48	109	48,50 €
H-CEM4080XL-r1,5-C55x1°	8	10	1,5	10	55	109	49,30 €
H-CEM4080XL-r1,5-C70x1°	8	10	1,5	10	70	109	51,95 €
H-CEM4080XL-r2,0-C48x1°	8	10	2	10	48	109	48,50 €
H-CEM4080XL-r2,0-C55x1°	8	10	2	10	55	109	49,30 €
H-CEM4080XL-r2,0-C70x1°	8	10	2	10	70	109	51,95 €

I Z2 FRESA TÓRICA CONICA A 1,5°

EN Z2 CORNER RADIUS END MILL | 1,5° TAPER

FR Z2 FRAISE TORIQUE | 1,5°


DE Z2 TORUSFRÄSER | 1,5°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



1,5° CONICIDAD AL RÁDIO

Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	C	L	
H-CEM2015XL-r0,3-C43x1,5°	1,5	6	0,3	2	43	109	26,70 €
H-CEM2015XL-r0,3-C53x1,5°	1,5	6	0,3	2	53	109	27,50 €
H-CEM2015XL-r0,3-C63x1,5°	1,5	6	0,3	2	63	109	28,50 €
H-CEM2020XL-r0,5-C43x1,5°	2	6	0,5	3	43	109	26,70 €
H-CEM2020XL-r0,5-C53x1,5°	2	6	0,5	3	53	109	27,50 €
H-CEM2020XL-r0,5-C63x1,5°	2	6	0,5	3	63	109	28,50 €
H-CEM2030XL-r0,5-C44x1,5°	3	6	0,5	5	44	109	26,70 €
H-CEM2030XL-r0,5-C55x1,5°	3	6	0,5	5	55	109	27,50 €
H-CEM2030XL-r0,5-C65x1,5°	3	6	0,5	5	65	109	28,50 €
H-CEM2040XL-r0,5-C45x1,5°	4	6	0,5	6	45	109	26,70 €
H-CEM2040XL-r1,0-C45x1,5°	4	6	1	6	45	109	26,70 €
H-CEM2050XL-r0,5-C45x1,5°	5	8	0,5	7	45	109	36,50 €
H-CEM2050XL-r0,5-C55x1,5°	5	8	0,5	7	55	109	37,20 €
H-CEM2050XL-r1,0-C45x1,5°	5	8	1	7	45	109	36,50 €
H-CEM2050XL-r1,0-C55x1,5°	5	8	1	7	55	109	37,20 €
H-CEM2060XL-r0,5-C48x1,5°	6	8	0,5	9	48	109	36,50 €

I Z2 FRESA TÓRICA CONICA A 1,5°

EN Z2 CORNER RADIUS END MILL | 1,5° TAPER

FR Z2 FRAISE TORIQUE | 1,5°

DE Z2 TORUSFRÄSER | 1,5°



Ref.	Dimensiones (mm)						Precio €
2 Flutes (Z2)	Dc	d	R	Lc	C	L	
H-CEM2060XL-r1,0-C48x1,5°	6	8	1	9	48	109	36,50 €
H-CEM2060XL-r1,5-C48x1,5°	6	8	1,5	9	48	109	36,50 €
H-CEM2080XL-r0,5-C48x1,5°	8	10	0,5	10	48	109	48,50 €
H-CEM2080XL-r1,0-C48x1,5°	8	10	1	10	48	109	48,50 €
H-CEM2080XL-r1,5-C48x1,5°	8	10	1,5	10	48	109	48,50 €
H-CEM2080XL-r2,0-C48x1,5°	8	10	2	10	48	109	48,50 €

I Z4 FRESA TÓRICA CONICA A 1,5°

EN Z4 CORNER RADIUS END MILL | 1,5° TAPER

FR Z4 FRAISE TORIQUE | 1,5°

DE Z4 TORUSFRÄSER | 1,5°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 62 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 62 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 62 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Gehärteter Stahl 62 HRC.



ALTIN NANO



Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	C	L	
H-CEM4020XL-r0,5-C43x1,5°	2	6	0,5	3	43	109	26,70 €
H-CEM4020XL-r0,5-C53x1,5°	2	6	0,5	3	53	109	27,50 €
H-CEM4020XL-r0,5-C63x1,5°	2	6	0,5	3	63	109	28,50 €
H-CEM4030XL-r0,5-C44x1,5°	3	6	0,5	5	44	109	26,70 €
H-CEM4030XL-r0,5-C55x1,5°	3	6	0,5	5	55	109	27,50 €
H-CEM4030XL-r0,5-C65x1,5°	3	6	0,5	5	65	109	28,50 €
H-CEM4040XL-r0,5-C45x1,5°	4	6	0,5	6	45	109	26,70 €
H-CEM4040XL-r1,0-C45x1,5°	4	6	1	6	45	109	26,70 €
H-CEM4050XL-r0,5-C45x1,5°	5	8	0,5	7	45	109	36,50 €
H-CEM4050XL-r0,5-C55x1,5°	5	8	0,5	7	55	109	37,20 €
H-CEM4050XL-r1,0-C45x1,5°	5	8	1	7	45	109	36,50 €
H-CEM4050XL-r1,0-C55x1,5°	5	8	1	7	55	109	37,20 €
H-CEM4060XL-r0,5-C48x1,5°	6	8	0,5	9	48	109	36,50 €
H-CEM4060XL-r1,0-C48x1,5°	6	8	1	9	48	109	36,50 €
H-CEM4060XL-r1,5-C48x1,5°	6	8	1,5	9	48	109	36,50 €
H-CEM4080XL-r0,5-C48x1,5°	8	10	0,5	10	48	109	48,50 €
H-CEM4080XL-r1,0-C48x1,5°	8	10	1	10	48	109	48,50 €
H-CEM4080XL-r1,5-C48x1,5°	8	10	1,5	10	48	109	48,50 €
H-CEM4080XL-r2,0-C48x1,5°	8	10	2	10	48	109	48,50 €



05

FRESAS de alto rendimiento y específicas

HIGH PERFORMANCE END MILLS
HAUTE PERFORMANCE
SHOCHLEISTUNGSBEARBEITUNG

I Z3 HYPERLINK: FRESA HELICE VARIABLE 35°/38°

CHAFLAN EN ESQUINA / SERIE ECONÓMICA

EN Z3 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | ECONOMY

FR Z3 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | ÉCONOMIQUE


DE Z3 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | WIRTSCHAFTLICH

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



HELICE 35°/38°

Ref.	Dimensiones (mm)					Precio €
3 Flutes (Z3)	Dc	d	LC	C-45°	L	
HYP-3030R	3	6	8	0,05	50	15,70 €
HYP-3040R	4	6	11	0,05	50	15,70 €
HYP-3050R	5	6	13	0,07	50	15,70 €
HYP-3060R	6	6	16	0,10	50	15,70 €
HYP-3080R	8	8	19	0,15	60	19,80 €
HYP-3100R	10	10	22	0,15	73	29,25 €
HYP-3120R	12	12	26	0,25	75	39,90 €
HYP-3140R	14	14	30	0,30	85	54,50 €
HYP-3160R	16	16	32	0,35	92	77,70 €
HYP-3200R	20	20	38	0,35	100	114,60 €

Z4 HYPERLINK: FRESA HELICE VARIABLE 35°/38° CHAFLAN EN ESQUINA / SERIE ECONÓMICA

EN Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | ECONOMY

FR Z4 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | ÉCONOMIQUE


DE Z4 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | WIRTSCHAFTLICH

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



HELICE 35°/38°

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	LC	C-45°	L	
HYP-4030R	3	6	8	0,05	50	15,70 €
HYP-4040R	4	6	11	0,05	50	15,70 €
HYP-4050R	5	6	13	0,07	50	15,70 €
HYP-4060R	6	6	16	0,10	50	15,70 €
HYP-4080R	8	8	19	0,15	60	19,80 €
HYP-4100R	10	10	22	0,15	73	29,25 €
HYP-4120R	12	12	26	0,25	75	39,90 €
HYP-4140R	14	14	30	0,30	85	54,50 €
HYP-4160R	16	16	32	0,35	92	77,70 €
HYP-4200R	20	20	38	0,35	100	114,60 €

I Z4 HYPERLINK: FRESA HELICE VARIABLE 35°/38° WELDOM

CHAFLAN EN ESQUINA / MANGO WELDOM DIN6535 / SERIE ECONÓMICA

EN Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | WELDOM DIN6535 | ECONOMY

FR Z4 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | WELDOM DIN6535 | ÉCONOMIQUE


DE Z4 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | WELDOM DIN6535 | WIRTSCHAFTLICH

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



MANGO WELDOM HELICE 35°/38°

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	Lc	C-45°	L	
HYP-4030RW	3	6	8	0,05	57	18,65 €
HYP-4040RW	4	6	11	0,05	57	18,65 €
HYP-4050RW	5	6	13	0,07	57	18,65 €
HYP-4060RW	6	6	16	0,10	57	18,65 €
HYP-4080RW	8	8	19	0,15	63	22,70 €
HYP-4100RW	10	10	22	0,15	73	32,25 €
HYP-4120RW	12	12	26	0,25	84	47,90 €
HYP-4140RW	14	14	30	0,30	85	59,10 €
HYP-4160RW	16	16	32	0,35	92	82,70 €
HYP-4200RW	20	20	38	0,35	104	120,60 €

I Z4 HYPERLINK: FRESA HELICE VARIABLE 35°/38° Medidas Especiales CHAFLAN EN ESQUINA / SERIE ECONÓMICA

EN Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | SPECIAL SIZES | ECONOMY

FR Z4 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | SPECIAL MEASURES | ÉCONOMIQUE


DE Z4 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | SPECIAL MEASURES | WIRTSCHAFTLICH

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



MEDIDAS ESPECIALES HELICE 35°/38°

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	Lc	C-45°	L	
HYP-4100-25R	10	10	25	0,15	73	32,50 €
HYP-4120L-35R	12	12	35	0,25	83	47,50 €
HYP-4160-45R	16	16	45	0,35	100	85,75 €
HYP-4160-52R	16	16	52	0,35	100	89,90 €
HYP-4160-65R	16	16	65	0,35	150	107,65 €
HYP-4200-55R	20	20	55	0,35	104	123,00 €
HYP-4200-70R	20	20	70	0,35	150	158,75 €

I Z4 HYPERLINK: F. H. V. 35°/38° Cuello Rebajado. Económica

CHAFLAN EN ESQUINA

EN Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | REDUCED NECK | ECONOMY

FR Z4 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | ÉCONOMIQUE


DE Z4 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | WIRTSCHAFTLICH

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan und Gehärteter Stahl 56 HRC.



ALTIN NANO



CUELLO REBAJADO. HELICE 35°/38°

Ref.	Dimensiones (mm)						Precio €
	Dc	d	Lc	U	C-45°	L	
4 Flutes (Z4)							
HYP-4030U20H	3	6	8	20	0,05	57	16,95 €
HYP-4040U20H	4	6	11	20	0,05	57	16,95 €
HYP-4050U21H	5	6	13	21	0,07	57	16,95 €
HYP-4060U21H	6	6	13	21	0,10	57	16,95 €
HYP-4080U27H	8	8	19	27	0,15	63	20,65 €
HYP-4100U32H	10	10	22	32	0,15	73	30,30 €
HYP-4120U38H	12	12	26	38	0,25	83	45,50 €
HYP-4140U40H	14	14	30	40	0,30	84	55,80 €
HYP-4160U44H	16	16	32	44	0,35	92	79,40 €
HYP-4200U55H	20	20	38	55	0,35	104	116,65 €

I Z4 HYPERLINK: F. H. V. 35°/38° Cuello Rebajado WELDOM Econ. CHAFLAN EN ESQUINA

EN Z4 HYPERLINK. UNEQUAL HELIX ANGLES 35°-38° | WELDOM DIN6535 | REDUCED NECK | ECONOMY

FR Z4 HYPERLINK. HÉLICE DIFFÉRENTE 35°-38° | WELDOM DIN6535 | ECONOMY


DE Z4 HYPERLINK. UNGLEICHER DRALLWINKEL 35°-38° | WELDOM DIN6535

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan und Gehärteter Stahl 56 HRC.



ALTIN NANO



SHANK: DIN6535HB. HELICE 35°/38°

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYP-4030U20HW	3	6	8	20	0,05	57	19,15 €
HYP-4040U20HW	4	6	11	20	0,05	57	19,15 €
HYP-4050U21HW	5	6	13	21	0,07	57	19,15 €
HYP-4060U21HW	6	6	13	21	0,10	57	19,15 €
HYP-4080U27HW	8	8	19	27	0,15	63	23,80 €
HYP-4100U32HW	10	10	22	32	0,15	73	33,90 €
HYP-4120U38HW	12	12	26	38	0,25	83	49,25 €
HYP-4140U40HW	14	14	30	40	0,30	84	60,97 €
HYP-4160U44HW	16	16	32	44	0,35	92	84,35 €
HYP-4200U55HW	20	20	38	55	0,35	104	122,40 €

Z4 HYPERLINK PLUS: FRESA HELICE VARIABLE Cuello Rebajado

MULTIUSOS / HELICE VARIABLE 35°/38° / CALIDAD PREMIUM

EN Z4 HYPERLINK PLUS: UNEQUAL HELIX ANGLES 35°-38° | MULTIPURPOSE | REDUCED NECK | PREMIUM

FR Z4 HYPERLINK PLUS: HÉLICE DIFFÉRENTE 35°-38° | PREMIUM


DE Z4 HYPERLINK PLUS: UNGLEICHER DRALLWINKEL 35°-38° | PREMIUM

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



CUELLO REBAJADO. HELICE 35°/38°

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYP-4030U20PB	3	6	8	20	0,05	57	21,15 €
HYP-4040U20PB	4	6	11	20	0,05	57	21,15 €
HYP-4050U21PB	5	6	13	21	0,07	57	21,15 €
HYP-4060U21PB	6	6	13	21	0,10	57	21,15 €
HYP-4080U27PB	8	8	19	27	0,15	63	25,85 €
HYP-4100U32PB	10	10	22	32	0,15	73	37,50 €
HYP-4120U38PB	12	12	26	38	0,25	83	53,22 €
HYP-4140U40PB	14	14	30	40	0,30	84	67,65 €
HYP-4160U44PB	16	16	32	44	0,35	92	94,90 €
HYP-4200U55PB	20	20	38	55	0,35	104	139,80 €

I Z4 HYPERLINK PLUS: FRESA H. V. WELDOM Cuello Rebajado

MULTIUSOS / HELICE VARIABLE 35°/38° / WELDOM DIN6535 / PREMIUM

EN Z4 HYPERLINK PLUS. UNEQUAL HELIX ANGLES 35°-38° | WELDOM DIN6535 | MULTIPURPOSE | PREMIUM

FR Z4 HYPERLINK PLUS. HÉLICE DIFFÉRENTE 35°-38° | WELDOM DIN6535 | PREMIUM


DE Z4 HYPERLINK PLUS. UNGLEICHER DRALLWINKEL 35°-38° | WELDOM | PREMIUM

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



CUELLO REBAJADO. SHANK: DIN6535HB. 35°/38°

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYP-4030U20PBW	3	6	8	20	0,05	57	23,35 €
HYP-4040U20PBW	4	6	11	20	0,05	57	23,35 €
HYP-4050U21PBW	5	6	13	21	0,07	57	23,35 €
HYP-4060U21PBW	6	6	13	21	0,10	57	23,35 €
HYP-4080U27PBW	8	8	19	27	0,15	63	29,00 €
HYP-4100U32PBW	10	10	22	32	0,15	73	41,10 €
HYP-4120U38PBW	12	12	26	38	0,25	83	56,97 €
HYP-4140U40PBW	14	14	30	40	0,30	84	72,80 €
HYP-4160U44PBW	16	16	32	44	0,35	92	99,85 €
HYP-4200U55PBW	20	20	38	55	0,35	104	145,50 €

Z4 HYRUX: FRESA HELICE VARIABLE 43°/45° Alto Rendimiento

CHAFLAN EN ESQUINA /MULTIUSOS / CALIDAD PREMIUM

EN Z4 HYRUX: UNEQUAL HELIX ANGLES 43-35° | MULTIPURPOSE | HIGH PERFORMANCE

FR Z4 HYRUX: HÉLICE DIFFÉRENTE 43-35° | HAUTE PERFORMANCE


DE Z4 HYRUX: UNGLEICHER DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



ALTO RENDIMIENTO

Ref.	Dimensiones (mm)					Precio €
	Dc	d	Lc	C-45°	L	
4 Flutes (Z4)						
HYRUX-4060B	6	6	13	0,2	57	22,90 €
HYRUX-4080B	8	8	19	0,25	63	28,55 €
HYRUX-4100B	10	10	22	0,35	73	41,55 €
HYRUX-4120B	12	12	26	0,35	83	58,35 €
HYRUX-4140B	14	14	30	0,4	84	74,25 €
HYRUX-4160B	16	16	32	0,5	92	105,95 €
HYRUX-4200B	20	20	38	0,5	104	154,90 €

I Z4 HYRUX: FRESA H. VARIABLE 43°/45° WELDOM Alto Rendimiento

CHAFLAN EN ESQUINA / MULTIUSOS / WELDOM DIN6535 / PREMIUM

EN Z4 HYRUX. UNEQUAL HELIX ANGLES 43-35° | WELDOM | MULTIPURPOSE | HIGH PERFORMANCE

FR Z4 HYRUX. HÉLICE DIFFÉRENTE 43-35° | WELDOM | HAUTE PERFORMANCE


DE Z4 HYRUX. U. DRALLWINKEL 43-35° | WELDOM | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



ALTO RENDIMIENTO. WELDOM DIN6535.

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	Lc	C-45°	L	
HYRUX-4060BW	6	6	13	0,2	57	25,10 €
HYRUX-4080BW	8	8	19	0,25	63	31,70 €
HYRUX-4100BW	10	10	22	0,35	73	45,35 €
HYRUX-4120BW	12	12	26	0,35	83	62,80 €
HYRUX-4140BW	14	14	30	0,4	84	79,63 €
HYRUX-4160BW	16	16	32	0,5	92	110,90 €
HYRUX-4200BW	20	20	38	0,5	104	159,95 €

I Z4 HYRUX: FRESA H. V. 43°/45° Cuello Rebajado. Alto Rendimiento CHAFLAN EN ESQUINA /MULTIUSOS

EN Z4 HYRUX: UNEQUAL HELIX ANGLES 43-35° | MULTIPURPOSE | R. NECK | HIGH PERFORMANCE

FR Z4 HYRUX: HÉLICE DIFFÉRENTE 43-35° | HAUTE PERFORMANCE


DE Z4 HYRUX: UNGLEICHER DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



ALTO RENDIMIENTO

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYRUX-4030U11B	3	6	8	11	0,07	57	23,95 €
HYRUX-4030U20B	3	6	8	20	0,07	57	23,95 €
HYRUX-4040U14B	4	6	11	14	0,09	57	23,95 €
HYRUX-4040U20B	4	6	11	20	0,09	57	23,95 €
HYRUX-4050U16B	5	6	13	16	0,12	57	23,95 €
HYRUX-4050U21B	5	6	13	21	0,12	57	23,95 €
HYRUX-4060U21B	6	6	13	21	0,2	57	23,95 €
HYRUX-4080U27B	8	8	19	27	0,25	63	29,65 €
HYRUX-4100U32B	10	10	22	32	0,35	73	42,70 €
HYRUX-4120U38B	12	12	26	38	0,35	83	59,97 €
HYRUX-4140U40B	14	14	30	40	0,4	84	75,70 €
HYRUX-4160U44B	16	16	32	44	0,5	92	107,83 €
HYRUX-4200U55B	20	20	38	55	0,5	104	156,23 €

Z4 HYRUX: F.H.V. 43°/45° Cuello Rebajado WELDOM Alto Rendimien. CHAFLAN EN ESQUINA / MULTIUSOS / WELDOM DIN6535

EN Z4 HYRUX. UNEQUAL HELIX ANGLES 43-35° | WELDOM | MULTIPURPOSE | R. NECK | HIGH PERFORMANCE

FR Z4 HYRUX. HÉLICE DIFFÉRENTE 43-35° | WELDOM | HAUTE PERFORMANCE


DE Z4 HYRUX. UNGLEICHER DRALLWINKEL 43-35° | WELDOM | SHOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALCrN



ALTO RENDIMIENTO. WELDOM DIN6535.

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYRUX-4030U11BW	3	6	8	11	0,07	57	26,15 €
HYRUX-4030U20BW	3	6	8	20	0,07	57	26,15 €
HYRUX-4040U14BW	4	6	11	14	0,09	57	26,15 €
HYRUX-4040U20BW	4	6	11	20	0,09	57	26,15 €
HYRUX-4050U16BW	5	6	13	16	0,12	57	26,15 €
HYRUX-4050U21BW	5	6	13	21	0,12	57	26,15 €
HYRUX-4060U21BW	6	6	13	21	0,2	57	26,15 €
HYRUX-4080U27BW	8	8	19	27	0,25	63	32,80 €
HYRUX-4100U32BW	10	10	22	32	0,35	73	46,60 €
HYRUX-4120U38BW	12	12	26	38	0,35	83	63,72 €
HYRUX-4140U40BW	14	14	30	40	0,4	84	80,85 €
HYRUX-4160U44BW	16	16	32	44	0,5	92	112,78 €
HYRUX-4200U55BW	20	20	38	55	0,5	104	161,93 €

I Z4 HYRUX TITANIO: FRESA HELICE VARIABLE 43°/45°

CHAFLAN EN ESQUINA / ALTO RENDIMIENTO


- EN** Z4 HYRUX TITANIUM: UNEQUAL HELIX ANGLES 43-35° | HIGH PERFORMANCE
FR Z4 HYRUX TITANIUM: HÉLICE DIFFÉRENTE 43-35° | DE HAUTE PERFORMANCE
DE Z4 HYRUX TITANIUM: UNGLEICHER DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero Inoxidable, Titanio, Aleaciones Titanio y Aleaciones Resistentes al Calor.

EN Stainless Steel, Titanium, Titanium Alloys and Heat Resistance Alloys.

FR Acier Inoxydable, Alliages de Titane, Titane, Alliages de et Résistance à la Chaleur.

DE Rostfreier Stahl, Titan, Warmfeste und Legierungen.



ALTIN TITAN



ESPECIAL TITANIO Y ALEACIONES NICKEL

Ref.	Dimensiones (mm)					Precio €
	Dc	d	Lc	C-45°	L	
4 Flutes (Z4)						
HYRUX-4060R	6	6	13	0,2	57	22,90 €
HYRUX-4080R	8	8	19	0,25	63	28,55 €
HYRUX-4100R	10	10	22	0,35	73	41,55 €
HYRUX-4120R	12	12	26	0,35	83	58,35 €
HYRUX-4140R	14	14	30	0,4	84	74,25 €
HYRUX-4160R	16	16	32	0,5	92	105,95 €
HYRUX-4200R	20	20	38	0,5	104	154,90 €

Z4 HYRUX TITANIO: FRESA HELICE VARIABLE 43°/45° WELDOM CHAFLAN EN ESQUINA / WELDOM DIN6535 / ALTO RENDIMIENTO


EN Z4 HYRUX TITANIUM. UNEQUAL HELIX ANGLES 43-35° | WELDOM DIN6535 | HIGH PERFORMANCE
FR Z4 HYRUX TITANIUM. HÉLICE DIFFÉRENTE 43-35° | WELDOM DIN6535 | DE HAUTE PERFORMANCE
DE Z4 HYRUX TITANIUM. UNGLEICHER DRALLWINKEL 43-35° | W. DIN6535 | HOCHLEISTUNGSBEARBEITUNG

ES Acero Inoxidable, Titanio, Aleaciones Titanio y Aleaciones Resistentes al Calor.


EN Stainless Steel, Titanium, Titanium Alloys and Heat Resistance Alloys.

FR Acier Inoxydable, Alliages de Titanie, Titane, Alliages de et Résistance à la Chaleur.

DE Rostfreier Stahl, Titan, Warmfeste und Legierungen.



ALTIN TITAN



ESPECIAL TITANIO Y ALEACIONES NICKEL. WELDOM DIN6535

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	Lc	C-45°	L	
HYRUX-4060RW	6	6	13	0,2	57	25,10 €
HYRUX-4080RW	8	8	19	0,25	63	31,70 €
HYRUX-4100RW	10	10	22	0,35	73	45,35 €
HYRUX-4120RW	12	12	26	0,35	83	62,80 €
HYRUX-4140RW	14	14	30	0,4	84	79,63 €
HYRUX-4160RW	16	16	32	0,5	92	110,90 €
HYRUX-4200RW	20	20	38	0,5	104	159,95 €

I Z4 HYRUX TITANIO: FRESA H. V. 43°/45° Cuello Rebajado

CHAFLAN EN ESQUINA / PREMIUM / ALTO RENDIMIENTO

EN Z4 HYRUX TITANIUM: UNEQUAL HELIX ANGLES 43-35° | REDUCED NECK | HIGH PERFORMANCE

FR Z4 HYRUX TITANIUM: HÉLICE DIFFÉRENTE 43-35° | DE HAUTE PERFORMANCE


DE Z4 HYRUX TITANIUM: UNGLEICHER DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero Inoxidable, Titanio, Aleaciones Titanio y Aleaciones Resistentes al Calor.

EN Stainless Steel, Titanium, Titanium Alloys and Heat Resistance Alloys.

FR Acier Inoxydable, Alliages de Titane, Titane, Alliages de et Résistance à la Chaleur.

DE Rostfreier Stahl, Titan, Warmfeste und Legierungen.



ALTIN TITAN



ESPECIAL TITANIO Y ALEACIONES NICKEL

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYRUX-4030U11R	3	6	8	11	0,07	57	23,95 €
HYRUX-4030U20R	3	6	8	20	0,07	57	23,95 €
HYRUX-4040U14R	4	6	11	14	0,09	57	23,95 €
HYRUX-4040U20R	4	6	11	20	0,09	57	23,95 €
HYRUX-4050U16R	5	6	13	16	0,12	57	23,95 €
HYRUX-4050U21R	5	6	13	21	0,12	57	23,95 €
HYRUX-4060U21R	6	6	13	21	0,2	57	23,95 €
HYRUX-4080U27R	8	8	19	27	0,25	63	29,65 €
HYRUX-4100U32R	10	10	22	32	0,35	73	42,70 €
HYRUX-4120U38R	12	12	26	38	0,35	83	59,97 €
HYRUX-4140U40R	14	14	30	40	0,4	84	75,70 €
HYRUX-4160U44R	16	16	32	44	0,5	92	107,83 €
HYRUX-4200U55R	20	20	38	55	0,5	104	156,23 €

Z4 HYRUX TITANIO: FRESA H. V. 43°/45° Cuello Rebajado WELDOM CHAFLAN EN ESQUINA / WELDOM DIN6535 / ALTO RENDIMIENTO

EN Z4 HYRUX TITANIUM: UNEQUAL HELIX ANGLES 43-35° | W. DIN6535 | R. NECK | HIGH PERFORMANCE

FR Z4 HYRUX TITANIUM: HÉLICE DIFFÉRENTE 43-35° | W. DIN6535 | DE HAUTE PERFORMANCE


DE Z4 HYRUX TITANIUM: UNGLEICHER DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero Inoxidable, Titanio, Aleaciones Titanio y Aleaciones Resistentes al Calor.


EN Stainless Steel, Titanium, Titanium Alloys and Heat Resistance Alloys.

FR Acier Inoxydable, Alliages de Titanie, Titane, Alliages de et Résistance à la Chaleur.

DE Rostfreier Stahl, Titan, Warmfeste und Legierungen.



ALTIN TITAN



ESPECIAL TITANIO Y ALEACIONES NICKEL. WELDOM DIN6535

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	Lc	U	C-45°	L	
HYRUX-4030U11RW	3	6	8	11	0,07	57	26,15 €
HYRUX-4030U20RW	3	6	8	20	0,07	57	26,15 €
HYRUX-4040U14RW	4	6	11	14	0,09	57	26,15 €
HYRUX-4040U20RW	4	6	11	20	0,09	57	26,15 €
HYRUX-4050U16RW	5	6	13	16	0,12	57	26,15 €
HYRUX-4050U21RW	5	6	13	21	0,12	57	26,15 €
HYRUX-4060U21RW	6	6	13	21	0,2	57	26,15 €
HYRUX-4080U27RW	8	8	19	27	0,25	63	32,80 €
HYRUX-4100U32RW	10	10	22	32	0,35	73	46,60 €
HYRUX-4120U38RW	12	12	26	38	0,35	83	63,72 €
HYRUX-4140U40RW	14	14	30	40	0,4	84	80,85 €
HYRUX-4160U44RW	16	16	32	44	0,5	92	112,78 €
HYRUX-4200U55RW	20	20	38	55	0,5	104	161,93 €

Z5 HELIX: FRESA H.V. 43°/45° Cuello Rebajado 1°. Chaflán <55HRC

CHAFLAN EN ESQUINA / ALTO RENDIMIENTO / MULTIUSO

EN Z5 HELIX: UNEQUAL HELIX ANGLES 43-35° | REDUCED NECK | MULTIURPOSE | HIGH PERFORMANCE

FR Z5 HELIX: HÉLICE DIFFÉRENTE 43-35° | DE HAUTE PERFORMANCE


DE Z5 HELIX: U. DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
HELIX-06K01-C	6	6	14	—	0,1	53	28,60 €
HELIX-06K01-M	6	6	14	32	0,1	65	33,10 €
HELIX-06K01-L	6	6	14	42	0,1	75	34,80 €
HELIX-06K01-LL	6	6	14	51	0,1	81	39,50 €
HELIX-08K01-C	8	8	18	—	0,1	60	37,15 €
HELIX-08K01-M	8	8	18	42	0,1	75	40,00 €
HELIX-08K01-L	8	8	18	58	0,1	90	45,60 €
HELIX-08K01-LL	8	8	18	71	0,1	109	52,40 €
HELIX-10K015-C	10	10	22	—	0,15	65	48,50 €
HELIX-10K015-M	10	10	22	51	0,15	81	54,70 €
HELIX-10K015-L	10	10	22	71	0,15	109	64,60 €
HELIX-10K015-LL	10	10	22	82	0,15	109	65,70 €
HELIX-12K02-C	12	12	26	—	0,2	81	79,60 €
HELIX-12K02-M	12	12	26	51	0,2	81	85,90 €
HELIX-12K02-L	12	12	26	71	0,2	109	99,95 €
HELIX-12K02-LL	12	12	26	86	0,2	117	100,50 €

I Z5 HELIX: FRESA H.V. 43°/45° Cuello Rebajado 1°. Chaflán <55HRC CHAFLAN EN ESQUINA / ALTO RENDIMIENTO / MULTIUSO

EN Z5 HELIX: UNEQUAL HELIX ANGLES 43-35° | REDUCED NECK | MULTIURPOSE | HIGH PERFORMANCE

FR Z5 HELIX: HÉLICE DIFFÉRENTE 43-35° | DE HAUTE PERFORMANCE

DE Z5 HELIX: U. DRALLWINKEL 43-35° | HOCHLEISTUNGSBEARBEITUNG



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
HELIX-16K02-C	16	16	38	–	0,2	81	109,65 €
HELIX-16K02-M	16	16	38	61	0,2	109	121,80 €
HELIX-16K02-L	16	16	38	76	0,2	109	123,60 €
HELIX-16K02-LL	16	16	38	101	0,2	150	171,30 €
HELIX-20K02-C	20	20	45	–	0,2	100	166,20 €
HELIX-20K02-M	20	20	45	71	0,2	109	183,90 €
HELIX-20K02-L	20	20	45	86	0,2	130	196,90 €
HELIX-20K02-LL	20	20	45	101	0,2	150	255,80 €

Z5 HELIX: FRESA H.V. 43°/45° Cuello Rebajado 1°. Chaflán <65HRC

CHAFLAN EN ESQUINA / ALTO RENDIMIENTO / MULTIUSOS

EN Z5 HELIX: U.H.A. 43-35° | REDUCED NECK 1° | MULTIURPOSE | HIGH PERFORMANCE

FR Z5 HELIX: H.D. 43-35° | DE HAUTE PERFORMANCE


DE Z5 HELIX: U.D. 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
S-HELIX-06K01-C	6	6	14	—	0,1	53	31,45 €
S-HELIX-06K01-M	6	6	14	32	0,1	65	36,40 €
S-HELIX-06K01-L	6	6	14	42	0,1	75	38,30 €
S-HELIX-06K01-LL	6	6	14	51	0,1	81	43,50 €
S-HELIX-08K01-C	8	8	18	—	0,1	60	40,90 €
S-HELIX-08K01-M	8	8	18	42	0,1	75	44,00 €
S-HELIX-08K01-L	8	8	18	58	0,1	90	50,20 €
S-HELIX-08K01-LL	8	8	18	71	0,1	109	57,70 €
S-HELIX-10K015-C	10	10	22	—	0,15	65	53,50 €
S-HELIX-10K015-M	10	10	22	51	0,15	81	60,20 €
S-HELIX-10K015-L	10	10	22	71	0,15	109	71,00 €
S-HELIX-10K015-LL	10	10	22	82	0,15	109	72,30 €
S-HELIX-12K02-C	12	12	26	—	0,2	81	87,60 €
S-HELIX-12K02-M	12	12	26	51	0,2	81	94,50 €
S-HELIX-12K02-L	12	12	26	71	0,2	109	109,70 €
S-HELIX-12K02-LL	12	12	26	86	0,2	117	111,80 €

I Z5 HELIX: FRESA H.V. 43°/45° Cuello Rebajado 1°. Chaflán <65HRC CHAFLAN EN ESQUINA / ALTO RENDIMIENTO / MULTIUSOS

EN Z5 HELIX: U.H.A. 43-35° | REDUCED NECK 1° | MULTIURPOSE | HIGH PERFORMANCE

FR Z5 HELIX: H.D. 43-35° | DE HAUTE PERFORMANCE

DE Z5 HELIX: U.D. 43-35° | HOCHLEISTUNGSBEARBEITUNG



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
S-HELIX-16K02-C	16	16	38	–	0,2	81	117,50 €
S-HELIX-16K02-M	16	16	38	61	0,2	109	130,30 €
S-HELIX-16K02-L	16	16	38	76	0,2	109	132,20 €
S-HELIX-16K02-LL	16	16	38	101	0,2	150	183,30 €
S-HELIX-20K02-C	20	20	45	–	0,2	100	177,85 €
S-HELIX-20K02-M	20	20	45	71	0,2	109	196,80 €
S-HELIX-20K02-L	20	20	45	86	0,2	130	210,70 €
S-HELIX-20K02-LL	20	20	45	101	0,2	150	273,70 €

Z5 HELIX: FRESA H.V. 43°/45° Chaflán <56HRC. Refrigeración central CHAFLAN EN ESQUINA / CUELLO REBAJADO 1° / ALTO RENDIMIENTO

EN Z5 HELIX: UNEQUAL HELIX ANGLES 43-35° | R. NECK 1° | CENTRAL COOLANT | HIGH PERFORMANCE

FR Z5 HELIX: HÉLICE DIFFÉRENTE 43-35°


DE Z5 HELIX: UNGLEICHER DRALLWINKEL 43-35°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Copper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
HELIX-06K01-C-O	6	6	14	—	0,1	53	34,50 €
HELIX-06K01-M-O	6	6	14	32	0,1	65	40,70 €
HELIX-06K01-L-O	6	6	14	42	0,1	75	42,40 €
HELIX-06K01-LL-O	6	6	14	51	0,1	81	47,20 €
HELIX-08K01-C-O	8	8	18	—	0,1	60	44,80 €
HELIX-08K01-M-O	8	8	18	42	0,1	75	50,10 €
HELIX-08K01-L-O	8	8	18	58	0,1	90	55,70 €
HELIX-08K01-LL-O	8	8	18	71	0,1	109	62,50 €
HELIX-10K015-C-O	10	10	22	—	0,15	65	60,50 €
HELIX-10K015-M-O	10	10	22	51	0,15	81	66,70 €
HELIX-10K015-L-O	10	10	22	71	0,15	109	80,75 €
HELIX-10K015-LL-O	10	10	22	82	0,15	109	82,00 €
HELIX-12K02-C-O	12	12	26	—	0,2	81	95,80 €
HELIX-12K02-M-O	12	12	26	51	0,2	81	102,00 €
HELIX-12K02-L-O	12	12	26	71	0,2	109	120,30 €
HELIX-12K02-LL-O	12	12	26	86	0,2	117	121,90 €

I Z5 HELIX: FRESA H.V. 43°/45° Chaflán <56HRC. Refrigeración central CHAFLAN EN ESQUINA / CUELLO REBAJADO 1° / ALTO RENDIMIENTO

EN Z5 HELIX: UNEQUAL HELIX ANGLES 43-35° | R. NECK 1° | CENTRAL COOLANT | HIGH PERFORMANCE

FR Z5 HELIX: HÉLICE DIFFÉRENTE 43-35°

DE Z5 HELIX: UNGLEICHER DRALLWINKEL 43-35°



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	C-45°	L	
HELIX-16K02-C-O	16	16	38	–	0,2	81	130,90 €
HELIX-16K02-M-O	16	16	38	61	0,2	109	149,80 €
HELIX-16K02-L-O	16	16	38	76	0,2	109	151,70 €
HELIX-16K02-LL-O	16	16	38	101	0,2	150	199,40 €
HELIX-20K02-C-O	20	20	45	–	0,2	100	197,70 €
HELIX-20K02-M-O	20	20	45	71	0,2	109	226,24 €
HELIX-20K02-L-O	20	20	45	86	0,2	130	242,20 €
HELIX-20K02-LL-O	20	20	45	101	0,2	150	296,70 €

I Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <56HRC

MULTIUSOS / CUELLO REBAJADO 1°

- EN** Z5 HELIX: U.H.A. 43-35° | R. NECK 1° | HIGH PERFORMANCE | MULTI PURPOSE | CORNER RADIUS
FR Z5 HELIX: H.D. 43-35° | R. NECK 1° | HAUTE PERFORMANCE
DE Z5 HELIX: U. D. 43-35° | R. NECK 1° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
HELIX-06R05-C	6	6	14	—	0,5	53	33,60 €
HELIX-06R05-M	6	6	14	32	0,5	65	38,90 €
HELIX-06R05-L	6	6	14	42	0,5	75	40,90 €
HELIX-06R05-LL	6	6	14	51	0,5	81	46,50 €
HELIX-08R05-C	8	8	18	—	0,5	60	43,70 €
HELIX-08R05-M	8	8	18	42	0,5	75	47,00 €
HELIX-08R05-L	8	8	18	58	0,5	90	53,60 €
HELIX-08R05-LL	8	8	18	71	0,5	109	61,50 €
HELIX-10R05-C	10	10	22	—	0,5	65	57,00 €
HELIX-10R05-M	10	10	22	51	0,5	81	64,30 €
HELIX-10R05-L	10	10	22	71	0,5	109	76,00 €
HELIX-10R05-LL	10	10	22	82	0,5	109	77,20 €
HELIX-12R1-C	12	12	26	—	1	81	93,60 €
HELIX-12R1-M	12	12	26	51	1	81	101,00 €
HELIX-12R1-L	12	12	26	71	1	109	117,50 €
HELIX-12R1-LL	12	12	26	86	1	117	119,30 €

I Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <56HRC

MULTIUSOS / CUELLO REBAJADO 1°

EN Z5 HELIX: U.H.A. 43-35° | R. NECK 1° | HIGH PERFORMANCE | MULTI PURPOSE | CORNER RADIUS

FR Z5 HELIX: H.D. 43-35° | R. NECK 1° | HAUTE PERFORMANCE

DE Z5 HELIX: U. D. 43-35° 1° | R. NECK 1° | HOCHLEISTUNGSBEARBEITUNG



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
HELIX-16R2-C	16	16	38	—	2	81	129,00 €
HELIX-16R2-M	16	16	38	61	2	109	143,20 €
HELIX-16R2-L	16	16	38	76	2	109	145,40 €
HELIX-16R2-LL	16	16	38	101	2	150	201,50 €
HELIX-20R2-C	20	20	45	—	2	100	194,50 €
HELIX-20R2-M	20	20	45	71	2	109	215,20 €
HELIX-20R2-L	20	20	45	86	2	130	230,40 €
HELIX-20R2-LL	20	20	45	101	2	150	299,30 €

Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <65HRC

MULTIUSOS / ALTO RENDIMIENTO / CUELLO REBAJADO 1°

EN Z5 HELIX: U.H. A. 43-35° | REDUCED NECK 1° | HIGH PERFORMANCE | MULTI PURPOSE | CORNER RADIUS

FR Z5 HELIX: H.D. 43-35° | DE HAUTE PERFORMANCE


DE Z5 HELIX: U. D. 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.


EN Steel, Stainless Steel, Cast Iron, Copper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
S-HELIX-06R05-C	6	6	14	—	0,5	53	36,96 €
S-HELIX-06R05-M	6	6	14	32	0,5	65	42,79 €
S-HELIX-06R05-L	6	6	14	42	0,5	75	44,99 €
S-HELIX-06R05-LL	6	6	14	51	0,5	81	51,15 €
S-HELIX-08R05-C	8	8	18	—	0,5	60	48,07 €
S-HELIX-08R05-M	8	8	18	42	0,5	75	51,70 €
S-HELIX-08R05-L	8	8	18	58	0,5	90	58,96 €
S-HELIX-08R05-LL	8	8	18	71	0,5	109	67,65 €
S-HELIX-10R05-C	10	10	22	—	0,5	65	62,70 €
S-HELIX-10R05-M	10	10	22	51	0,5	81	70,73 €
S-HELIX-10R05-L	10	10	22	71	0,5	109	83,60 €
S-HELIX-10R05-LL	10	10	22	82	0,5	109	84,92 €
S-HELIX-12R1-C	12	12	26	—	1	81	102,96 €
S-HELIX-12R1-M	12	12	26	51	1	81	111,10 €
S-HELIX-12R1-L	12	12	26	71	1	109	129,25 €
S-HELIX-12R1-LL	12	12	26	86	1	117	131,23 €

I Z5 HELIX: FRESA HELICE VARIABLE 43°/45° Radio <65HRC

MULTIUSOS / ALTO RENDIMIENTO / CUELLO REBAJADO 1°

EN Z5 HELIX: U.H. A. 43-35° | REDUCED NECK 1° | HIGH PERFORMANCE | MULTI PURPOSE | CORNER RADIUS

FR Z5 HELIX: H.D. 43-35° | DE HAUTE PERFORMANCE

DE Z5 HELIX: U. D. 43-35° | HOCHLEISTUNGSBEARBEITUNG



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
S-HELIX-16R2-C	16	16	38	–	2	81	138,03 €
S-HELIX-16R2-M	16	16	38	61	2	109	153,22 €
S-HELIX-16R2-L	16	16	38	76	2	109	155,58 €
S-HELIX-16R2-LL	16	16	38	101	2	150	215,61 €
S-HELIX-20R2-C	20	20	45	–	2	100	208,12 €
S-HELIX-20R2-M	20	20	45	71	2	109	230,26 €
S-HELIX-20R2-L	20	20	45	86	2	130	246,53 €
S-HELIX-20R2-LL	20	20	45	101	2	150	320,25 €

Z5 HELIX: FRESA H.V. 43°/45° Radio <55HRC Refrigeración central MULTIUSOS / ALTO RENDIMIENTO / CUELLO REBAJADO 1°


EN Z5 HELIX: U.H.A. 43-35° | R. NECK 1° | H. PERFORMANCE | MULTI PURPOSE | CORNER RADIUS | COOLANT
FR Z5 HELIX: H. D. 43-35° | HAUTE PERFORMANCE
DE Z5 HELIX: U.D. 43-35° | HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN TITAN



CUELLO REBAJADO A 1°

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
HELIX-06R05-C-O	6	6	14	—	0,5	53	40,60 €
HELIX-06R05-M-O	6	6	14	32	0,5	65	47,90 €
HELIX-06R05-L-O	6	6	14	42	0,5	75	49,90 €
HELIX-06R05-LL-O	6	6	14	51	0,5	81	55,50 €
HELIX-08R05-C-O	8	8	18	—	0,5	60	52,70 €
HELIX-08R05-M-O	8	8	18	42	0,5	75	59,00 €
HELIX-08R05-L-O	8	8	18	58	0,5	90	65,60 €
HELIX-08R05-LL-O	8	8	18	71	0,5	109	73,50 €
HELIX-10R05-C-O	10	10	22	—	0,5	65	71,00 €
HELIX-10R05-M-O	10	10	22	51	0,5	81	78,30 €
HELIX-10R05-L-O	10	10	22	71	0,5	109	95,00 €
HELIX-10R05-LL-O	10	10	22	82	0,5	109	96,20 €
HELIX-12R1-C-O	12	12	26	—	1	81	112,60 €

Z5 HELIX: FRESA H.V. 43°/45° Radio <55HRC Refrigeración central MULTIUSOS / ALTO RENDIMIENTO / CUELLO REBAJADO 1°

EN Z5 HELIX: U.H.A. 43-35° | R. NECK 1° | H. PERFORMANCE | MULTI PURPOSE | CORNER RADIUS | COOLANT

FR Z5 HELIX: H. D. 43-35° | HAUTE PERFORMANCE

DE Z5 HELIX: U.D. 43-35° | HOCHLEISTUNGSBEARBEITUNG



Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	C	R	L	
HELIX-12R1-M-O	12	12	26	51	1	81	120,00 €
HELIX-12R1-L-O	12	12	26	71	1	109	141,50 €
HELIX-12R1-LL-O	12	12	26	86	1	117	143,30 €
HELIX-16R2-C-O	16	16	38	—	2	81	154,00 €
HELIX-16R2-M-O	16	16	38	61	2	109	176,20 €
HELIX-16R2-L-O	16	16	38	76	2	109	178,40 €
HELIX-16R2-LL-O	16	16	38	101	2	150	234,50 €
HELIX-20R2-C-O	20	20	45	—	2	100	231,40 €
HELIX-20R2-M-O	20	20	45	71	2	109	264,70 €
HELIX-20R2-L-O	20	20	45	86	2	130	283,40 €
HELIX-20R2-LL-O	20	20	45	101	2	150	347,20 €

I Z4 HYPERBALL: FRESA HÉLICE VARIABLE ESFÉRICA

EN Z4 HYPERBALL: BALL NOSE END MILL | UNEQUAL HELIX ANGLES

FR Z4 HYPERBALL: FRAISE CYLINDRIQUE HÉMISPHERIQUE | HÉLICE DIFFÉRENTE


DE Z4 HYPERBALL: UNGLEICHER DRALLWINKEL | KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



Ref.	Dimensiones (mm)				Precio €
4 Flutes (Z4)	Dc	d	Lc	L	
HPB-4060	6	6	8	50	19,20 €
HPB-4060L	6	6	8	80	25,18 €
HPB-4060XL	6	6	8	100	27,73 €
HPB-4060XXL	6	6	8	150	36,54 €
HPB-4080	8	8	10	60	24,58 €
HPB-4080L	8	8	10	100	34,84 €
HPB-4080XL	8	8	10	150	47,03 €
HPB-4100	10	10	13	72	36,34 €
HPB-4100L	10	10	13	100	50,07 €
HPB-4100XL	10	10	13	150	66,76 €
HPB-4100XXL	10	10	13	200	93,76 €
HPB-4120	12	12	15	75	49,77 €
HPB-4120L	12	12	15	100	70,13 €
HPB-4120XL	12	12	15	150	97,65 €
HPB-4120XXL	12	12	15	200	114,47 €

I Z4 HYPERBALL: FRESA HÉLICE VARIABLE ESFÉRICA. CÓNICA 1,5°


- EN** Z4 HYPERBALL: BALL NOSE END MILL | UNEQUAL HELIX ANGLES | CONICAL 1,5°
FR Z4 HYPERBALL: FRAISE CYLINDRIQUE HÉMISPHERIQUE | HÉLICE DIFFÉRENTE
DE Z4 HYPERBALL: UNGLEICHER DRALLWINKEL | KUGELFRÄSER

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



CONICAS CON 1,5°

Ref.	Dimensiones (mm)					Precio €
4 Flutes (Z4)	Dc	d	Lc	C	L	
HPB-CON4060	6	8	8	32	80	35,82 €
HPB-CON4060L	6	8	8	45	108	48,09 €
HPB-CON4080	8	10	10	32	80	51,64 €
HPB-CON4080L	8	10	10	48	108	63,12 €

FRESA TURBO ALTO AVANCE Serie Normal

- EN** TURBO HIGH FEED END MILL | Normal series
FR TURBO FRAISE CYLINDRIQUE DE HAUTE AVANCE | Normale
DE TURBO HOCHVORSCHUBFRÄSER | Normale

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



SERIE NORMAL

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
T-SEM4030X-R0,5	3	6	0,5	1,5	12	60	29,55 €
T-SEM4040X-R0,5	4	6	0,5	2	12	60	29,55 €
T-SEM4060X-R1.0	6	6	1	3	14	60	29,55 €
T-SEM4080X-R2.0	8	8	2	4	18	60	37,75 €
T-SEM4100X-R2.0	10	10	2	5	20	72	45,50 €
T-SEM4120X-R2.0	12	12	2	6	22	83	63,15 €

L1.= Long rebajada del cuello
d.= diametro mango

I FRESA TURBO ALTO AVANCE Serie Larga


- EN** TURBO HIGH FEED END MILL | Long series
FR TURBO FRAISE CYLINDRIQUE DE HAUTE AVANCE | Longue
DE TURBO HOCHVORSCHUBFRÄSER | Lange

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 65 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 65 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 65 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 65 HRC.



ALTISIN



SERIE LARGA

Ref.	Dimensiones (mm)						Precio €
4 Flutes (Z4)	Dc	d	R	Lc	U	L	
T-SEM4030XL-R0,5	3	6	0,5	1,5	20	80	36,84 €
T-SEM4040XL-R0,5	4	6	0,5	2	20	80	36,84 €
T-SEM4060XL-R1.0	6	6	1	3	30	80	36,84 €
T-SEM4080XL-R2.0	8	8	2	4	40	80	46,43 €
T-SEM4100XL-R2.0	10	10	2	5	50	100	55,97 €
T-SEM4120XL-R2.0	12	12	2	6	50	110	77,67 €

L1.= Long rebajada del cuello
d.= diametro mango

I FRESA PARA ACHAFLANAR 60°

EN COUNTERSINKER, 60°

FR CHAMFREIN, 60°

DE KEGELSENKER, 60°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN



Ref.	Dimensiones (mm)				Precio €
	Dc	d	Z	L	
ACH60-SEM4040	4	4	4	50	10,75 €
ACH60-SEM4060	6	6	4	50	15,25 €
ACH60-SEM4080	8	8	4	60	19,50 €
ACH60-SEM4100	10	10	4	72	28,90 €
ACH60-SEM6100	10	10	6	72	28,90 €
ACH60-SEM4120	12	12	4	75	39,50 €
ACH60-SEM6120	12	12	6	75	39,50 €

I FRESA PARA ACHAFLANAR 90°

EN COUNTERSINKER, 90°

FR CHAMFREIN, 90°

DE KEGELSENKER, 90°

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN



Ref.	Dimensiones (mm)				Precio €
REF.	Dc	d	Z	L	
ACH90-SEM4040	4	4	4	50	10,75 €
ACH90-SEM4060	6	6	4	50	15,25 €
ACH90-SEM4080	8	8	4	60	19,50 €
ACH90-SEM6080	8	8	6	60	19,50 €
ACH90-SEM4100	10	10	4	72	28,90 €
ACH90-SEM6100	10	10	6	72	28,90 €
ACH90-SEM4120	12	12	4	75	39,50 €
ACH90-SEM6120	12	12	6	75	39,50 €
ACH90-SEM4160	16	16	4	92	78,50 €
ACH90-SEM6160	16	16	6	92	78,50 €

I Z5 TROCOIDAL: FRESA DE ALTO RENDIMIENTO CUELLO REBAJADO

EN Z5 TROCHOIDAL. HIGH PERFORMANCE END MILL | REDUCED NECK

FR Z5 TROCOIDALE. FRAISE DE HAUTE PERFORMANCE


DE Z5 TROCHOIDALFRÄSER. UNGLEICHER DRALLWINKEL HOCHLEISTUNGSBEARBEITUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN NANO



ALTO RENDIMIENTO

Ref.	Dimensiones (mm)						Precio €
5 Flutes (Z5)	Dc	d	Lc	U	C-45°	L	
TR-5060U25H	6	6	18	25	0,1	62	23,95 €
TR-5080U30H	8	8	24	30	0,15	70	29,65 €
TR-5100U35H	10	10	30	35	0,2	80	42,70 €
TR-5120U45H	12	12	36	45	0,2	94	59,97 €
TR-5160U55H	16	16	48	55	0,4	110	107,83 €
TR-5200U70H	20	20	60	70	0,4	126	156,23 €

06

BROCAS de metal duro

SOLID CARBIDE DRILL
FORET EN CARBURE MONOBLOC
VOLLHARTMETALLBOHRER

3XD BROCA DE METAL DURO

DIN6537K


- EN** 3xD SOLID CARBIDE DRILL | DIN6537K
FR 3xD FORET EN CARBURE MONOBLOC | DIN6537K
DE 3xD VOLLHARTMETALLBOHRER | DIN6537K

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN



DIN6537K

Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0300D3	3	6	20	14	62	16,96 €
DR0310D3	3,1	6	20	14	62	16,96 €
DR0320D3	3,2	6	20	14	62	16,96 €
DR0330D3	3,3	6	20	14	62	16,96 €
DR0340D3	3,4	6	20	14	62	16,96 €
DR0350D3	3,5	6	20	14	62	16,96 €
DR0360D3	3,6	6	20	14	62	16,96 €
DR0370D3	3,7	6	20	14	62	16,96 €
DR0380D3	3,8	6	24	17	66	16,96 €
DR0390D3	3,9	6	24	17	66	16,96 €
DR0400D3	4	6	24	17	66	16,96 €
DR0410D3	4,1	6	24	17	66	16,96 €
DR0420D3	4,2	6	24	17	66	16,96 €
DR0430D3	4,3	6	24	17	66	16,96 €
DR0440D3	4,4	6	24	17	66	16,96 €
DR0450D3	4,5	6	24	17	66	16,96 €
DR0460D3	4,6	6	24	17	66	16,96 €

3XD BROCA DE METAL DURO

DIN6537K



Ref.	Dimensiones (mm)					Precio €
5 Flutes (Z5)	Dc	d	U	Lc	L	
DR0470D3	4,7	6	24	17	66	16,96 €
DR0480D3	4,8	6	28	20	66	16,96 €
DR0490D3	4,9	6	28	20	66	16,96 €
DR0500D3	5	6	28	20	66	16,96 €
DR0510D3	5,1	6	28	20	66	16,96 €
DR0520D3	5,2	6	28	20	66	16,96 €
DR0530D3	5,3	6	28	20	66	16,96 €
DR0540D3	5,4	6	28	20	66	16,96 €
DR0550D3	5,5	6	28	20	66	16,96 €
DR0560D3	5,6	6	28	20	66	16,96 €
DR0570D3	5,7	6	28	20	66	16,96 €
DR0580D3	5,8	6	28	20	66	16,96 €
DR0590D3	5,9	6	28	20	66	16,96 €
DR0600D3	6	6	28	20	66	16,96 €
DR0610D3	6,1	8	34	24	79	19,95 €
DR0620D3	6,2	8	34	24	79	19,95 €
DR0630D3	6,3	8	34	24	79	19,95 €
DR0640D3	6,4	8	34	24	79	19,95 €
DR0650D3	6,5	8	34	24	79	19,95 €
DR0660D3	6,6	8	34	24	79	19,95 €
DR0670D3	6,7	8	34	24	79	19,95 €
DR0680D3	6,8	8	34	24	79	19,95 €
DR0690D3	6,9	8	34	24	79	19,95 €
DR0700D3	7	8	34	24	79	19,95 €
DR0710D3	7,1	8	41	29	79	19,95 €
DR0720D3	7,2	8	41	29	79	19,95 €
DR0730D3	7,3	8	41	29	79	19,95 €
DR0740D3	7,4	8	41	29	79	19,95 €
DR0750D3	7,5	8	41	29	79	19,95 €
DR0760D3	7,6	8	41	29	79	19,95 €
DR0770D3	7,7	8	41	29	79	19,95 €

I 3XD BROCA DE METAL DURO

DIN6537K



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0780D3	7,8	8	41	29	79	19,95 €
DR0790D3	7,9	8	41	29	79	19,95 €
DR0800D3	8	8	41	29	79	19,95 €
DR0810D3	8,1	10	47	35	89	25,89 €
DR0820D3	8,2	10	47	35	89	25,89 €
DR0830D3	8,3	10	47	35	89	25,89 €
DR0840D3	8,4	10	47	35	89	25,89 €
DR0850D3	8,5	10	47	35	89	25,89 €
DR0860D3	8,6	10	47	35	89	25,89 €
DR0870D3	8,7	10	47	35	89	25,89 €
DR0880D3	8,8	10	47	35	89	25,89 €
DR0890D3	8,9	10	47	35	89	25,89 €
DR0900D3	9	10	47	35	89	25,89 €
DR0910D3	9,1	10	47	35	89	25,89 €
DR0920D3	9,2	10	47	35	89	25,89 €
DR0930D3	9,3	10	47	35	89	25,89 €
DR0940D3	9,4	10	47	35	89	25,89 €
DR0950D3	9,5	10	47	35	89	25,89 €
DR0960D3	9,6	10	47	35	89	25,89 €
DR0970D3	9,7	10	47	35	89	25,89 €
DR0980D3	9,8	10	47	35	89	25,89 €
DR0990D3	9,9	10	47	35	89	25,89 €
DR1000D3	10	10	47	35	89	25,89 €
DR1010D3	10,1	12	55	40	102	37,77 €
DR1020D3	10,2	12	55	40	102	37,77 €
DR1030D3	10,3	12	55	40	102	37,77 €
DR1040D3	10,4	12	55	40	102	37,77 €
DR1050D3	10,5	12	55	40	102	37,77 €
DR1060D3	10,6	12	55	40	102	37,77 €
DR1070D3	10,7	12	55	40	102	37,77 €
DR1080D3	10,8	12	55	40	102	37,77 €
DR1090D3	10,9	12	55	40	102	37,77 €
DR1100D3	11	12	55	40	102	37,77 €

3XD BROCA DE METAL DURO

DIN6537K



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR1110D3	11,1	12	55	40	102	37,77 €
DR1120D3	11,2	12	55	40	102	37,77 €
DR1130D3	11,3	12	55	40	102	37,77 €
DR1140D3	11,4	12	55	40	102	37,77 €
DR1150D3	11,5	12	55	40	102	37,77 €
DR1160D3	11,6	12	55	40	102	37,77 €
DR1170D3	11,7	12	55	40	102	37,77 €
DR1180D3	11,8	12	55	40	102	37,77 €
DR1190D3	11,9	12	55	40	102	37,77 €
DR1200D3	12	12	55	40	102	37,77 €
DR1220D3	12,2	14	60	43	107	48,55 €
DR1250D3	12,5	14	60	43	107	48,55 €
DR1270D3	12,7	14	60	43	107	48,55 €
DR1280D3	12,8	14	60	43	107	48,55 €
DR1300D3	13	14	60	43	107	48,55 €
DR1310D3	13,1	14	60	43	107	48,55 €
DR1350D3	13,5	14	60	43	107	48,55 €
DR1380D3	13,8	14	60	43	107	48,55 €
DR1400D3	14	14	60	43	107	48,55 €
DR1450D3	14,5	16	65	45	115	71,65 €
DR1480D3	14,8	16	65	45	115	71,65 €
DR1500D3	15	16	65	45	115	71,65 €
DR1550D3	15,5	16	65	45	115	71,65 €
DR1600D3	16	16	65	45	115	71,65 €
DR1650D3	16,5	18	73	51	123	109,23 €
DR1700D3	17	18	73	51	123	109,23 €
DR1750D3	17,5	18	73	51	123	109,23 €
DR1800D3	18	18	73	51	123	109,23 €
DR1850D3	18,5	20	79	55	131	129,37 €
DR1900D3	19	20	79	55	131	129,37 €
DR1950D3	19,5	20	79	55	131	129,37 €
DR2000D3	20	20	79	55	131	129,37 €

5XD BROCA PARA METAL DURO Con refrigeración DIN6537L

EN 5xD SOLID CARBIDE DRILL | DIN6537L | INTERNAL COOLANT

FR 5xD FORET EN CARBURE MONOBLOC | DIN6537L | AVEC TROUS DE LUBRIFICATION



DE 5xD VOLLHARTMETALLBOHRER | DIN6537L | INTEME KÜHLUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



Dc = tolerancia h8
d = tolerancia h6

DIN6537L

Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0300D5CH	3	6	28	23	66	38,12 €
DR0310D5CH	3,1	6	28	23	66	38,12 €
DR0320D5CH	3,2	6	28	23	66	38,12 €
DR0330D5CH	3,3	6	28	23	66	38,12 €
DR0340D5CH	3,4	6	28	23	66	38,12 €
DR0350D5CH	3,5	6	28	23	66	38,12 €
DR0360D5CH	3,6	6	28	23	66	38,12 €
DR0370D5CH	3,7	6	28	23	66	38,12 €
DR0380D5CH	3,8	6	36	29	74	38,12 €
DR0390D5CH	3,9	6	36	29	74	38,12 €
DR0400D5CH	4	6	36	29	74	38,12 €
DR0410D5CH	4,1	6	36	29	74	38,12 €
DR0420D5CH	4,2	6	36	29	74	38,12 €
DR0430D5CH	4,3	6	36	29	74	38,12 €
DR0440D5CH	4,4	6	36	29	74	38,12 €
DR0450D5CH	4,5	6	36	29	74	38,12 €
DR0460D5CH	4,6	6	36	29	74	38,12 €

5XD BROCA PARA METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0470D5CH	4,7	6	36	29	74	38,12 €
DR0480D5CH	4,8	6	44	35	82	38,12 €
DR0490D5CH	4,9	6	44	35	82	38,12 €
DR0500D5CH	5	6	44	35	82	38,12 €
DR0510D5CH	5,1	6	44	35	82	38,12 €
DR0520D5CH	5,2	6	44	35	82	38,12 €
DR0530D5CH	5,3	6	44	35	82	38,12 €
DR0540D5CH	5,4	6	44	35	82	38,12 €
DR0550D5CH	5,5	6	44	35	82	38,12 €
DR0560D5CH	5,6	6	44	35	82	38,12 €
DR0570D5CH	5,7	6	44	35	82	38,12 €
DR0580D5CH	5,8	6	44	35	82	38,12 €
DR0590D5CH	5,9	6	44	35	82	38,12 €
DR0600D5CH	6	6	44	35	82	38,12 €
DR0610D5CH	6,1	8	53	43	91	46,97 €
DR0620D5CH	6,2	8	53	43	91	46,97 €
DR0630D5CH	6,3	8	53	43	91	46,97 €
DR0640D5CH	6,4	8	53	43	91	46,97 €
DR0650D5CH	6,5	8	53	43	91	46,97 €
DR0660D5CH	6,6	8	53	43	91	46,97 €
DR0670D5CH	6,7	8	53	43	91	46,97 €
DR0680D5CH	6,8	8	53	43	91	46,97 €
DR0690D5CH	6,9	8	53	43	91	46,97 €
DR0700D5CH	7	8	53	43	91	46,97 €
DR0710D5CH	7,1	8	53	43	91	46,97 €
DR0720D5CH	7,2	8	53	43	91	46,97 €
DR0730D5CH	7,3	8	53	43	91	46,97 €
DR0740D5CH	7,4	8	53	43	91	46,97 €
DR0750D5CH	7,5	8	53	43	91	46,97 €
DR0760D5CH	7,6	8	53	43	91	46,97 €
DR0770D5CH	7,7	8	53	43	91	46,97 €

I 5XD BROCA PARA METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0780D5CH	7,8	8	53	43	91	46,97 €
DR0790D5CH	7,9	8	53	43	91	46,97 €
DR0800D5CH	8	8	53	43	91	46,97 €
DR0810D5CH	8,1	10	61	49	103	57,32 €
DR0820D5CH	8,2	10	61	49	103	57,32 €
DR0830D5CH	8,3	10	61	49	103	57,32 €
DR0840D5CH	8,4	10	61	49	103	57,32 €
DR0850D5CH	8,5	10	61	49	103	57,32 €
DR0860D5CH	8,6	10	61	49	103	57,32 €
DR0870D5CH	8,7	10	61	49	103	57,32 €
DR0880D5CH	8,8	10	61	49	103	57,32 €
DR0890D5CH	8,9	10	61	49	103	57,32 €
DR0900D5CH	9	10	61	49	103	57,32 €
DR0910D5CH	9,1	10	61	49	103	57,32 €
DR0920D5CH	9,2	10	61	49	103	57,32 €
DR0930D5CH	9,3	10	61	49	103	57,32 €
DR0940D5CH	9,4	10	61	49	103	57,32 €
DR0950D5CH	9,5	10	61	49	103	57,32 €
DR0960D5CH	9,6	10	61	49	103	57,32 €
DR0970D5CH	9,7	10	61	49	103	57,32 €
DR0980D5CH	9,8	10	61	49	103	57,32 €
DR0990D5CH	9,9	10	61	49	103	57,32 €
DR1000D5CH	10	10	61	49	103	57,32 €
DR1010D5CH	10,1	12	71	56	118	76,92 €
DR1020D5CH	10,2	12	71	56	118	76,92 €
DR1030D5CH	10,3	12	71	56	118	76,92 €
DR1040D5CH	10,4	12	71	56	118	76,92 €
DR1050D5CH	10,5	12	71	56	118	76,92 €
DR1060D5CH	10,6	12	71	56	118	76,92 €
DR1070D5CH	10,7	12	71	56	118	76,92 €
DR1080D5CH	10,8	12	71	56	118	76,92 €
DR1090D5CH	10,9	12	71	56	118	76,92 €
DR1100D5CH	11	12	71	56	118	76,92 €

5XD BROCA PARA METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR1110D5CH	11,1	12	71	56	118	76,92 €
DR1120D5CH	11,2	12	71	56	118	76,92 €
DR1130D5CH	11,3	12	71	56	118	76,92 €
DR1140D5CH	11,4	12	71	56	118	76,92 €
DR1150D5CH	11,5	12	71	56	118	76,92 €
DR1160D5CH	11,6	12	71	56	118	76,92 €
DR1170D5CH	11,7	12	71	56	118	76,92 €
DR1180D5CH	11,8	12	71	56	118	76,92 €
DR1190D5CH	11,9	12	71	56	118	76,92 €
DR1200D5CH	12	12	71	56	118	76,92 €
DR1220D5CH	12,2	14	77	60	124	106,74 €
DR1250D5CH	12,5	14	77	60	124	106,74 €
DR1270D5CH	12,7	14	77	60	124	106,74 €
DR1280D5CH	12,8	14	77	60	124	106,74 €
DR1300D5CH	13	14	77	60	124	106,74 €
DR1310D5CH	13,1	14	77	60	124	106,74 €
DR1350D5CH	13,5	14	77	60	124	106,74 €
DR1380D5CH	13,8	14	77	60	124	106,74 €
DR1400D5CH	14	14	77	60	124	106,74 €
DR1450D5CH	14,5	16	83	63	133	139,85 €
DR1480D5CH	14,8	16	83	63	133	139,85 €
DR1500D5CH	15	16	83	63	133	139,85 €
DR1550D5CH	15,5	16	83	63	133	139,85 €
DR1600D5CH	16	16	83	63	133	139,85 €
DR1650D5CH	16,5	18	93	71	143	204,55 €
DR1700D5CH	17	18	93	71	143	204,55 €
DR1750D5CH	17,5	18	93	71	143	204,55 €
DR1800D5CH	18	18	93	71	143	204,55 €
DR1850D5CH	18,5	20	101	77	153	239,55 €
DR1900D5CH	19	20	101	77	153	239,55 €
DR1950D5CH	19,5	20	101	77	153	239,55 €
DR2000D5CH	20	20	101	77	153	239,55 €

5XD BROCA DE METAL DURO

DIN6537L



- EN 5xD SOLID CARBIDE DRILL | DIN6537L
 FR 5xD FORET EN CARBURE MONOBLOC | DIN6537L
 DE 5xD VOLLHARTMETALLBOHRER | DIN6537L

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.


ALTIN


DIN6537L

Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0300D5	3	6	28	23	66	22,70 €
DR0310D5	3,1	6	28	23	66	22,70 €
DR0320D5	3,2	6	28	23	66	22,70 €
DR0330D5	3,3	6	28	23	66	22,70 €
DR0340D5	3,4	6	28	23	66	22,70 €
DR0350D5	3,5	6	28	23	66	22,70 €
DR0360D5	3,6	6	28	23	66	22,70 €
DR0370D5	3,7	6	28	23	66	22,70 €
DR0380D5	3,8	6	36	29	74	22,70 €
DR0390D5	3,9	6	36	29	74	22,70 €
DR0400D5	4	6	36	29	74	22,70 €
DR0410D5	4,1	6	36	29	74	22,70 €
DR0420D5	4,2	6	36	29	74	22,70 €
DR0430D5	4,3	6	36	29	74	22,70 €
DR0440D5	4,4	6	36	29	74	22,70 €
DR0450D5	4,5	6	36	29	74	22,70 €
DR0460D5	4,6	6	36	29	74	22,70 €

I 5XD BROCA DE METAL DURO

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0470D5	4,7	6	36	29	74	22,70 €
DR0480D5	4,8	6	44	35	82	22,70 €
DR0490D5	4,9	6	44	35	82	22,70 €
DR0500D5	5	6	44	35	82	22,70 €
DR0510D5	5,1	6	44	35	82	22,70 €
DR0520D5	5,2	6	44	35	82	22,70 €
DR0530D5	5,3	6	44	35	82	22,70 €
DR0540D5	5,4	6	44	35	82	22,70 €
DR0550D5	5,5	6	44	35	82	22,70 €
DR0560D5	5,6	6	44	35	82	22,70 €
DR0570D5	5,7	6	44	35	82	22,70 €
DR0580D5	5,8	6	44	35	82	22,70 €
DR0590D5	5,9	6	44	35	82	22,70 €
DR0600D5	6	6	44	35	82	22,70 €
DR0610D5	6,1	8	53	43	91	27,55 €
DR0620D5	6,2	8	53	43	91	27,55 €
DR0630D5	6,3	8	53	43	91	27,55 €
DR0640D5	6,4	8	53	43	91	27,55 €
DR0650D5	6,5	8	53	43	91	27,55 €
DR0660D5	6,6	8	53	43	91	27,55 €
DR0670D5	6,7	8	53	43	91	27,55 €
DR0680D5	6,8	8	53	43	91	27,55 €
DR0690D5	6,9	8	53	43	91	27,55 €
DR0700D5	7	8	53	43	91	27,55 €
DR0710D5	7,1	8	53	43	91	27,55 €
DR0720D5	7,2	8	53	43	91	27,55 €
DR0730D5	7,3	8	53	43	91	27,55 €
DR0740D5	7,4	8	53	43	91	27,55 €
DR0750D5	7,5	8	53	43	91	27,55 €
DR0760D5	7,6	8	53	43	91	27,55 €
DR0770D5	7,7	8	53	43	91	27,55 €

I 5XD BROCA DE METAL DURO

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0780D5	7,8	8	53	43	91	27,55 €
DR0790D5	7,9	8	53	43	91	27,55 €
DR0800D5	8	8	53	43	91	27,55 €
DR0810D5	8,1	10	61	49	103	37,92 €
DR0820D5	8,2	10	61	49	103	37,92 €
DR0830D5	8,3	10	61	49	103	37,92 €
DR0840D5	8,4	10	61	49	103	37,92 €
DR0850D5	8,5	10	61	49	103	37,92 €
DR0860D5	8,6	10	61	49	103	37,92 €
DR0870D5	8,7	10	61	49	103	37,92 €
DR0880D5	8,8	10	61	49	103	37,92 €
DR0890D5	8,9	10	61	49	103	37,92 €
DR0900D5	9	10	61	49	103	37,92 €
DR0910D5	9,1	10	61	49	103	37,92 €
DR0920D5	9,2	10	61	49	103	37,92 €
DR0930D5	9,3	10	61	49	103	37,92 €
DR0940D5	9,4	10	61	49	103	37,92 €
DR0950D5	9,5	10	61	49	103	37,92 €
DR0960D5	9,6	10	61	49	103	37,92 €
DR0970D5	9,7	10	61	49	103	37,92 €
DR0980D5	9,8	10	61	49	103	37,92 €
DR0990D5	9,9	10	61	49	103	37,92 €
DR1000D5	10	10	61	49	103	37,92 €
DR1010D5	10,1	12	71	56	118	52,74 €
DR1020D5	10,2	12	71	56	118	52,74 €
DR1030D5	10,3	12	71	56	118	52,74 €
DR1040D5	10,4	12	71	56	118	52,74 €
DR1050D5	10,5	12	71	56	118	52,74 €
DR1060D5	10,6	12	71	56	118	52,74 €
DR1070D5	10,7	12	71	56	118	52,74 €
DR1080D5	10,8	12	71	56	118	52,74 €
DR1090D5	10,9	12	71	56	118	52,74 €
DR1100D5	11	12	71	56	118	52,74 €

5XD BROCA DE METAL DURO

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR1110D5	11,1	12	71	56	118	52,74 €
DR1120D5	11,2	12	71	56	118	52,74 €
DR1130D5	11,3	12	71	56	118	52,74 €
DR1140D5	11,4	12	71	56	118	52,74 €
DR1150D5	11,5	12	71	56	118	52,74 €
DR1160D5	11,6	12	71	56	118	52,74 €
DR1170D5	11,7	12	71	56	118	52,74 €
DR1180D5	11,8	12	71	56	118	52,74 €
DR1190D5	11,9	12	71	56	118	52,74 €
DR1200D5	12	12	71	56	118	52,74 €
DR1220D5	12,2	14	77	60	124	69,23 €
DR1250D5	12,5	14	77	60	124	69,23 €
DR1270D5	12,7	14	77	60	124	69,23 €
DR1280D5	12,8	14	77	60	124	69,23 €
DR1300D5	13	14	77	60	124	69,23 €
DR1310D5	13,1	14	77	60	124	69,23 €
DR1350D5	13,5	14	77	60	124	69,23 €
DR1380D5	13,8	14	77	60	124	69,23 €
DR1400D5	14	14	77	60	124	69,23 €
DR1450D5	14,5	16	83	63	133	99,23 €
DR1480D5	14,8	16	83	63	133	99,23 €
DR1500D5	15	16	83	63	133	99,23 €
DR1550D5	15,5	16	83	63	133	99,23 €
DR1600D5	16	16	83	63	133	99,23 €
DR1650D5	16,5	18	93	71	143	138,72 €
DR1700D5	17	18	93	71	143	138,72 €
DR1750D5	17,5	18	93	71	143	138,72 €
DR1800D5	18	18	93	71	143	138,72 €
DR1850D5	18,5	20	101	77	153	159,17 €
DR1900D5	19	20	101	77	153	159,17 €
DR1950D5	19,5	20	101	77	153	159,17 €
DR2000D5	20	20	101	77	153	159,17 €

8XD BROCA DE METAL DURO Con refrigeración

DIN6537L

EN 8xD SOLID CARBIDE DRILL | DIN6537L | INTERNAL COOLANT

FR 8xD FORET EN CARBURE MONOBLOC | DIN6537L | AVEC TROUS DE LUBRIFICATION


DE 8xD VOLLHARTMETALLBOHRER | DIN6537L | INTEME KÜHLUNG

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.


EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusq'ua 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



ALTIN



DIN6537L

Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0300D8CH	Ø3	6	34	29	72	56,94 €
DR0310D8CH	Ø3,1	6	34	29	72	56,94 €
DR0320D8CH	Ø3,2	6	34	29	72	56,94 €
DR0330D8CH	Ø3,3	6	34	29	72	56,94 €
DR0340D8CH	Ø3,4	6	34	29	72	56,94 €
DR0350D8CH	Ø3,5	6	34	29	72	56,94 €
DR0360D8CH	Ø3,6	6	34	29	72	56,94 €
DR0370D8CH	Ø3,7	6	34	29	72	56,94 €
DR0380D8CH	Ø3,8	6	43	36	81	56,94 €
DR0390D8CH	Ø3,9	6	43	36	81	56,94 €
DR0400D8CH	Ø4	6	43	36	81	56,94 €
DR0410D8CH	Ø4,1	6	43	36	81	56,94 €
DR0420D8CH	Ø4,2	6	43	36	81	56,94 €
DR0430D8CH	Ø4,3	6	43	36	81	56,94 €
DR0440D8CH	Ø4,4	6	43	36	81	56,94 €
DR0450D8CH	Ø4,5	6	43	36	81	56,94 €
DR0460D8CH	Ø4,6	6	43	36	81	56,94 €

8XD BROCA DE METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0470D8CH	Ø4,7	6	43	36	81	56,94 €
DR0480D8CH	Ø4,8	6	57	48	95	56,94 €
DR0490D8CH	Ø4,9	6	57	48	95	56,94 €
DR0500D8CH	Ø5	6	57	48	95	56,94 €
DR0510D8CH	Ø5,1	6	57	48	95	56,94 €
DR0520D8CH	Ø5,2	6	57	48	95	56,94 €
DR0530D8CH	Ø5,3	6	57	48	95	56,94 €
DR0540D8CH	Ø5,4	6	57	48	95	56,94 €
DR0550D8CH	Ø5,5	6	57	48	95	56,94 €
DR0560D8CH	Ø5,6	6	57	48	95	56,94 €
DR0570D8CH	Ø5,7	6	57	48	95	56,94 €
DR0580D8CH	Ø5,8	6	57	48	95	56,94 €
DR0590D8CH	Ø5,9	6	57	48	95	56,94 €
DR0600D8CH	Ø6	6	57	48	95	56,94 €
DR0610D8CH	Ø6,1	8	76	66	114	77,55 €
DR0620D8CH	Ø6,2	8	76	66	114	77,55 €
DR0630DCH	Ø6,3	8	76	66	114	77,55 €
DR0640D8CH	Ø6,4	8	76	66	114	77,55 €
DR0650D8CH	Ø6,5	8	76	66	114	77,55 €
DR0660D8CH	Ø6,6	8	76	66	114	77,55 €
DR0670D8CH	Ø6,7	8	76	66	114	77,55 €
DR0680D8CH	Ø6,8	8	76	66	114	77,55 €
DR0690D8CH	Ø6,9	8	76	66	114	77,55 €
DR0700D8CH	Ø7	8	76	66	114	77,55 €
DR0710D8CH	Ø7,1	8	76	66	114	77,55 €
DR0720D8CH	Ø7,2	8	76	66	114	77,55 €
DR0730D8CH	Ø7,3	8	76	66	114	77,55 €
DR0740D8CH	Ø7,4	8	76	66	114	77,55 €
DR0750D8CH	Ø7,5	8	76	66	114	77,55 €
DR0760D8CH	Ø7,6	8	76	66	114	77,55 €
DR0770D8CH	Ø7,7	8	76	66	114	77,55 €

I 8XD BROCA DE METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR0780D8CH	Ø7,8	8	76	66	114	77,55 €
DR0790D8CH	Ø7,9	8	76	66	114	77,55 €
DR0800D8CH	Ø8	8	76	66	114	77,55 €
DR0810D8CH	Ø8,1	10	95	83	142	99,85 €
DR0820D8CH	Ø8,2	10	95	83	142	99,85 €
DR0830D8CH	Ø8,3	10	95	83	142	99,85 €
DR0840D8CH	Ø8,4	10	95	83	142	99,85 €
DR0850D8CH	Ø8,5	10	95	83	142	99,85 €
DR0860D8CH	Ø8,6	10	95	83	142	99,85 €
DR0870D8CH	Ø8,7	10	95	83	142	99,85 €
DR0880D8CH	Ø8,8	10	95	83	142	99,85 €
DR0890D8CH	Ø8,9	10	95	83	142	99,85 €
DR0900D8CH	Ø9	10	95	83	142	99,85 €
DR0910D8CH	Ø9,1	10	95	83	142	99,85 €
DR0920D8CH	Ø9,2	10	95	83	142	99,85 €
DR0930D8CH	Ø9,3	10	95	83	142	99,85 €
DR0940D8CH	Ø9,4	10	95	83	142	99,85 €
DR0950D8CH	Ø9,5	10	95	83	142	99,85 €
DR0960D8CH	Ø9,6	10	95	83	142	99,85 €
DR0970D8CH	Ø9,7	10	95	83	142	99,85 €
DR0980D8CH	Ø9,8	10	95	83	142	99,85 €
DR0990D8CH	Ø9,9	10	95	83	142	99,85 €
DR1000D8CH	Ø10	10	95	83	142	99,85 €
DR1020D8CH	Ø10,2	12	114	99	162	138,72 €
DR1040D8CH	Ø10,4	12	114	99	162	138,72 €
DR1050D8CH	Ø10,5	12	114	99	162	138,72 €
DR1080D8CH	Ø10,8	12	114	99	162	138,72 €
DR1100D8CH	Ø11	12	114	99	162	138,72 €
DR1150D8CH	Ø11,5	12	114	99	162	138,72 €
DR1180D8CH	Ø11,8	12	114	99	162	138,72 €
DR1200D8CH	Ø12	12	114	99	162	138,72 €

8XD BROCA DE METAL DURO Con refrigeración

DIN6537L



Ref.	Dimensiones (mm)					Precio €
	Dc	d	U	Lc	L	
DR1250D8CH	Ø12,5	14	133	116	178	189,77 €
DR1300D8CH	Ø13	14	133	116	178	189,77 €
DR1350D8CH	Ø13,5	14	133	116	178	189,77 €
DR1380D8CH	Ø13,8	14	133	116	178	189,77 €
DR1400D8CH	Ø14	14	133	116	178	189,77 €
DR1450D8CH	Ø14,5	16	152	132	203	263,55 €
DR1500D8CH	Ø15	16	152	132	203	263,55 €
DR1550D8CH	Ø15,5	16	152	132	203	263,55 €
DR1600D8CH	Ø16	16	152	132	203	263,55 €
DR1650D8CH	Ø16,5	18	171	149	222	359,44 €
DR1700D8CH	Ø17	18	171	149	222	359,44 €
DR1750D8CH	Ø17,5	18	171	149	222	359,44 €
DR1800D8CH	Ø18	18	171	149	222	359,44 €
DR1850D8CH	Ø18,5	20	190	170	243	428,23 €
DR1900D8CH	Ø19	20	190	170	243	428,23 €
DR1950D8CH	Ø19,5	20	190	170	243	428,23 €
DR2000D8CH	Ø20	20	190	170	243	428,23 €

07

ESCARIADORES

REAMERS
ALÉSOIRS
REIBAHLEN

ESCARIADOR DE METAL DURO Sin recubrimiento

H7

EN REAMERS | H7

FR ALÉSOIRS | H7


DE REIBAHLEN | H7

ES Acero, Acero Inoxidable, Fundición Gris, Cobre, Titanio, Aleaciones Resistentes al Calor y Aceros hasta 56 HRC.

EN Steel, Stainless Steel, Cast Iron, Cooper, Titanium, Heat Resistance Alloys and Hardened Steels up to 56 HRC.

FR Acier, Acier Inoxydable, Fonte Grise, Cuivre, Titane, Alliages de Résistance à la Chaleur et Acier Jusqu'à 56 HRC.

DE Stahl, Rostfreier Stahl, Gubeisen, Kupfer, Titan, Warmfeste Legierungen und Gehärteter Stahl 56 HRC.



HELIX 10° H7

Ref.	Dimensiones (mm)						Precio €
	D	d	L	Lc	U	Z	
RE100298	2,98	3	61	12	36	4	23,95 €
RE100299	2,99	3	61	12	36	4	23,95 €
RE100300	3,00	3	61	12	36	4	23,95 €
RE100301	3,01	3	61	12	36	4	23,95 €
RE100302	3,02	3	61	12	36	4	23,95 €
RE100350	3,50	4	70	12	40	4	25,47 €
RE100398	3,98	4	75	12	45	4	25,47 €
RE100399	3,99	4	75	12	45	4	25,47 €
RE100400	4,00	4	75	12	45	4	25,47 €
RE100400L	4,00	4	105	16	80	4	31,83 €
RE100401	4,01	4	75	12	45	4	25,47 €
RE100402	4,02	4	75	12	45	4	25,47 €
RE100450	4,50	5	80	12	52	4	26,95 €
RE100498	4,98	5	86	16	56	4	28,05 €
RE100499	4,99	5	86	16	56	4	28,05 €
RE100500	5,00	5	86	16	56	4	28,05 €
RE100500L	5,00	5	115	30	90	4	35,06 €

ESCARIADOR DE METAL DURO Sin recubrimiento

H7



Ref.	Dimensiones (mm)						Precio €
	D	d	L	Lc	U	Z	
RE100501	5,01	5	86	16	56	4	28,05 €
RE100502	5,02	5	86	16	56	4	28,05 €
RE100510	5,10	5	86	16	56	4	28,05 €
RE100520	5,20	6	86	16	56	4	28,05 €
RE100530	5,30	6	86	16	56	4	28,05 €
RE100550	5,50	6	86	16	56	4	29,95 €
RE100598	5,98	6	86	16	56	4	29,95 €
RE100599	5,99	6	86	16	56	4	29,95 €
RE100600	6,00	6	86	16	56	4	29,95 €
RE100600L	6,00	6	130	30	100	4	37,95 €
RE100601	6,01	6	86	16	56	4	29,95 €
RE100602	6,02	6	86	16	56	4	29,95 €
RE100610	6,10	6	86	16	56	4	29,95 €
RE100620	6,20	6	86	16	56	4	37,52 €
RE100630	6,30	6	86	16	56	4	37,52 €
RE100640	6,40	6	86	16	56	6	37,52 €
RE100650	6,50	8	86	16	56	6	39,23 €
RE100700	7,00	8	86	16	56	6	39,23 €
RE100700L	7,00	8	140	30	110	6	51,24 €
RE100750	7,50	8	86	16	56	6	39,23 €
RE100798	7,98	8	86	16	56	6	39,23 €
RE100799	7,99	8	86	16	56	6	39,23 €
RE100800	8,00	8	86	16	56	6	39,23 €
RE100800L	8,00	8	117	33	84	6	48,25 €
RE100800LL	8,00	8	160	30	130	6	60,31 €
RE100801	8,01	8	86	16	56	6	39,23 €
RE100801L	8,01	8	117	33	84	6	48,25 €
RE100802	8,02	8	86	16	56	6	44,92 €
RE100802L	8,02	8	117	33	84	6	52,23 €
RE100810L	8,10	8	117	33	84	6	59,31 €
RE100820L	8,20	8	117	33	84	6	59,31 €

ESCARIADOR DE METAL DURO Sin recubrimiento

H7



Ref.	Dimensiones (mm)						Precio €
	D	d	L	Lc	U	Z	
RE100830L	8,30	8	117	33	84	6	59,31 €
RE100850	8,50	8	90	20	60	6	44,92 €
RE100850L	8,50	8	117	33	84	6	59,31 €
RE100898	8,98	10	90	20	60	6	44,92 €
RE100899	8,99	10	90	20	60	6	44,92 €
RE100900	9,00	10	90	20	60	6	44,92 €
RE100900L	9,00	10	125	36	88	6	61,54 €
RE100900LL	9,00	10	160	30	130	6	76,92 €
RE100950	9,50	10	90	20	60	6	51,92 €
RE100950L	9,50	10	125	36	88	6	63,22 €
RE100998	9,98	10	90	20	60	6	51,92 €
RE100999	9,99	10	90	20	60	6	51,92 €
RE1001000	10,00	10	90	20	60	6	51,92 €
RE1001000L	10,00	10	133	38	97	6	64,40 €
RE1001000LL	10,00	10	190	30	150	6	81,55 €
RE1001001	10,01	10	90	20	60	6	51,92 €
RE1001001L	10,01	10	133	38	97	6	65,40 €
RE1001002	10,02	10	90	20	60	6	51,92 €
RE1001002L	10,02	10	133	38	97	6	65,40 €
RE1001010L	10,10	10	133	38	97	6	65,40 €
RE1001020L	10,20	10	133	38	97	6	73,45 €
RE1001030L	10,30	10	133	38	97	6	73,45 €
RE1001050	10,50	10	90	20	60	6	56,50 €
RE1001050L	10,50	10	133	38	97	6	73,45 €
RE1001100	11,00	12	90	20	60	6	56,50 €
RE1001100L	11,00	12	151	44	110	6	81,57 €
RE1001150	11,50	12	90	20	60	6	62,75 €
RE1001150L	11,50	12	151	44	110	6	81,57 €
RE1001198	11,98	12	90	20	60	6	62,75 €
RE1001199	11,99	12	90	20	60	6	62,75 €

ESCARIADOR DE METAL DURO Sin recubrimiento

H7







Ref.	Dimensiones (mm)						Precio €
	D	d	L	Lc	U	Z	
RE1001200	12,00	12	90	20	60	6	62,75 €
RE1001200L	12,00	12	151	44	110	6	81,57 €
RE1001200LL	12,00	12	220	35	170	6	101,96 €
RE1001201	12,01	12	90	20	60	6	62,75 €
RE1001201L	12,01	12	151	44	110	6	81,57 €
RE1001202	12,02	12	90	20	60	6	62,75 €
RE1001202L	12,02	12	151	44	110	6	81,57 €
RE1001250L	12,50	12	151	44	110	6	81,57 €
RE1001300	13,00	12	151	44	110	6	97,80 €
RE1001300L	13,00	12	220	35	170	6	123,25 €
RE1001301L	13,01	12	151	44	110	6	97,80 €
RE1001302L	13,02	12	151	44	110	6	97,80 €
RE1001400L	14,00	14	160	47	110	6	147,30 €
RE1001400LL	14,00	14	220	35	170	6	183,12 €
RE1001401L	14,01	14	160	47	110	6	147,30 €
RE1001402L	14,02	14	160	47	110	6	147,30 €
RE1001500L	15,00	14	162	50	112	6	159,82 €
RE1001500LL	15,00	16	220	35	170	6	198,55 €
RE1001501L	15,01	14	162	50	112	6	159,82 €
RE1001502L	15,02	14	162	50	112	6	159,82 €
RE1001600L	16,00	16	170	52	117	6	185,44 €
RE1001600LL	16,00	16	230	40	180	6	232,44 €
RE1001601L	16,01	16	170	52	117	6	185,44 €
RE1001602L	16,02	16	170	52	117	6	185,44 €
RE1001800L	18,00	18	182	56	129	6	245,55 €
RE1001800LL	18,00	18	230	40	180	6	306,33 €
RE1002000L	20,00	20	195	60	142	6	315,20 €
RE1002000LL	20,00	20	230	40	180	6	376,35 €





CONDICIONES DE CORTE

CUTTING PARAMETERS
PARAMÈTRES DE COUPE
SCHNITTDATEN





H-SEM Z2

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel -56HRC																	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)																
1	20.000	200	20000	60	20000	165	20000	120	20000	90																
2	15.000	320	11150	85	15000	285	13000	180	11140	130																
3	14000	545	7500	120	10600	420	8500	330	7430	240																
4	10800	560	5500	135	8000	425	6500	335	5570	245																
5	8200	585	4500	135	6400	445	5000	355	4460	260																
6	7000	600	3700	140	5300	465	4200	360	3710	260																
8	5200	595	2800	140	4000	455	3200	365	2785	270																
10	4200	585	2200	140	3200	445	2500	350	2230	250																
12	3500	585	1850	140	2650	445	2100	350	1855	250																
14	3000	545	1600	135	2300	420	1800	330	1590	240																
16	2600	545	1400	120	2000	420	1600	330	1390	240																
18	2300	535	1250	120	1800	415	1400	325	1240	235																
20	2050	535	1100	120	1600	415	1250	325	1115	235																
25	1650	425	880	100	1300	345	1000	260	890	185																
Max. Cutting depth																										
				<table><tr><th colspan="2">Milling Slot</th></tr><tr><th>ø</th><th>Ap</th></tr><tr><td>ø1≤ø3</td><td>0.15D</td></tr><tr><td>ø3≤ø6</td><td>0.3D</td></tr><tr><td>ø6≤D<ø20</td><td>0.5D</td></tr></table>			Milling Slot		ø	Ap	ø1≤ø3	0.15D	ø3≤ø6	0.3D	ø6≤D<ø20	0.5D	<table><tr><th colspan="2">Milling Slot</th></tr><tr><th>ø</th><th>Ap</th></tr><tr><td>ø1≤D<ø3</td><td>0.1D</td></tr><tr><td>ø3≤D</td><td>0.2D</td></tr></table>			Milling Slot		ø	Ap	ø1≤D<ø3	0.1D	ø3≤D
Milling Slot																										
ø	Ap																									
ø1≤ø3	0.15D																									
ø3≤ø6	0.3D																									
ø6≤D<ø20	0.5D																									
Milling Slot																										
ø	Ap																									
ø1≤D<ø3	0.1D																									
ø3≤D	0.2D																									




H-SEM Z4

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel -56HRC																	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)																
1	20.000	270	20000	95	20000	215	20000	135	20000	120																
2	15.000	435	11150	110	15000	380	13000	200	11140	175																
3	14000	735	7500	135	10600	565	8500	370	7430	325																
4	10800	755	5500	140	8000	575	6500	380	5570	335																
5	8200	795	4500	140	6400	605	5000	400	4460	350																
6	7000	810	3700	145	5300	620	4200	405	3710	350																
8	5200	800	2800	145	4000	615	3200	415	2785	365																
10	4200	795	2200	145	3200	605	2500	390	2230	340																
12	3500	795	1850	145	2650	605	2100	390	1855	340																
14	3000	735	1600	140	2300	565	1800	370	1590	325																
16	2600	735	1400	135	2000	565	1600	370	1390	325																
18	2300	720	1250	115	1800	555	1400	365	1240	315																
20	2050	720	1100	115	1600	555	1250	365	1115	2050																
25	1650	575	880	95	1300	445	1000	295	900	255																
Max. Cutting depth																										
				<table><tr><th colspan="2">Milling Slot</th></tr><tr><th>ø</th><th>Ap</th></tr><tr><td>ø1≤ø3</td><td>0.15D</td></tr><tr><td>ø3≤ø6</td><td>0.3D</td></tr><tr><td>ø6≤D<ø20</td><td>0.5D</td></tr></table>			Milling Slot		ø	Ap	ø1≤ø3	0.15D	ø3≤ø6	0.3D	ø6≤D<ø20	0.5D	<table><tr><th colspan="2">Milling Slot</th></tr><tr><th>ø</th><th>Ap</th></tr><tr><td>ø1≤D<ø3</td><td>0.1D</td></tr><tr><td>ø3≤D</td><td>0.2D</td></tr></table>			Milling Slot		ø	Ap	ø1≤D<ø3	0.1D	ø3≤D
Milling Slot																										
ø	Ap																									
ø1≤ø3	0.15D																									
ø3≤ø6	0.3D																									
ø6≤D<ø20	0.5D																									
Milling Slot																										
ø	Ap																									
ø1≤D<ø3	0.1D																									
ø3≤D	0.2D																									

H-SEM Z3

Workpiece material	Cast iron, Nodular cast iron		Carbon steel, Alloy steel -750Nmm²		Carbon steel, Alloy steel -30HRC		Pre-hardened steel, Quenched and tempered steel -40HRC		Stainless steel		Pre-Hardened steel, Quenched and tempered steel -56HRC								
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)							
1	20.000	215	20000	215	20000	175	20000	175	20000	65	20000	130							
2	15.000	345	15000	345	15000	310	15000	305	11150	90	13000	195							
3	14000	590	14000	590	13000	546	10600	455	7500	130	8500	360							
4	10800	600	10800	605	10000	560	8000	460	5500	145	6500	365							
5	8200	630	8200	630	7600	585	6400	480	4500	145	5000	380							
6	7000	650	7000	650	6400	600	5300	500	3700	150	4200	390							
8	5200	645	5200	645	4800	590	4000	495	2800	150	3200	400							
10	4200	630	4200	630	3800	585	3200	480	2200	150	2500	380							
12	3500	630	3500	630	3200	585	2650	480	1850	150	2100	380							
14	3000	590	3000	590	2700	545	2300	455	1600	145	1800	360							
16	2600	590	2600	590	2400	545	2000	455	1400	130	1600	360							
18	2300	580	2300	580	2100	530	1800	450	1250	130	1400	350							
20	2050	580	2050	580	1900	530	1600	450	1100	130	1250	350							
25	1650	465	1650	465	1520	425	1300	370	880	110	1000	280							
Max. Cutting depth																			
						<table><tr><th colspan="2">Milling Slot</th></tr><tr><th>Ø</th><th>Ap</th></tr><tr><td>Ø1 ≤ Ø3</td><td>0.15D</td></tr><tr><td>Ø3 ≤ D</td><td>0.3D</td></tr></table>					Milling Slot		Ø	Ap	Ø1 ≤ Ø3	0.15D	Ø3 ≤ D	0.3D	
Milling Slot																			
Ø	Ap																		
Ø1 ≤ Ø3	0.15D																		
Ø3 ≤ D	0.3D																		

H-HEM Z6


Workpiece material	Pre-hardened steel, Hardened steel 40-50HRC		Hardened steel 50-60HRC		Hardened steel 60-65HRC	
Cutting Speed	300m/min		150m/min		100m/min	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	29.135	3380	14625	1690	9685	1130
4	22.940	2660	11515	1330	7625	890
5	18880	2180	9440	1090	6250	732
6	16000	1850	8000	925	5300	610
8	12000	1850	6000	925	4000	610
10	9600	1850	4800	925	3200	610
12	8000	1920	4000	960	2700	650
14	6800	1600	3400	815	2300	550
16	6000	1440	3000	720	2000	480
18	5300	1270	2700	635	1800	430
20	4800	1150	2400	575	1600	385
25	4250	1025	2120	510	1420	340
Max. Cutting depth	$a_e = 0.05D$  Máx. A_c - 1.0 mm.		$a_e = 0.03D$  Máx. A_c - 0.5 mm.		$a_e = 0.02D$  Máx. A_c - 0.2 mm.	

FRESAS Z1 ALUMINIO



Workpiece material	Aleaciones de Aluminio, <6% Si		Aleaciones de Aluminio, <6-12% Si	
Cutting Speed	300m/min		150m/min	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	32.000	480	21000	200
4	24.000	600	16000	290
5	19100	580	12700	300
6	16000	560	10600	300
8	12000	540	8000	280
10	9500	525	6400	255
12	8000	560	5300	265

Profundidad de corte: e: 1xD Ap.: 0,5xD

I A-SEM Z2

Workpiece material	Aluminum alloy		Silicon aluminium alloy Si≤10%	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	26500	1500	21000	1100
4	20000	1600	16000	1250
5	16000	1500	13000	1100
6	13000	1250	10600	1000
8	10000	1400	8000	1100
10	8000	1600	6500	1250
12	6600	1650	5300	1300
14	5700	1700	4600	1350
16	5000	1700	4000	1350
20	4000	1700	3200	1350
Max. Cutting depth				


A-SEM Z3 / A-SEM Z3-R

Workpiece material	Aluminum alloy		Silicon aluminium alloy Si≤10%	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	26500	1800	21000	1300
4	20000	2000	16000	1500
5	16000	1750	13000	1300
6	13000	1500	10600	1200
8	10000	1650	8000	1300
10	8000	1900	6500	1500
12	6600	1950	5300	1550
14	5700	2000	4600	1600
16	5000	2000	4000	1600
20	4000	2000	3200	1600
Max. Cutting depth	 $a_e = 0.1D$ $a_p = 1.5D$  $a_e = 1D$ $a_p = 0.6D$			



A-SBM Z2

Workpiece material	Aluminum alloy		Silicon aluminium alloy Si≤10%	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	26500	1950	21000	1550
4	20000	1950	16000	1550
5	16000	1950	13000	1550
6	13000	2000	10600	1600
8	10000	2450	8000	2000
10	8000	2200	6500	1750
12	6600	2050	5300	1650
14	5700	2000	4600	1600
16	5000	1950	4000	1550
20	4000	1900	3200	1520



Max. Cutting depth





H-HEM Z6 LARGA

Workpiece material	Pre-hardened steel, Hardened steel 40-50HRC		Hardened steel 50-60HRC		Hardened steel 60-65HRC	
Cutting Speed	300m/min		150m/min		100m/min	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	29.135	2380	14625	1190	9685	795
4	22.940	1875	11515	935	7625	626
5	18880	1535	9440	770	6250	515
6	16000	1300	8000	650	5300	430
8	12000	1300	6000	650	4000	430
10	9600	1300	4800	650	3200	430
12	8000	1350	4000	670	2700	460
14	6800	1150	3400	570	2300	380
16	6000	1000	3000	500	2000	340
18	5300	890	2700	450	1800	300
20	4800	800	2400	400	1600	270
25	4250	720	2120	360	1420	240
32	3900	680	2000	320	1350	190
Max. Cutting depth	 $a_e = 0.02D$ $a_p = 3D$ Máx. A_c - 0.3 mm.		 $a_e = 0.01D$ $a_p = 3D$			


I BW-SEM

Workpiece material	Cast Iron, Nodular cast iron		Carbon steel, Alloy steel -750Nmm ²		Carbon steel, Alloy steel -30 HRC		Pre-hardened steel, Quenched and tempered steel 40-50HRC		Stainless steel	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
6	6350	760	5300	640	4500	360	3450	280	2650	210
8	4750	760	4000	640	3400	410	2650	310	2000	240
10	3800	760	3200	640	2400	430	2050	330	1600	260
12	3200	770	2250	650	1950	470	1500	360	1150	280
14	2800	770	2125	650	1825	470	1400	360	1075	280
16	2400	770	2000	640	1700	480	1300	360	1000	280
20	1900	760	1600	610	1350	470	1050	350	800	260
Max. Cutting depth										


I M-SEM Ø4

Workpiece material	Pre-hardened steel, Hardened steel -40HRC		Hardened steel 40-56HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
0.2	32.000	150	25000	120
0.3	32.000	150	25000	120
0.4	32000	200	25000	160
0.5	21000	400	17000	300
0.6	21000	480	17000	380
0.7	20000	520	14000	360
0.8	20000	560	14000	400
0.9	17000	560	12000	400
Max. Cutting depth				

■ H-SEM Ø6

Workpiece material		Pre-hardened steel, Hardened steel -40HRC			Hardened steel 40-56HRC		
Diameter Ø (mm)	Effective length(mm)	Rotating (min ⁻¹)	Feed (mm/min)	Ap (mm)	Feed (mm/min)	Rotating (min ⁻¹)	Ap (mm)
1.0	5	17000	400	0.03	12000	100	0.014
	12	12000	150	0.01	10000	50	0.008
1.5	5	12000	400	0.06	8000	200	0.028
	12	10000	300	0.025	7000	100	0.01
2.0	10	7000	300	0.10	6000	200	0.05
	16	7000	200	0.02	6000	100	0.008
3.0	10	7000	400	0.12	5000	300	0.06
	16	6000	300	0.06	5000	200	0.03
4.0	12	4500	400	0.16	4000	300	0.08
	20	4500	300	0.10	4000	300	0.04
Max. Cutting depth							


H-MEM

Workpiece material		Pre-hardened steel, Hardened steel 40-50HRC		Hardened steel 50-62HRC	
Diameter Ø (mm)	Effective length(mm)	Rotating (min ⁻¹)	Feed (mm/min)	Feed (mm/min)	Rotating (min ⁻¹)
0.5	4	28000	150	25000	100
	6	22000	100	20000	75
0.6	4	28000	150	25000	100
	6	22000	100	20000	75
	8	22000	75	18000	75
0.8	6	26000	200	21000	150
	8	22000	125	18000	100
	10	22000	75	18000	75
1.2	6	22000	400	17000	300
	8	19000	300	14000	200
	10	19000	300	14000	200
Max. Cutting depth					

H-SBM

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 56-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
1.0	40000	960	22300	240	32000	385	25000	330	22280	295
1.5	32.000	1020	16500	255	24000	435	19000	330	16700	295
2.0	24000	1080	11150	275	16000	480	13000	330	11140	295
2.5	15500	1150	5550	445	8000	665	6500	450	5570	385
3.0	15500	1150	5550	445	8000	665	6500	450	5570	385
4.0	11500	1150	5550	445	8000	665	6500	450	5570	385
5.0	9500	1270	4450	445	6400	665	5000	455	4455	405
6.0	8000	1270	3700	470	5300	700	4200	470	3715	420
8.0	6000	1575	2750	550	4000	850	3200	535	2785	465
10	4800	1455	2200	520	3200	785	2500	535	2230	465
12	4000	1330	1850	520	2650	740	2100	505	1855	450
14	3500	1300	1550	500	2400	730	1800	475	1670	425
16	3000	1270	1350	455	2000	725	1600	455	1395	395
18	2700	1200	1250	455	1800	700	1400	425	1275	375
20	2400	1150	1100	445	1600	675	1250	400	1115	360


Max. Cutting depth




H-NBM

Workpiece material		Pre-hardened steel, Hardened steel 40-50HRC				Hardened steel 50-62HRC			
Diameter Ø (mm)	Effective length(mm)	Rotating (min ⁻¹)	Feed (mm/min)	Ap (mm)	Ae (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Ap (mm)	Ae (mm)
1	5	16000	200	0.05	0.10	11500	150	0.05	0.10
	12	14000	135	0.01	0.03	9800	75	0.01	0.03
2	10	10000	275	0.08	0.16	5500	175	0.08	0.16
	14	10000	275	0.06	0.16	5500	175	0.06	0.16
	16	10000	250	0.02	0.10	5500	150	0.02	0.10
	35	8000	175	0.02	0.05	5500	125	0.01	0.05
2.5	20	5500	175	0.02	0.05	5000	125	0.01	0.05
3	9	7500	400	0.15	0.30	4000	200	0.15	0.30
	15	6500	250	0.05	0.20	3000	150	0.05	0.20
	20	6500	250	0.02	0.10	3000	150	0.02	0.05
	40	5000	200	0.02	0.1	2500	100	0.02	0.05
4	12	6000	400	0.20	0.40	3000	200	0.20	0.40
	20	5000	250	0.10	0.20	2500	100	0.10	0.20
5	20	4000	250	0.25	0.50	3000	100	0.20	0.2




Max. Cutting depth






H-CBM

Workpiece material		Pre-hardened steel, Hardened steel 40-50HRC				Hardened steel 50-62HRC			
Diameter Ø (mm)	Effective length(mm)	Rotating (min ⁻¹)	Feed (mm/min)	Ap (mm)	Ae (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Ap (mm)	Ae (mm)
1	20	22000	450	0.02	0.1	22000	345	0.02	0.1
1.5	20	20000	750	0.03	0.15	20000	700	0.03	0.15
2	20	18000	1000	0.05	0.2	18000	800	0.05	0.2
	40	18000	750	0.03	0.2	18000	600	0.05	0.2
3	30	16000	1200	0.1	0.3	16000	960	0.1	0.3
	50	16000	850	0.03	0.3	16000	680	0.03	0.3
4	30	14000	1400	0.15	0.4	14000	1120	0.15	0.4
	60	14000	1100	0.1	0.4	14000	880	0.1	0.4
5	60	11700	1400	0.25	0.5	11700	880	0.25	0.5
Max. Cutting depth									
									




TORICA Z2

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 56-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
1	20000	240	20000	75	20000	195	20000	145	20000	95
1.5	17000	300	15500	90	17000	260	16000	180	15500	110
2	15000	385	11150	100	15000	335	13000	215	11140	130
3	14000	655	7500	145	10600	505	8500	395	7430	245
4	10800	675	5500	155	8000	515	6500	405	5570	245
5	8200	695	4500	155	6400	540	5000	425	4460	260
6	7000	720	3700	170	5300	555	4200	435	3710	260
8	5200	720	2800	170	4000	555	3200	440	2785	275
10	4200	695	2200	170	3200	535	2500	420	2230	255
12	3500	695	1850	170	2650	535	2100	420	1855	255
Max. Cutting depth										




TORICA Z4

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 56-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
2	15000	950	9500	175	15000	720	13000	550	9500	400
3	14000	985	7500	175	10600	755	8500	590	7430	435
4	10800	1010	5500	175	8000	770	6500	600	5570	445
5	8200	1055	4500	175	6400	805	5000	640	4460	470
6	7000	1080	3700	195	5300	830	4200	650	3710	470
8	5200	1070	2800	195	4000	815	3200	660	2785	485
10	4200	1055	2200	195	3200	805	2500	625	2230	450
12	3500	1055	1850	195	2650	805	2100	625	1855	450
Max. Cutting depth										



H-CEM Z2

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 56-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
2	15000	385	11150	100	15000	335	13000	215	11140	130
3	14000	655	7500	145	10600	505	8500	395	7430	245
4	10800	675	5500	155	8000	515	6500	405	5570	245
5	8200	695	4500	155	6400	540	5000	425	4460	260
6	7000	720	3700	170	5300	555	4200	435	3710	260
8	5200	720	2800	170	4000	555	3200	440	2785	275
Max. Cutting depth										

H-CEM Z4

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless steel		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 56-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
2	15000	950	9500	175	15000	720	13000	550	9500	400
3	14000	985	7500	175	10600	755	8500	590	7430	435
4	10800	1010	5500	175	8000	770	6500	600	5570	445
5	8200	1055	4500	175	6400	805	5000	640	4460	470
6	7000	1080	3700	195	5300	830	4200	650	3710	470
8	5200	1070	2800	195	4000	815	3200	660	2785	485
Max. Cutting depth										

■ HYRUX / HYPERLINK

												
		Fresado lateral A y B, Ranurado C										
		A		B		C		Velocidad de corte vc m/min				
		ap	ae	ap	ae	ap		min	max	mm		
P	1	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		150	220	fz		
	2	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		150	200	fz		
	3	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		120	170	fz		
	4	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		110	160	fz		
	5	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		70	90	fz		
M	1	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		90	115	fz		
	2	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		80	100	fz		
	3	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		95	125	fz		
K	1	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		180	220	fz		
	2	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		150	180	fz		
	3	2 x D	0,1-0,2 x D	1,5 x D	0,5 x D	1 x D		120	150	fz		
S	1	2 x D	0,1 x D	1,5 x D	0,5 x D	1 x D		60	100	fz		
	2	2 x D	0,1 x D	1,5 x D	0,5 x D	1 x D		50	80	fz		
	3	2 x D	0,1 x D	1,5 x D	0,3 x D	0,3 x D		30	50	fz		
	4	2 x D	0,1 x D	1,5 x D	0,3 x D	0,3 x D		25	40	fz		
H	1	2 x D	0,1 x D	1,5 x D	0,3 x D	0,75 x D		80	110	fz		

P1	Non alloyed steel <700 N/mm ²
P2	Low alloyed steel <24HRC 700-1000 N/mm ²
P3	High alloyed steel <30HRC <700 N/mm ²
P4	Hardened steel 30-38HRC
P5	Hardened steel 38-48HRC
M1	Stainless steel, austenitic 500-950 N/mm ²
M2	Stainless steel, ferritic, martensitic 500-950 N/mm ²
M3	Stainless steel, martensitic 800-1000 N/mm ²
K1	Grey Cast Iron, 100-400 N/mm ²
K2	Alloyed grey-Nodular cast Iron, 200-800 N/mm ²
K3	Malleable cast iron, 350-700 N/mm ²
S1	Titanium alloys, medium strength, -950N/mm ²
S2	Titanium alloys, high strength, 900-1400N/mm ²
S3	Nickel based Alloys, medium strength -950N/mm ²
S4	Heat resistant Nickel based Alloys, high strength 900-1400 N/mm ²
H1	Hardened steel 48-56HRC

Avance por diente recomendado (f_z =mm/diente) para fresado lateral (A) y (B). Para ranurado C, reduzca el valor f_z en un 20%.

D1 / Diametro

3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	20,0
0,022	0,028	0,035	0,045	0,06	0,07	0,08	0,09	0,1	0,11
0,022	0,028	0,035	0,045	0,06	0,07	0,08	0,09	0,1	0,11
0,022	0,028	0,035	0,045	0,06	0,07	0,08	0,09	0,1	0,11
0.018	0.023	0.030	0.035	0.050	0.060	0.070	0.080	0.09	0.10
0.015	0.017	0.025	0.030	0.040	0.050	0.055	0.065	0.07	0.08
0.018	0.023	0.030	0.035	0.050	0.060	0.070	0.080	0.09	0.10
0,022	0,028	0,035	0,045	0,06	0,07	0,08	0,09	0,1	0,11
0.020	0.025	0.030	0.035	0.045	0.07	0.075	0.09	0.095	0.105
0,022	0,028	0,035	0,045	0,06	0,07	0,08	0,09	0,1	0,11
0.018	0.023	0.030	0.035	0.050	0.060	0.070	0.080	0.09	0.10
0.018	0.023	0.030	0.035	0.050	0.060	0.070	0.080	0.09	0.10
0,022	0,028	0,035	0,035	0,05	0,06	0,06	0,1	0,1	0,11
0.015	0.020	0.025	0.025	0.04	0.040	0.040	0.06	0.06	0.07
0,022	0,028	0,035	0,035	0,05	0,06	0,06	0,1	0,1	0,11
0.015	0.020	0.025	0.025	0.04	0.040	0.040	0.06	0.06	0.07
0.018	0.023	0.030	0.035	0.050	0.060	0.070	0.080	0.09	0.10

T-SEM (TURBO)


Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Pre-hardened steel, Quenched and tempered steel -40HRC		Pre-hardened steel, Quenched and tempered steel -45HRC		Pre-hardened steel, Quenched and tempered steel -50HRC		Hardened steel 55-62HRC	
Diameter Ø (mm)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)	Rotating (min ⁻¹)	Feed (mm/min)
3	10500	6250	8500	4500	7450	3900	5300	2600	3200	995
4	7.950	6600	6350	4800	5550	4200	4000	2750	2400	1050
6	5300	7000	4250	5100	3700	4450	2650	2850	1600	1150
8	4550	7000	3200	5100	2800	4450	2000	2850	1200	1150
10	3200	7000	2550	5100	2250	4450	1600	2850	955	1150
12	2650	7000	2100	5100	1850	4450	1350	2850	795	1150
	max Ap: 0.5mm Ae: 0.5D Ap: 0.2R		max Ap: 0.5mm Ae: 0.5D Ap: 0.2R		max Ap: 0.5mm Ae: 0.5D Ap: 0.2R		max Ap: 0.4mm Ae: 0.5D Ap: 0.2R		max Ap: 0.2mm Ae: 0.5D Ap: 0.2R	

FRESA ACHAFLANAR

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless Steel		Pre-hardened steel, Quenched and tempered steel 40-55HRC		Non ferrite materials	
Diameter Ø (mm)	Vc (m/min)	fz (mm/z)	Vc (m/min)	fz (mm/z)	Vc (m/min)	fz (mm/z)	Vc (m/min)	fz (mm/z)
4	90	0.02	60-90	0.02	70-120	0.02	200-280	0.02
6	90	0.03	60-90	0.03	70-120	0.03	200-280	0.03
8	90	0.04	60-90	0.04	70-120	0.04	200-280	0.04
10	90	0.05	60-90	0.05	70-120	0.05	200-280	0.05
12	90	0.06	60-90	0.06	70-120	0.06	200-280	0.06
16	90	0.08	60-90	0.08	70-120	0.08	200-280	0.08

FRESA TROCOIDAL - 3XD

Workpiece material	Cast iron, Carbon steel, Alloy steel -30 HRC		Stainless Steel		Pre-hardened steel, Quenched and tempered steel 30-40HRC		Pre-hardened steel, Quenched and tempered steel 45-55HRC	
6	250-350	0.065	150-220	0.055	150-230	0.055	55-75	0.050
8	250-350	0.075	150-220	0.065	150-230	0.065	55-75	0.060
10	250-350	0.100	150-220	0.080	150-230	0.080	55-75	0.070
12	250-350	0.120	150-220	0.100	150-230	0.100	55-75	0.090
16	250-350	0.150	150-220	0.130	150-230	0.130	55-75	0.110
20	250-350	0.200	150-220	0.170	150-230	0.170	55-75	0.130



BROCA 3D / 5D

Work-piece material	Mild steel HB≤180		Carbon steel, alloy steel -30HRC		Pre-hardened steel 40-50HRC		Stainless steel		Cash iron		Nodular Cash iron GGG		Aluminum alloy		Heat resistant alloy	
Vc	60-120m/min		60-120m/min		40-70 m/min		25-40 m/min		60-120 m/min		50-100 m/min		60-140 m/min		12-25 m/min	
Ø (mm)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)
3	9500	0.09-0.12	9500	0.09-0.12	6300	0.09-0.12	3700	0.03-0.07	9500	0.09-0.12	7400	0.09-0.12	10600	0.09-0.12	2100	0.03-0.06
4	7000	0.10-0.15	7000	0.10-0.15	4700	0.10-0.15	2700	0.04-0.08	7000	0.10-0.15	5600	0.10-0.15	8000	0.10-0.15	1600	0.04-0.07
5	5700	0.12-0.18	5700	0.12-0.18	3800	0.12-0.18	2200	0.05-0.10	5700	0.12-0.18	4500	0.12-0.18	6400	0.12-0.18	1250	0.05-0.09
6	4700	0.14-0.20	4700	0.14-0.20	3100	0.14-0.20	1850	0.06-0.12	4700	0.14-0.20	3700	0.14-0.20	5300	0.14-0.20	1050	0.06-0.11
8	3600	0.16-0.24	3600	0.16-0.24	2400	0.16-0.24	1400	0.08-0.16	3600	0.16-0.24	2800	0.16-0.24	4000	0.16-0.24	800	0.08-0.14
10	2800	0.18-0.27	2800	0.18-0.27	1900	0.18-0.27	1100	0.10-0.18	2800	0.18-0.27	2200	0.16-0.27	3200	0.18-0.27	600	0.10-0.16
12	2400	0.20-0.30	2400	0.20-0.30	1600	0.20-0.30	930	0.12-0.20	2400	0.20-0.30	1900	0.20-0.30	2700	0.20-0.30	500	0.12-0.18
14	2100	0.22-0.35	2100	0.22-0.35	1400	0.22-0.35	800	0.13-0.22	2100	0.22-0.35	1600	0.22-0.35	2300	0.22-0.35	450	0.13-0.20
16	1800	0.25-0.36	1800	0.25-0.36	1200	0.25-0.36	700	0.14-0.25	1800	0.25-0.36	1400	0.25-0.36	2000	0.25-0.36	400	0.14-0.25
18	1600	0.28-0.38	1600	0.28-0.38	1100	0.28-0.38	620	0.15-0.28	1600	0.28-0.38	1200	0.28-0.38	1800	0.28-0.38	350	0.15-0.25
20	1400	0.30-0.40	1400	0.30-0.40	950	0.30-0.40	550	0.16-0.30	1400	0.30-0.40	1100	0.30-0.40	1600	0.30-0.40	320	0.16-0.20

BROCA 5D REFRIGERADA

Work-piece material	Mild steel HB≤180		Carbon steel, alloy steel -30HRC		Pre-hardened steel 40-50HRC		Stainless steel		Cash iron		Nodular Cash iron GGG		Aluminum alloy		Heat resistant alloy	
Vc	80-150m/min		80-150m/min		50-80 m/min		50-80 m/min		80-150 m/min		60-120 m/min		100-120 m/min		12-25 m/min	
Ø (mm)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)
3	12700	0.09-0.12	12700	0.09-0.12	7400	0.09-0.12	6300	0.03-0.07	12700	0.09-0.12	9500	0.09-0.12	15000	0.09-0.12	2100	0.03-0.06
4	9600	0.10-0.15	9600	0.10-0.15	5600	0.10-0.15	4700	0.04-0.08	9600	0.10-0.15	7000	0.10-0.15	11100	0.10-0.15	1600	0.04-0.07
5	7600	0.12-0.18	7600	0.12-0.18	4500	0.12-0.18	3800	0.05-0.10	7600	0.12-0.18	5700	0.12-0.18	9000	0.12-0.18	1250	0.05-0.09
6	6400	0.14-0.20	6400	0.14-0.20	3700	0.14-0.20	3200	0.06-0.12	6400	0.14-0.20	4700	0.14-0.20	7400	0.14-0.20	1050	0.06-0.11
8	4800	0.16-0.24	4800	0.16-0.24	2800	0.16-0.24	2400	0.08-0.16	4800	0.16-0.24	3600	0.16-0.24	5600	0.16-0.24	800	0.08-0.14
10	3800	0.18-0.27	3800	0.18-0.27	2200	0.18-0.27	1900	0.10-0.18	3800	0.18-0.27	2800	0.16-0.27	4500	0.18-0.27	600	0.10-0.16
12	3200	0.20-0.30	3200	0.20-0.30	1900	0.20-0.30	1600	0.12-0.20	3200	0.20-0.30	2400	0.20-0.30	3700	0.20-0.30	500	0.12-0.18
14	2700	0.22-0.35	2700	0.22-0.35	1600	0.22-0.35	1350	0.13-0.22	2700	0.22-0.35	2100	0.22-0.35	3200	0.22-0.35	450	0.13-0.20
16	2400	0.25-0.36	2400	0.25-0.36	1400	0.25-0.36	1200	0.14-0.25	2400	0.25-0.36	1800	0.25-0.36	2800	0.25-0.36	400	0.14-0.25
18	2100	0.28-0.38	2100	0.28-0.38	1200	0.28-0.38	1050	0.15-0.28	2100	0.28-0.38	1600	0.28-0.38	2500	0.28-0.38	350	0.15-0.25
20	1900	0.30-0.40	1900	0.30-0.40	1100	0.30-0.40	950	0.16-0.30	1900	0.30-0.40	1400	0.30-0.40	2300	0.30-0.40	320	0.16-0.20

BROCA 8D REFRIGERADA

Work-piece material	Mild steel HB≤180		Carbon steel, alloy steel -30HRC		Pre-hardened steel 40-50HRC		Stainless steel		Cash iron		Nodular Cash iron GGG		Aluminum alloy		Heat resistant alloy	
Vc	80-150m/min		80-150m/min		50-80 m/min		40-60 m/min		80-150 m/min		60-120 m/min		100-180 m/min		15-25 m/min	
Ø (mm)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)	n (min ⁻¹)	f (mm/r)
3	12700	0.06-0.10	12700	0.06-0.10	7400	0.06-0.10	5300	0.03-0.07	12700	0.06-0.10	9500	0.06-0.10	15000	0.09-0.12	2100	0.03-0.06
4	9600	0.08-0.12	9600	0.08-0.12	5600	0.08-0.12	4000	0.04-0.08	9600	0.08-0.12	7000	0.08-0.12	11100	0.10-0.15	1600	0.04-0.07
5	7600	0.10-0.14	7600	0.10-0.14	4500	0.10-0.14	3200	0.05-0.10	7600	0.10-0.14	5700	0.10-0.14	9000	0.10-0.14	1250	0.05-0.09
6	6400	0.11-0.16	6400	0.11-0.16	3700	0.11-0.16	2700	0.06-0.12	6400	0.11-0.16	4700	0.11-0.16	7400	0.11-0.16	1050	0.06-0.11
8	4800	0.13-0.19	4800	0.13-0.19	2800	0.13-0.19	2000	0.08-0.16	4800	0.13-0.19	3600	0.13-0.19	5600	0.13-0.19	800	0.08-0.14
10	3800	0.14-0.22	3800	0.14-0.22	2200	0.14-0.22	1600	0.10-0.18	3800	0.14-0.22	2800	0.14-0.22	4500	0.14-0.22	600	0.10-0.16
12	3200	0.16-0.24	3200	0.16-0.24	1900	0.16-0.24	1300	0.12-0.20	3200	0.16-0.24	2400	0.16-0.24	3700	0.16-0.24	500	0.12-0.18
14	2700	0.18-0.28	2700	0.18-0.28	1600	0.18-0.28	1100	0.13-0.22	2700	0.18-0.28	2100	0.18-0.28	3200	0.18-0.28	450	0.13-0.20
16	2400	0.20-0.29	2400	0.20-0.29	1400	0.20-0.29	1000	0.14-0.25	2400	0.20-0.29	1800	0.20-0.29	2800	0.20-0.29	400	0.14-0.23
18	2100	0.24-0.32	2100	0.24-0.32	1200	0.24-0.32	880	0.15-0.28	2100	0.24-0.32	1600	0.24-0.32	2500	0.24-0.32	350	0.15-0.25

■ ESCARIADOR

Workpiece material	Steel <1000 N/mm ² , Cast Iron, Modular cast iron			Copper alloy			Aluminium alloy		
V _c	8-16 m/min			10-25 m/min			15-30 m/min		
Ø (mm)	n (min ⁻¹)	f (mm/r)	Tolerance (mm)	n (min ⁻¹)	f (mm/r)	Tolerance (mm)	n (min ⁻¹)	f (mm/r)	Tolerance (mm)
3	1150	0.03-0.05	0.1-0.2	1900	0.03-0.05	0.1-0.2	2400	0.03-0.05	0.1-0.2
4	950	0.04-0.06	0.1-0.2	1600	0.04-0.06	0.1-0.2	2000	0.04-0.06	0.1-0.2
5	760	0.05-0.09	0.1-0.2	1300	0.05-0.09	0.1-0.2	1600	0.05-0.09	0.1-0.2
6	640	0.06-0.12	0.1-0.2	1050	0.06-0.12	0.1-0.2	1300	0.06-0.12	0.1-0.2
7	550	0.07-0.14	0.1-0.2	910	0.07-0.14	0.1-0.2	1150	0.07-0.14	0.1-0.2
8	480	0.08-0.16	0.1-0.2	800	0.08-0.16	0.1-0.2	1000	0.08-0.16	0.1-0.2
9	430	0.09-0.18	0.1-0.2	710	0.09-0.18	0.1-0.2	890	0.09-0.18	0.1-0.2
10	380	0.10-0.20	0.1-0.2	640	0.10-0.20	0.1-0.2	800	0.10-0.20	0.1-0.2
11	350	0.11-0.22	0.1-0.2	580	0.11-0.22	0.1-0.2	720	0.11-0.22	0.1-0.2
12	320	0.12-0.24	0.1-0.2	530	0.12-0.24	0.1-0.2	660	0.12-0.24	0.1-0.2
13	290	0.13-0.26	0.1-0.2	490	0.13-0.26	0.1-0.2	610	0.13-0.26	0.1-0.2
14	270	0.14-0.28	0.1-0.2	460	0.14-0.28	0.1-0.2	570	0.14-0.28	0.1-0.2
15	250	0.15-0.30	0.1-0.2	430	0.15-0.30	0.1-0.2	530	0.15-0.30	0.1-0.2
16	240	0.16-0.32	0.1-0.2	400	0.16-0.32	0.1-0.2	500	0.16-0.32	0.1-0.2
17	225	0.18-0.34	0.1-0.2	380	0.18-0.34	0.1-0.2	470	0.18-0.34	0.1-0.2
18	210	0.20-0.36	0.1-0.2	350	0.20-0.36	0.1-0.2	440	0.20-0.36	0.1-0.2
19	200	0.22-0.34	0.1-0.2	340	0.22-0.34	0.1-0.2	420	0.22-0.34	0.1-0.2
20	190	0.24-0.40	0.1-0.2	320	0.24-0.40	0.1-0.2	400	0.24-0.40	0.1-0.2



CATÁLOGO de productos

PRODUCT CATALOGUE
CATALOGUE DES PRODUITS
PRODUKTKATALOG



Meatz Erreka 11 bgo
ARRASATE-MONDRAGON
20500 (GIPUZKOA) SPAIN
Tel.: +34 943 79 10 22
Mail: info@arralbe.com

www.arralbe.com